
ADDITIONAL TMA REQUIRED ON
FREEWAYS ONLY, TO PREVENT
VEHICLES FROM ENTERING WORK AREA

CLASS 2 MOBILE SCENARIO

VEHICLES TRAVELLING GREATER THAN 20km/h BELOW THE SPEED LIMIT
(NO WORKERS ON FOOT)
TRUCK MOUNTED ATTENUATOR.

→ ACING E)	← SHUNT → DISTANCE
---------------------------------	----------------------------------

MA REQUIRED ON
LY, TO PREVENT
M ENTERING WORK AREA
VARIO
BELOW THE SPEED LIMIT
OR.

CONVOY
ANCE SPACING
FER TABLE)

DOCUMENTATION

DAILY RECORDS OF THE SITE LAYOUT INCLUDING DEVICES, SIGHT DISTANCE, RISK ASSESSMENTS, SIGNS OR TGS, MUST BE KEPT IN A DIARY OR IN WORK SHEETS (DAILY DAIRY). ANY SIGNIFICANT DEPARTURES FROM OR ADDITIONS TO, THE SIGNS AND DEVICES INCLUDED IN THIS DIAGRAM SHOULD BE NOTED AND APPROVED.

DRAWING NO	0922-01531-MS2-006	REVISION	6
------------	--------------------	----------	---

8