

The diagram illustrates the Class 2 Mobile Scenario for a road closure. It shows a sequence of vehicles from left to right: an Advanced Warning Vehicle, a Shadow Vehicle, a Work Vehicle, and a Lead Vehicle. Above each vehicle is its corresponding signage. The Advanced Warning Vehicle has a Flashing Arrow Board and a Variable Message Board with two displays: '40 AHEAD' and 'WORKS IN LANE AHEAD'. The Shadow Vehicle has a Flashing Arrow Board and a Variable Message Board with two displays: '40' and 'ROAD PLANT AHEAD'. The Work Vehicle has a Flashing Arrow Board and a Variable Message Board with one display: 'END 40'. The Lead Vehicle has a Flashing Arrow Board and a Variable Message Board with one display: 'END 40'. The vehicles are spaced according to 'CONVOY DISTANCE SPACING (REFER TABLE)'. A 40m distance is indicated between the Shadow Vehicle and the Work Vehicle. Red arrows on the right side of the road indicate the direction of traffic flow. A note at the bottom right states: 'WORKS CONVOY TO STRADDLE LANE LINE, MINIMUM 3.0m LANE MUST BE PROVIDED FOR VEHICLES TO PASS ON THE RIGHT SIDE OF THE CONVOY'.

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
40
AHEAD

VARIABLE MESSAGE BOARD
DISPLAY 2
WORKS
IN LANE
AHEAD

ADVANCED WARNING VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
40

VARIABLE MESSAGE BOARD
DISPLAY 2
ROAD
PLANT
AHEAD

SHADOW VEHICLE

40m

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
END
40

WORK VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
END
40

LEAD VEHICLE

WORKS CONVOY TO STRADDLE LANE LINE, MINIMUM 3.0m LANE MUST BE PROVIDED FOR VEHICLES TO PASS ON THE RIGHT SIDE OF THE CONVOY

CLASS 2 MOBILE SCENARIO
VEHICLES TRAVELLING GREATER THAN 20km/h BELOW THE SPEED LIMIT
(NO WORKERS ON FOOT)

The diagram illustrates the 'CLASS 2 MOBILE SCENARIO' for a truck-mounted attenuator (TMA) on a road. It shows a sequence of vehicles from left to right: an 'ADVANCED WARNING VEHICLE', a 'WORK VEHICLE', and a 'LEAD VEHICLE'. Above each vehicle are its respective signs and lighting configurations.

- ADVANCED WARNING VEHICLE:** Features a 'FLASHING ARROW BOARD' and a 'VARIABLE MESSAGE BOARD' with two displays. Display 1 shows a '40' speed limit sign with 'AHEAD' below it. Display 2 shows 'WORKS IN LANE AHEAD' in orange text.
- WORK VEHICLE:** Features a 'FLASHING ARROW ON TMA' and a 'VARIABLE MESSAGE BOARD' with two displays. Display 1 shows a '40' speed limit sign. Display 2 shows 'ROAD PLANT AHEAD' in orange text.
- LEAD VEHICLE:** Features a 'FLASHING ARROW BOARD' and a 'VARIABLE MESSAGE BOARD' with one display showing 'END' above a '40' speed limit sign.

Below the vehicles, a road layout shows the spacing between them. Arrows indicate 'CONVOY DISTANCE SPACING (REFER TABLE)' between the Advanced Warning Vehicle and the Work Vehicle, and between the Work Vehicle and the Lead Vehicle. A 'SHUNT DISTANCE' is also indicated between the Work Vehicle and the Lead Vehicle. Red arrows on the right side of the road indicate traffic flow.

Text at the bottom right states: 'WORKS CONVOY TO STRADDLE LANE LINE, MINIMUM 3.0m LANE MUST BE PROVIDED FOR VEHICLES TO PASS ON THE RIGHT SIDE OF THE CONVOY'.

CLASS 2 MOBILE SCENARIO
 VEHICLES TRAVELLING GREATER THAN 20km/h BELOW THE SPEED LIMIT
 (NO WORKERS ON FOOT)
 TRUCK MOUNTED ATTENUATOR.

DAILY RECORDS OF THE SITE LAYOUT INCLUDING DEVICES, SIGHT DISTANCE, RISK ASSESSMENTS, SIGNS OR TGS, MUST BE KEPT IN A DIARY OR IN WORK SHEETS (DAILY DIARY). ANY SIGNIFICANT DEPARTURES FROM, OR ADDITIONS TO, THE SIGNS AND DEVICES INCLUDED IN THIS DIAGRAM SHOULD BE NOTED AND APPROVED.

DRAWING NO	0922-01531-MS2-014	REVISION	6
------------	--------------------	----------	---