

FLASHING ARROW BOARD

FLASHING CORNERS

VARIABLE MESSAGE BOARD

DISPLAY 1

DISPLAY 2

ROAD WORK AHEAD

EMERGENCY LANE CLOSED

ADVANCED WARNING VEHICLE

CONVOY DISTANCE SPACING (REFER TABLE)

40M

SHADOW VEHICLE

FLASHING ARROW BOARD

FLASHING CORNERS

VARIABLE MESSAGE BOARD

DISPLAY 1

DISPLAY 2

EMERGENCY LANE CLOSED

ROAD PLANT AHEAD

WORK VEHICLE

CONVOY DISTANCE SPACING (REFER TABLE)

LEAD VEHICLE

FLASHING ARROW BOARD

FLASHING CORNERS

VARIABLE MESSAGE BOARD

DISPLAY 1

END ROAD WORK

LEAD VEHICLE

The diagram illustrates the layout of the Advanced Warning Vehicle (AWV) and the Work Vehicle (WV) for the flashing arrow board (FAB) and the flashing arrow on TMA (FATMA) configurations. The diagram shows the relative positions of the FAB, the Variable Message Board (VMB), and the vehicles, along with the required spacing and distances.

FLASHING ARROW BOARD (FAB) Configuration:

- FLASHING ARROW BOARD:** A black rectangular board with four yellow flashing corners.
- VARIABLE MESSAGE BOARD (VMB):** Two displays showing "ROAD WORK AHEAD" and "EMERGENCY LANE CLOSED".
- ADVANCED WARNING VEHICLE (AWV):** A white vehicle with a yellow flashing arrow on the roof.
- CONVOY DISTANCE SPACING (REFER TABLE):** The distance between the AWV and the WV.
- SHUNT DISTANCE:** The distance between the FAB and the WV.

FLASHING ARROW ON TMA (FATMA) Configuration:

- FLASHING ARROW ON TMA:** A black rectangular board with four yellow flashing corners.
- VARIABLE MESSAGE BOARD (VMB):** Two displays showing "EMERGENCY LANE CLOSED" and "ROAD PLANT AHEAD".
- WORK VEHICLE (WV):** A white vehicle with a yellow flashing arrow on the roof.
- CONVOY DISTANCE SPACING (REFER TABLE):** The distance between the WV and the FAB.

FLASHING ARROW BOARD (FAB) Configuration (Lead Vehicle):

- FLASHING ARROW BOARD:** A black rectangular board with four yellow flashing corners.
- VARIABLE MESSAGE BOARD (VMB):** One display showing "END ROAD WORK".
- LEAD VEHICLE:** A white vehicle with a yellow flashing arrow on the roof.
- CONVOY DISTANCE SPACING (REFER TABLE):** The distance between the WV and the FAB.
- LEAD VEHICLE OPTIONAL SUBJECT TO AWTM RISK ASSESSMENT:** A note indicating that the lead vehicle is optional and subject to AWTM risk assessment.

WORKS PROTECTED BY SHADOW VEHICLE

DISTANCE BETWEEN VEHICLES IN MOBILE CONVOY - EXCLUDING SHADOW VEHICLE

EXISTING ROAD



**METROPOLITAN REGIONS
TRAFFIC MANAGEMENT BRANCH**

WATERLOO CRESCENT
TELEPHONE (08) 138 138

EAST PERTH 6004

DATE OF DRAWING 2025 JULY	SCALE -
------------------------------	------------

LOCAL GOVERNMENT AUTHORITY	POSTED SPEED
-	-

ROAD AUTHORITY	WORKSITE SPEED
MAIN ROADS WA	-

CHECKED BY TYLER HARTLEY	SIGNATURE 
------------------------------------	--

ACCREDITATION	1 gler hunting
RTM-0066	

DESIGNED BY MICHAEL REED	SIGNATURE 
------------------------------------	--

THOMAS L. REED ACCREDITATION AWTM-23-11536-02	
--	---

AWT11201000002	GENERIC TRAFFIC GUIDANCE SCHEME CLASS 2 - MOBILE SCENARIOS EMERGENCY LANE CONVOY WORK VEHICLES ONLY	
----------------	--	--

DRAWING NO	0922-01531-MS2-021	REVISION	6
------------	--------------------	----------	---