

- the length of the single lane or shuttle flow segment is 120 m or less, and
- there is sight distance to opposing traffic of at least 200 m beyond the far end of the work area for traffic facing the GIVE WAY, ONE LANE assembly.
- No specific traffic control signs are required for the single lane section, and traffic operates under natural give and take using the one open lane and either one of the following applies:
 - it is a residential street (permanent posted speed is 50 km/h or less) and there is clear visibility past the work area and beyond it for at least 75 m, or to the end of the road if less than 75 m away and the length of the shuttle lane does not exceed 60 m, or
 - road users have clear visibility of the work area and the opposing approach for a distance greater than 150 m or to the end of the road if less than 150 m away, the traffic volume in both directions is 40 vph or less, the permanent posted speed is 70 km/h or less, and the length of the shuttle lane is 60 m or less.

Addition

Where active traffic control is not provided (working under natural give and take, or where GIVE WAY and ONE LANE signs are in operation), the taper should be at 45 degrees on both the approach and departure sides of the work area and the remaining open single lane section should have a maximum width of 3.5 m. See QGTTM Part 3 Figure 5.4.4(a) for an example layout.

Difference

In the subsection '**Other traffic assessment elements – Lane widths**'

Replace Table 3.6 with the following:

Table 3.6 – Lane widths

Criteria	Lane width (m)
General lane widths	
≤60 km/h	Minimum 3.0*
70, 80 or 90 km/h	Minimum 3.2*
≥100 km/h	Minimum 3.4*
Curve with radius 100–250 m	Add curve widening of 0.5 m per lane