

Table 2.5 – Lane widths

Criteria	Lane width (m)
General lane widths	
≤60 km/h	Minimum 3.0*
70, 80 or 90 km/h	Minimum 3.2*
≥100 km/h	Minimum 3.4*
Curve with radius 100–250 m	Add curve widening of 0.5 m per lane
Curve with radius <100 m	In addition to the curve widening of 0.5 m per lane, consider the swept path of long vehicles (for example, buses, trams)
Two-way residential street	Minimum of 5.5 (sum both ways)
Shuttle flow operation	
Shuttle flow with active control (by traffic controllers or PTCDs)	Minimum 3.0*
Shuttle flow, without active control on residential streets, includes no control or the use of GIVE WAY and ONE WAY signs (see Section 5.4.4).	Minimum 3.0* and Maximum 3.5 to ensure vehicles take turns using a single lane

*Temporary minimum lane widths are not to be greater than existing lane widths. This minimum temporary lane width does not apply to curves of radius 250 m or less, or locations where there are fixed vertical obstructions such as fences or safety barriers within 30 cm of the edge of the lane on one or both sides. Where these conditions apply, consider widths wider than those listed previously to accommodate large vehicles. The speed to be used when considering lane width requirements is the speed limit (permanent or reduced) which is applicable to that length of road.

Consideration must also be given to cyclists and pedestrians (see Sections 3.10, 4.10 and 5.13 for further details on traffic management regarding pedestrians and cyclists).

When selecting lane widths, especially when travel paths are confined on each side by physical barriers and / or hazards (e.g. excavations or safety barriers) for a significant distance, it is important to consider any impact of breakdowns and congestion for emergency vehicle access and on traffic flow. Refer to QGTMM Part 2 Section 3.3.4 for more detail.