

with:

Detour markers must be erected at all subsequent changes of direction. Detour markers should also be installed at intersections along the route where drivers may consider turning or where they may require reassurance that they are on the correct detour path (e.g. detour in a built-up area through side streets) and they can continue their journey using permanent road sign information. This usually involves directing road users back onto their original route of travel at a point past the worksite. Signs must be erected for each direction of travel affected by the closure and checked to ensure all detour signs are prominently displayed with clear sight distance (see Section 2.5.3 Table 2.3).

Difference

Replace:

END DETOUR sign must be placed at the end of the detour, indicating to road users that they have returned to their original route and permanent signs can be followed.

with:

END DETOUR sign should be placed at the end of the detour, indicating to road users that they have returned to their original route and permanent signs can be followed.

Addition

For detour routes that include a U-turn requirement, these should only be used where a U-turn would normally be permitted (excluding signals which are not operating and are under other controls such as Police or Traffic Controllers who can manage the need for the U-turn movement). Where a U-turn would not normally be permitted, the turning paths and characteristics of the expected vehicle types should be reviewed in conjunction with advice from the RIM. A U-TURN NOT SUITABLE FOR LONGER VEHICLES (TC1972) sign may be required.

3.9 Termination Area

Addition

Additional guidance is provided in Section 5.12.