

- The swept path must accommodate heavy and over-dimensional vehicles if required.
- Active traffic control (by traffic controllers or PTCs) must be provided at each end of the operation (see Section 5.10), except as follows:
 - GIVE WAY and ONE LANE signs are provided at one end of the shuttle lane and the NO OVERTAKING OR PASSING sign is also to be erected at the start of the single lane for traffic in the opposite direction and all the following apply:
 - traffic volume in both directions is 150 vph or less
 - the traffic speed is 70 km/h or less
 - each entry to the work area is visible from the other
 - the length of the single lane or shuttle flow segment is 120 m or less, and
 - there is sight distance to opposing traffic of at least 200 m beyond the far end of the work area for traffic facing the GIVE WAY, ONE LANE assembly.
 - No specific traffic control signs are required for the single lane section, and traffic operates under natural give and take using the one open lane and either one of the following applies:
 - it is a residential street (permanent posted speed is 50 km/h or less) and there is clear visibility past the work area and beyond it for at least 75 m, or to the end of the road if less than 75 m away and the length of the shuttle lane does not exceed 60 m, or
 - road users have clear visibility of the work area and the opposing approach for a distance greater than 150 m or to the end of the road if less than 150 m away, the traffic volume in both directions is 40 vph or less, the permanent posted speed is 70 km/h or less, and the length of the shuttle lane is 60 m or less.
- Where active traffic control is not provided (working under natural give and take, or where GIVE WAY and ONE LANE signs are in operation), the taper should be at 45 degrees on both the approach and departure sides of the work area and the remaining open single lane section should have a maximum width of 3.5 m. See Figure 5.4.4(a) for an example layout.
- Single-lane section lengths should not exceed the recommended maximum distance as shown in Table 5.4.