

For shuttle flow operations, the traffic control taper must start a minimum of 6 m from the traffic controller or PTCD.

Difference

Replace the title for Table 5.8:

Table 5.8: Distance between tapers

with

Table 5.8: Minimum distance between tapers

Difference

Replace the text following Table 5.8:

The speed to use in Table 2.2 and 5.8 must be as per Figure 2.2 of Section 2.5.3.

For details on how to use delineation devices see Section 5.4.

with

The speed value used in Tables 5.7 and 5.8 shall be as per Figure 2.2 of Section 2.5.3 – the 200 m zone in Figure 2.2 applies to the recommended length and recommended spacing of tapers.

For the spacing of delineation devices at tapers, see Section 5.4. The 200 m zone in Figure 2.2 does not apply to delineation spacing.

Where the posted permanent speed limit of the road is 80 km/h or greater, the recommended taper length for merge tapers (Table 5.7) and the recommended distance between merge tapers (Table 5.8) may be increased and be based on the posted permanent speed limit of the road.

Addition

In subsection '**Merge taper**', add the following:

When signing merge tapers, the multi-message signs on each side of the multilane road on approach to the merge taper may be different. The MERGE LEFT / MERGE RIGHT panel should be included with the lane status panel for the lane which is required to merge (must change lanes); however, for the lane where no action is required as this lane continues, the MERGE LEFT / MERGE RIGHT panel may be replaced with either a DO NOT OVERTAKE or MERGE IN TURN panel as shown in the following Figure 5.9.1(a).