

5.10.1 Portable traffic control devices

Difference

Replace Section 5.10.1 with the following:

PTCDs are used to enhance the safety and protection of road users and road workers, specifically traffic controllers.

When using PTCDs, and situations occur where vehicles can bypass the temporary traffic control station, the placement of additional cones along the centreline must be installed to provide a sufficient distance to prevent the vehicle passing the PTCD. Prior to including a PTCD in a TGS, a risk assessment must be undertaken to ensure the suitability and choice of PTCD. Other considerations that impact the choice of a PTCD are as follows:

1. impacts of equipment failure on road workers and road users; employ back-up traffic controllers in case of failure
2. background impacts on the visibility of the PTCDs for approaching road users
3. clear visibility and available sight distance (see Section 2.5.4); install PTCDs on the left-hand side of each approach – if they are not readily visible in that location, they should be placed in a more visible position
4. speed of traffic
5. traffic volumes
6. duration of works, and
7. whether or not the PTCD needs to be operated when unattended.

PTCD options include:

8. portable traffic signal systems (PTSS):
 - a) intended for shuttle flow (see Section 5.4.4) or gating (all stop) operation
 - b) available to provide control at intersections (see [Guideline – Traffic Management at Works on Roads](#) Chapter 5 Clause 2.5.3.1)
 - c) signals automatically respond to traffic demands via vehicle actuated operation (unmanned)
 - d) option of fixed time operation that used fixed timed cycles when traffic flow is relatively constant