

5.10.2 Traffic controllers

Difference

Replace the entire Section 5.10.2 with the following:

Worksites are hazardous areas so use manual traffic control only where PTCDs are insufficient to provide the safety, capacity and efficiency required for effective traffic control. When traffic controllers are used, traffic controllers cannot direct a road user to contradict upcoming intersection signals. Traffic controllers are to coordinate activities with operating signals. If traffic controllers are operating within close proximity to a signalised intersection and the lights are flashing yellow or are off, a traffic controller must only control one lane and the approach to this intersection must be reduced to one lane of traffic. Where works cause delays to traffic flow, or a side road intersects the worksite, do not use an automated PTCD, a traffic controller using a STOP/SLOW bat or controlling a PTCD is required. The following requirements and recommendations apply when using traffic controllers:

- Only competent persons with appropriate certification must be appointed as a traffic controller (see AGTTM Part 7).
- Speed must be 60 km/h maximum. Provide a temporary speed limit of 60 km/h or less on the approach to a traffic controller if the speed is higher (see Section 5.5.1).
- An escape route must be identified for each traffic controller from their traffic control position.
- Traffic controllers must be positioned a clear sight distance from approaching road users (see Section 2.5.4) with no obstruction and where they are not obstructing visibility to traffic control devices (i.e. signs). No obstruction should be located in the area between the traffic controller and the end of the line of four cones.
- Ensure that a work vehicle is not parked in a way that impacts the visibility of the traffic controller or, limits the traffic controller's escape route or, is parked between the traffic controller and the taper.
- Ensure that traffic controllers are visible at all times of the day, particularly at dawn, dusk, against low morning or evening sun, when in the shade on a sunny day or working in dusty conditions.