

6.10.4 Lateral placement

Difference

Replace item (c):

Where practicable, the portable VMS should be positioned behind semi-rigid or rigid protection (e.g. guard fence, wire rope).

with:

Where practicable, the TVMS should be positioned behind semi-rigid or rigid protection (for example, guard fence, wire rope) and outside the appropriate deflection zone clearance area behind the barrier.

Addition

Add after the dot points:

The TVMS should be located in accordance with the provisions of this section (items (a) to (e), as applicable) or outside the applicable clear zone (see Section 6.11).

The further a TVMS can be located from the traffic lane (lateral clearance, see Figure 6.12), the less likely it will be impacted by errant vehicles; however, to perform satisfactorily, the TVMS must be located where drivers will easily see and read the messages displayed.

6.10.6 Other location requirements

New

Subject to the requirements in the previous section, the TVMS should be located so that it does not interfere with, or block visibility to, other official roadside signs and roadside advertising devices. It may be necessary to also consider impact for drivers approaching the rear of the TVMS.

Sight lines for road users from adjoining roads or driveways should also be considered.

Where the TVMS is to be located near a roadside advertising billboard, the requirements of the [Roadside Advertising Manual](#), Clause 2.1.2.2 and Appendix C should be considered, with the TVMS desirably being located outside any restriction areas for the billboard if practicable.