

Table 6.11.2 – Clear zone distances from edge of through travelled way (extracted from Table 3.1 (AASHTO 2011))

Design speed (km/h)	Design ADT	Clear zone width (m)					
		Fill batter			Cut batter		
		6:1 to flat	4:1 to 5:1	3:1 and steeper ⁽²⁾	6:1 to flat	4:1 to 5:1	3:1 and steeper ⁽²⁾
≤ 60	< 750	3.0	3.0	(2)	3.0	3.0	3.0
	750 – 1500	3.5	4.5	(2)	3.5	3.5	3.5
	1501 – 6000	4.5	5.0	(2)	4.5	4.5	4.5
	> 6000	5.0	5.5	(2)	5.0	5.0	5.0
70 – 80	< 750	3.5	4.5	(2)	3.5	3.0	3.0
	750 – 1500	5.0	6.0	(2)	5.0	4.5	3.5
	1501 – 6000	5.5	8.0	(2)	5.5	5.0	4.5
	> 6000	6.5	8.5	(2)	6.5	6.0	5.0
90	< 750	4.5	5.5	(2)	3.5	3.5	3.0
	750 – 1500	5.5	7.5	(2)	5.5	5.0	3.5
	1501 – 6000	6.5	9.0	(2)	6.5	5.5	5.0
	> 6000	7.5	10.0 ⁽¹⁾	(2)	7.5	6.5	5.5
100	< 750	5.5	7.5	(2)	5.0	4.5	3.5
	750 – 1500	7.5	10.0 ⁽¹⁾	(2)	6.5	5.5	4.5
	1501 – 6000	9.0	12.0 ⁽¹⁾	(2)	8.0	6.5	5.5
	> 6000	10.0 ⁽¹⁾	13.5 ⁽¹⁾	(2)	8.5	8.0	6.5
110	< 750	6.0	8.0	(2)	5.0	5.0	3.5
	750 – 1500	8.0	11.0 ⁽¹⁾	(2)	6.5	6.0	5.0
	1501 – 6000	10.0 ⁽¹⁾	13.0 ⁽¹⁾	(2)	8.5	7.5	6.0
	> 6000	10.5 ⁽¹⁾	14.0 ⁽¹⁾	(2)	9.0	9.0	7.5

Notes:

- Where a site-specific investigation indicates a high probability of continuing crashes, or such occurrences are indicated by crash history, the designer may provide clear zone distances greater than the clear zone shown in this Table.
- Since recovery is less likely on the unshielded, traversable 3:1 slopes, fixed objects should not be present in the vicinity of the toe of these slopes. Recovery of high-speed vehicles that encroach beyond the edge of the shoulder may be expected to occur beyond the toe of the slope. Determination of the recovery area at the toe of the slope should take into consideration available road reservation, environmental concerns, economic factors, safety needs, and crash histories. Also, the distance between the edge of the travelled lane and the beginning of the 3:1 slope should influence the recovery area provided at the toe of the slope. While the application may be limited by several factors, the fill slope parameters which may enter into determining a maximum desirable recovery area are illustrated in Figure 6.11.2(f).
- The design ADT in the table is the average daily traffic volume in both directions and in all lanes, other than for divided roads where it is the total traffic in all lanes in one direction.
- Where the road is curved the values in Table 6.11.2 should be adjusted by the curve correction factors in Figure 6.11.2(c).
- Design speeds used in Table 6.11.2 are to be determined in accordance with Section 2.5.9 *Speed*.