

The distance between the advance warning vehicle and shadow vehicle is 90 metres for this example.

3.7.2 Signs mounted on vehicles

Difference

Replace:

Vehicle mounted warning devices fitted with illuminated arrow signs must be fitted to all convoy vehicles and plant items. This excludes small plant items protected by a work vehicle and shadow vehicle. The sign mounted to the vehicle and illuminated flashing arrow sign must be the minimum size of:

with:

Vehicle mounted warning devices fitted with illuminated arrow signs must be fitted to all TTM vehicles in the convoy.

All work vehicles and items of plant in the mobile works convoy, other than minor items of plant protected by a works vehicle or a shadow vehicle, must display a vehicle-mounted warning device which when suitable may be fitted with an illuminated flashing arrow sign.

The sign mounted to the vehicle and illuminated flashing arrow sign must be the minimum size of:

Deletion

In subsection **Vehicle mounted warning device**, delete the first paragraph:

All vehicles and items of plant in the mobile works convoy, other than minor items of plant protected by a works vehicle and shadow vehicle must carry a vehicle-mounted warning device fitted with an illuminated flashing arrow sign.

Addition

In subsection **Vehicle mounted warning device**, add the following:

On two-way roads, vehicle mounted warning devices fitted with illuminated arrow signs must be visible to road users from both approaches where warning for both approaches is required (see Figure 3.9).