

# Contents

|                                                                        |            |
|------------------------------------------------------------------------|------------|
| <b>About this document</b> .....                                       | <b>i</b>   |
| <b>How to use this document</b> .....                                  | <b>i</b>   |
| <b>References</b> .....                                                | <b>ii</b>  |
| <b>Relationship table (harmonised to AGTTM05-21 Edition 1.1)</b> ..... | <b>iii</b> |
| <b>1 Introduction</b> .....                                            | <b>1</b>   |
| 1.3 Scope of Part 5.....                                               | 1          |
| <b>2 Design process</b> .....                                          | <b>1</b>   |
| 2.1 General .....                                                      | 1          |
| 2.2 Risk assessment.....                                               | 2          |
| 2.4 Essential design principles .....                                  | 2          |
| 2.4.2 <i>Signs</i> .....                                               | 2          |
| 2.4.4 <i>Lane width</i> .....                                          | 3          |
| 2.5 Variations to design .....                                         | 3          |
| <b>3 General considerations</b> .....                                  | <b>3</b>   |
| 3.1 Restrictions on use .....                                          | 3          |
| 3.2 Short-term low-impact options.....                                 | 4          |
| 3.4 Vehicle Mounted Warning Device .....                               | 5          |
| 3.6 Combining different works protection methods.....                  | 6          |
| <b>4 Works on road – within traffic lane</b> .....                     | <b>7</b>   |
| 4.1 Work protected by specialist vehicles .....                        | 7          |
| 4.1.2 <i>Truck-mounted attenuators</i> .....                           | 7          |
| 4.2 Works between gaps in traffic .....                                | 7          |
| 4.2.2 <i>Criteria</i> .....                                            | 7          |
| 4.2.3 <i>Traffic control devices</i> .....                             | 7          |
| 4.2.4 <i>Pre-installation processes</i> .....                          | 7          |
| 4.2.5 <i>Installation (TGS instruction)</i> .....                      | 8          |
| 4.3 Short term works in traffic .....                                  | 8          |
| 4.3.3 <i>Traffic control devices</i> .....                             | 8          |
| 4.3.4 <i>Pre-installation processes</i> .....                          | 8          |
| 4.3.5 <i>Installation (TGS instruction)</i> .....                      | 9          |
| 4.4 Frequently changing work area – in lane .....                      | 10         |
| 4.4.1 <i>Description</i> .....                                         | 10         |
| 4.4.3 <i>Traffic control devices</i> .....                             | 10         |
| 4.4.5 <i>Installation (TGS instruction)</i> .....                      | 10         |
| 4.5 Constantly moving work area – in lane.....                         | 11         |
| 4.5.1 <i>Description</i> .....                                         | 11         |