

2.4.4 Lane width

Difference

Replace Table 2.4 with the following.

Table 2.4 – Lane widths

Criteria	Lane width (m)
General lane widths	
≤60 km/h	Minimum 3.0*
70, 80 or 90 km/h	Minimum 3.2*
≥100 km/h	Minimum 3.4*
Curve with radius 100–250 m	Add curve widening of 0.5 m per lane
Curve with radius <100 m	In addition to the curve widening of 0.5 m per lane, consider the swept path of long vehicles (for example, buses, trams)
Two-way residential street	Minimum of 5.5 m (sum both ways)

*Temporary minimum lane widths are not to be greater than the existing lane widths. This minimum temporary lane width does not apply to curves of radius 250 m or less, or locations where there are fixed vertical obstructions such as fences or safety barriers within 30 cm of the edge of the lane on one or both sides. Where these conditions apply, consider widths wider than those listed above to accommodate large vehicles.

2.5 Variations to design

Addition

Refer to Clause 1.9 of the Queensland MUTCD Part 3.

3 General considerations

3.1 Restrictions on use

Difference

Replace:

Regardless of any risk assessment, if the speed limit, traffic volume, traffic clearance or occupation time constraints specified in this Part cannot be met, treatments of a fully protected static worksite (see AGTTM Part 3) or mobile works convoy (see AGTTM Part 4) must be applied. For many Category 3 roads, jurisdictions have determined that requirements of Part 5 are not applicable, instead choosing to undertake certain maintenance activities using static worksite practices, covered under Part 3 or Mobile work practices covered under Part 4.