

3.4 Vehicle Mounted Warning Device

Difference

Replace entire Section 3.4 with the following:

A vehicle mounted warning device provides advance warning and information to road users regarding works being carried out and any hazard.

A vehicle mounted warning device must consist of one of the following arrangements in Table 3.4:

Table 3.4 – Vehicle mounted warning devices

Arrangement	Vehicle Mounted Warning Device (VMWD)	Use conditions / requirements
1	A single flashing yellow lamp or LED light assembly	- For emergency or other infrequent use on a vehicle not normally used for either roadworks or inspection purposes. - For use on a plant item working within a static work area.
2	A pair of flashing yellow lamps or LED light assemblies (placed as far apart as practical)	- For use on vehicles on all roads without the protection of a static roadworks site. - Positioned on the vehicle so that at least one, and preferably both lamps are visible to all road users from any direction. - Additional flashing yellow lamp(s) or LED assemblies may be required to be added on the vehicle to ensure visibility is provided to all road users in any direction.
3	An illuminated flashing arrow sign (see Queensland MUTCD Part 3 Clause 4.14.2)	- For any situation where option 1 or 2 is not appropriate. - May be used for any type of work (including mobile works). - May be used in combination with options 1 or 2. - If required, supplementary signs (static or variable message signs) are mounted in conjunction or elsewhere in a prominent position on the vehicle. - The illuminated flashing arrow sign must be capable of being removed from view (e.g. covering, folding down, or turning off) when not needed.