

6.2 Road lighting or signal works

6.2.1 Description and criteria

New

Prior to undertaking these work activities, a risk assessment must be undertaken to ensure the works can be safely completed. Risk considerations are outlined in Section 2.2.1.

Examples of work appropriate for this treatment include, but are not limited to, maintenance and installation of power poles, lights, wires and traffic signals.

Road lighting or signal works may be undertaken by workers on foot with a vehicle equipped with a vehicle-mounted warning device (see Section 3.4) without the use of advance warning signs under the following conditions:

- a) where the vehicle is positioned where parking is legal and the safety of other road users is not compromised, and the vehicle does not obstruct the traffic flow:
 - i. the maximum work period at any one location must be one hour, and
 - ii. a minimum clearance of 5.5 m must be maintained above the road surface to any part of the maintenance vehicle that encroaches upon the open traffic lane, or
- b) where the vehicle is positioned other than outlined in Item a):
 - i. the maximum work period at any one location must be:
 - A. five minutes if on the roadway or within 1.2 m of moving traffic, or
 - B. 20 minutes if within 3 m of moving traffic but more than 1.2 m from moving traffic, and
 - ii. the following sight distance to the vehicle-mounted warning device for approaching drivers must be:
 - A. in a residential street, 75 m or to the end of the street, or
 - B. in all other locations, a minimum as per Table 6.2.1(a), and