

- iii. the vehicle-mounted warning device must not be obscured by either overhanging vegetation or a raised truck body, and
- iv. the work must not reduce:
 - A. the overall width to less than required for safe passage for two-way traffic (or one-way traffic if the volume is less than 50 vehicles per day), or
 - B. the running lane width adjacent to a barrier line to less than that needed to allow vehicles to proceed without crossing the line.
- c) A lookout person must be posted to warn workers on foot of the approach of any vehicle whose size or speed may constitute a safety threat. The lookout person is not required if the works are more than 1.2 m clear of moving traffic.

If required, the lookout person must be positioned adjacent to the worker so that they can view approaching traffic in time to warn workers to vacate the roadway before arrival of traffic. The recommended sight distance at which the lookout person should be able to see approaching traffic is as per Table 6.2.1(b). This distance allows for the worker to respond to a warning and vacate the roadway.

When using lookouts in Queensland, additional guidance and requirements for the Lookout Protection Method, in the [*Guideline – Traffic Management at Works on Roads*](#) must be applied.

The works vehicle placement should consider the effect on vulnerable road users including cyclists and the road workers should always have a clear exit path from the road and ensure that this is not blocked by the placement of the work vehicle.

Road lighting or signal works do not require a TGS when the works are completed in accordance with this section; however, a TGS may be developed and included in a generic TGS selection system for road lighting or signal works activities.

Vehicles used to install signage and equipment must, at a minimum, have a yellow flashing lamp(s) visible to all approaching traffic.

Before any equipment or materials are brought onto the work area, a visual check of the worksite traffic management set-up (vehicle-mounted warning devices and lookout (if required) are in place, and sight distance requirements are met) should be made in all directions, including all side roads and property accesses if required. This is to confirm that the work area is safe for all workers and road users, and signs and devices are placed as required by this section, or as indicated on the TGS (if provided).

Where the requirements of this section or another suitable section in this Part cannot be met, the treatments of a fully-protected static worksite (see QGTTM Part 3) or mobile works convoy (see QGTTM Part 4) must be applied.