

The following method must be used by traffic controllers to control traffic on multilane roads:

Changing from SLOW to STOP in LANE A

- to stop vehicles in LANE A, the first traffic controller must turn the bat to show the “STOP” sign and, while remaining outside the travel path (on shoulder, closed lane/s or footpath), face the oncoming traffic
- the first traffic controller must raise their free hand into the stop signal position with the palm towards the traffic.

Holding vehicles in LANE A

- the first traffic controller must keep facing the stationary vehicles and where possible allow 2-3 vehicles to stop before stepping in front of the stationary vehicles in LANE A
- the first traffic controller must be positioned approximately 10 m in front of the first stationary vehicle in LANE A
- the first traffic controller must ensure that the bat’s “STOP” sign continues to face the stationary traffic in LANE A.

Stopping vehicles in LANE B

- the second traffic controller must move to a position alongside the first traffic controller who is situated in front of the traffic in LANE A. The second traffic controller must be nearer to the lane to be stopped next
- the second traffic controller must ensure that the bat is indicating “STOP” to the stationary traffic in LANE A
- while remaining outside the travel path of vehicles in LANE B, the second traffic controller raises their free hand into the stop signal position with the palm towards the traffic in LANES A and B.

Holding vehicles in LANE B

- where possible, the second traffic controller allows 2-3 vehicles to stop before stepping in front of the stationary vehicles at LANE B
- the second traffic controller must keep facing the stationary vehicles with the bat displaying the “STOP” sign to the stationary vehicles in LANE B
- the second traffic controller must be positioned approximately 10 m in front of the first stationary vehicle in LANE B
- the second traffic controller must ensure that the bat’s “STOP” sign continues to face the stationary traffic.

Stopping vehicles in LANE C

- the third traffic controller must move to a position alongside the second traffic controller who is situated in front of the traffic in LANE B. The third traffic controller must be nearer to the lane to be stopped next
- the third traffic controller must ensure that the bat is indicating “STOP” to the stationary traffic in LANE B
- while remaining outside the travel path of vehicles in LANE C, the third traffic controller raises their free hand into the stop signal position with the palm towards the traffic in LANES B and C.