

Holding vehicles in LANE C

- where possible, the third traffic controller allows 2-3 vehicles to stop before stepping in front of the stationary vehicles at LANE C
- the third traffic controller must keep facing the stationary vehicles with the bat displaying the “STOP” sign to the stationary vehicles in LANE C
- the third traffic controller must be positioned approximately 10 m in front of the first stationary vehicles in LANE C
- the third traffic controller must ensure that the bat’s “STOP” sign continues to face the stationary traffic.

Changing from STOP to SLOW

- each traffic controller must check that the work area is clear behind them and that no vehicles or persons are turning into or approaching the respective lanes
- while keeping the “STOP” sign facing the stationary vehicles:
 - the traffic controller in LANE C then moves to a position outside the travelled path and positions the bat so that the drivers cannot see the STOP / SLOW bat
 - the traffic controller in LANE B then moves to a position outside the travelled path and positions the bat so that the drivers cannot see the STOP / SLOW bat
- the traffic controller in LANE A then moves to a position outside the travelled path, and facing the traffic, the traffic controller turns the bat to the “SLOW” sign and gives the TO GO signal, thus indicating to the drivers of the vehicles in all LANES that they may proceed slowly.

2.9.8 At or near traffic signals

When a traffic controller is operating at or near traffic signals, it is recommended the following conditions apply:

- traffic signals must be turned off (or turned to flashing amber) when traffic controllers are operating at a signalised intersection, or near, being within 50 m of a signalised intersection
- if the works are expected to interfere in any way with the operation of the traffic signals (i.e. turning them off, to flashing amber, masking displays, moving traffic lanes so that detectors are no longer functional, generating traffic queues through the intersection), ensure that appropriate approvals have been provided by the relevant authorities
- signals must be switched off or covered and traffic controlled manually by traffic controllers stationed at each intersection approach, releasing traffic one approach at a time
- switching of traffic signals to flashing amber or modification to traffic signal operation settings is only to be undertaken by the relevant authority
- if there is a risk of motorists departing the traffic-controlled section and ignoring nearby traffic signals after reading the hand-held “SLOW” sign, an additional traffic controller must be stationed at the approach of the signals (from the works), to display a hand-held “STOP” sign when the traffic signals display red
- if the conditions only allow one traffic controller to work on a multilane road, the approach should be reduced to a single lane
- if traffic controllers are using a STOP / SLOW bat to control traffic at an intersection, they must have the “SLOW” sign covered or removed to ensure that vehicles on other approaches do not proceed into the intersection.