

Entire clause now located in Queensland MUTCD to make it easier for the end user to use the document. No longer needing to go back and forth between the Queensland MUTCD and Australian Standard several times.

Information which was remaining in AS 1742.3 has been relocated to the Queensland MUTCD and is highlighted blue.

Added guidance in item g) on the recommended location of a 600x600 yellow retroreflective blank panel.

See changes highlighted yellow following.

4 Function, description and use of standard signs and devices

4.2 Selection and use

4.2.2 Multi-message signs

Difference

Replace the entire Clause 4.2.2 with the following:

Multi-message signs offer an alternative sign display to that of standard signs in the Temporary (T Series), Regulatory (R Series), Warning (W Series) and Traffic Instruction (G Series) which are displayed singularly or sometimes as two signs with related messages. Multi-message signs, designated within the TM, RM, WM and GM Series, allow for the display of up to three logically related messages within a single uniform modular frame (see Clause 4.5.2).

Additional multi-message sign panels in common use for which there are no standard sign alternatives may be selected from Appendix A.

Further multi-message sign panels may be developed by state and territory authorities. Where this occurs, the sign specifications, conditions of use and permissible panel combinations should be consistently applied across all jurisdictions.

The conditions of use for multi-message signs are as follows, except when used to control pedestrians only:

- a) Multi-message sign shall have relevant messages consisting of a minimum of —
 - i. two 600 mm × 600 mm panels; or
 - ii. one 600 mm × 600 mm panel and one 1200 mm × 300 mm panel; or
 - iii. one 1200 mm × 600 mm panel.