

- b) There shall be no more than one regulatory sign panel in the same multi-message sign frame displayed facing the direction of traffic. This excludes additional regulatory supplementary panels relating to and conditioning or otherwise the other regulatory sign panel(s) and which combine to form a single regulatory message.
- c) When used, regulatory sign panels shall be placed in the top position of the frame on the side closest to the traffic. This requirement does not apply to No Left (RM2 6A L) or No Right (RM2 6A R) Turn prohibition panels, these panels are installed on the side of the multi message assembly where the turn prohibition applies (see examples in Figure 4.2.2(a)).
- d) For multi-message signs facing traffic, within one frame, there should be no more than two message panels consisting of words only. If the 1200 mm × 600 mm space is filled with two separate 600 mm × 600 mm message panels, at least one of the 600 mm × 600 mm panels should be symbolic or a blank retroreflective yellow panel.

These requirements for text only multi message panels do not apply to the following arrangements:

- i. multi message signs installed in accordance with section 46 of the Transport Infrastructure Act 1994 for restricted road use notices, where, in most cases, three panels containing words are required (see examples in Figure 4.2.2(b))
 - ii. where police are performing traffic control duties and the 600 x 600 worded panels POLICE CONTROL AHEAD and PREPARE TO STOP are both required, see Figure 4.2.2(c) for examples, and
 - iii. where the 600 x 600 worded panels ROAD CLOSED AHEAD and LOCAL TRAFFIC ONLY are required, see Figure 4.2.2(d) for examples.
- e) A blank retroreflective yellow panel shall be placed within any unused module of the frame so that all panels in the frame are filled.
 - f) Multi-message sign panels (TM, RM, WM, GM Series) shall only be used in multimessage frames.
 - g) There shall be no more than one blank retroreflective yellow panel used in a multi message sign. When a 600x600 blank retroreflective yellow panel is used, it should be located furthest from traffic, except where arrows or other direction related symbol panels are required in this location.