

— closing one lane to be used for sign placement

— use of a variable message sign (VMS).

with:

- To effectively communicate relevant messages to road users, signs should be placed on both sides of all multilane roads and should also be placed on both sides of high volume (7500 vpd or greater) roads. For temporary speed restriction signs, refer to Section 5.5.1 for requirements to install on both sides of the road. If sign duplication is not possible (for example, vegetation, barrier, inadequate width), the designer must document an alternative to ensure all road users are able to see signs. This may involve:
 - placing signs on high temporary frames
 - repeating signs on one side of the road
 - closing one lane to be used for sign placement, and/or
 - use of a variable message sign (VMS).
- Signs and sign support structures should be kept away from the edge of the roadway as outlined in AGTTM Part 6.
- Sign supports on the outside of curves and other vulnerable places should be avoided or the sign support should be protected. Signs used at roadwork sites should be frangible and not require protecting with additional devices such as road safety barriers.
- The Lane Status sign must be used where one or more lanes of a multiway roadway are closed to assist with providing advance warning. These signs must not to be used instead of signage of the closure. They should be used in conjunction with closure signage.
- Signs must not encroach on footpaths or bicycle lanes unless the path is wide enough to accommodate them. Consider vulnerable road users with impaired vision, mobility or cognitive limitations. A delineation device (e.g. a traffic cone) should be placed at the base of signs on footpaths or bicycle lanes. If the width of the footpath/cycle path is insufficient, then an appropriate TGS must be determined to manage the path users.
- Avoid placement that could direct road users into incorrect or dangerous situations.