

Provided updated guidance for several pedestrian and footpath related TTM considerations.

Clarified information on providing alternative paths for pedestrians.

Added information on the surfacing requirements for footpaths or alternative routes for pedestrians.

Added a time consideration on the selection of an alternative route and surface type.

Added consideration for tactile signs.

3.10 Vulnerable Road Users

3.10.1 Pedestrians

Difference

Replace the two dot points:

- Desirably, if footpaths or pedestrian crossings have been partially closed or temporarily relocated, a temporary footpath should be provided with minimum width of 1.8 m to allow for all pedestrians including those with mobility aids or on the same scale and to the same width as any facilities for pedestrian that existed prior to the works. This width should also be applied to any temporary ramps (e.g. kerb ramps). If these widths are not practicable, alternative routes must be provided with a firm smooth surface and no trip hazards in the following order of preference:
 - 1 on the side of a road reserve away from traffic
 - between the work area and road but not in a traffic lane
 - onto the road either in a lane used for parking or a delineated and protected section of an existing traffic lane
 - across the road to a footpath on the opposite side with delineation at crossing points and kerb ramps. Consideration is required for persons with impaired vision, mobility, hearing or cognitive limitations. Only use this option if an appropriate crossing facility can be provided (see Austroads Pedestrian Facility Selection Tool).
 - a traffic controller to safely guide pedestrians around the operation. Only use this option if there is no safe temporary path available.
- Appropriate surfacing must be provided for prams, strollers, wheelchairs or any other mobility aids.