

- d) if a pre-designed contingency plan is not provided, seek urgent advice from the traffic management designer for the works.

8. A 60 km/h speed zone shall be established at least one sign spacing in advance of the traffic control station where the speed zone on the approach to the traffic control station is higher than 60 km/h. Duplicate the speed limit signs and install any required repeater speed limit signs as per the requirements in Section 5.5.1. If the speed of traffic on approach to the traffic control station and the end of queue is less than 60 km/h through other controls (such as the traffic control station and end of queue is down a side road), a 60 km/h speed zone in advance of the primary PREPARE TO STOP sign (for example on the through road) may not be required. Where the speed limit on approach to the traffic control station is greater than 60 km/h, a 60 km/h speed zone must be commenced at least one sign spacing (Table 2.2) in advance of the primary PREPARE TO STOP sign. This does not apply to situations where the traffic control station is located down a side road and the speed of traffic on approach to the traffic control station and the end of the traffic queue is less than 60 km/h through other controls (such as the traffic needing to turn onto the side road at a lower speed). Speed signs may be required on the side road if the speed of traffic on the side road may exceed 60km/h prior to the traffic control station or the end of the traffic queue. See Section 4.8.1 for more information on speed limits for traffic control stations on a through road near a side road. Duplicate the speed limit signs on both sides of the road and install repeater speed limit signs as required in Section 5.5.1.
9. Where intersections are located within the advance warning area (between the traffic control station and the ROADWORK AHEAD or VMS sign), see Section 4.8.1 for the signing requirements for traffic on or entering from side roads.
10. Provide additional devices and methods for avoiding end-of-queue collisions as required in Section 4.8.3.
11. For shuttle flow operations, the traffic control taper must start a minimum of 6 m from the traffic control station.