

Replace:

End treatments are not required if the temporary road safety barrier system is flared behind a permanent road safety barrier or is outside of the adjacent clearance area and therefore not regarded as a hazard.

with:

End treatments are not required if the temporary road safety barrier system is flared behind a permanent road safety barrier (or another temporary road safety barrier) and is outside the deflection zone requirements for that barrier system and therefore not regarded as a hazard.

The following elements apply when positioning road safety barrier systems:

- Adequate delineation of the road safety system must be provided to ensure road users are safely guided past the worksite.
- Fittings other than delineators (e.g. visibility screens) must not be fixed to the road safety barrier unless they are designed to accommodate the fitting.
- Screens designed to fit to barriers should also be approved by the relevant road authority relative to the work being done.
- Water runoff should pass unimpeded to avoid surface ponding.
- If positioned near high obstructions (e.g. power poles, fixed VMS, bridge piers, underpass scaffolding), the design should consider the extent of vehicle body roll (especially high vehicles) during impact.
- Barrier deflection must be accommodated in the area immediately behind the road safety barrier system. A containment fence or longitudinal channelising barrier should be placed a clear distance equal to the likely dynamic deflection behind the road safety barrier system. Clearance in Table 5.1 is measured between traffic and the front of the barrier system and not behind the barrier system in the deflection zone. For example, see Figure 5.4 illustrating dynamic deflection. This example does not include all traffic control devices required and must not be used as a TGS diagram.