

traffic controller using a STOP/SLOW bat or controlling a PTCF is required. The following requirements and recommendations apply when using traffic controllers:

- Only competent persons with appropriate certification must be appointed as a traffic controller (see AGTTM Part 7).
- Speed must be 60 km/h maximum. Provide a temporary speed limit of 60 km/h or less on the approach to a traffic controller if the speed is higher (see Section 5.5.1).
- An escape route must be identified for each traffic controller from their traffic control position.
- Traffic controllers must be positioned a clear sight distance from approaching road users (see Section 2.5.4) with no obstruction and where they are not obstructing visibility to traffic control devices (i.e. signs). No obstruction should be located in the area between the traffic controller and the end of the line of four cones.
- Ensure that a work vehicle is not parked in a way that impacts the visibility of the traffic controller or, limits the traffic controller's escape route or, is parked between the traffic controller and the taper.
- Ensure that traffic controllers are visible at all times of the day, particularly at dawn, dusk, against low morning or evening sun, when in the shade on a sunny day or working in dusty conditions.

Replace the following dot point:

- ~~Ensure that traffic controllers are well illuminated at night. Where required, provide additional lighting.~~

with

- The traffic control station and the area where traffic controllers are operating PTCFs must be well illuminated at night. Where required, provide additional lighting. See Section 6.7 *Night works* for greater detail about working at night.
- Relieve traffic controllers from traffic controller duties at least every 2 hours for at least 15 minutes.
- If cone tapers are used, position the traffic controller 6 m in front of the taper on the left-hand shoulder or edge of the road and facing approaching traffic.
- Place four traffic cones spaced 4 m apart, on the centre-line 6 m in front of the traffic controller position.
- If there is a queue, traffic controllers can move to the driver's side when safe to do so to remain visible to all road users.