


Specification

LED Module

P6 Outdoor, 32x16 dots, 192(L) x 96(H) x 17(T)mm, 1/8scan



1. PIXEL/MODULE Specification

Item	Parameter
Pixel Pitch	6 (mm)
Pixel Configuration	1R1G1B / R : G : B=3 : 6 : 1
LED Lamp	Full color
Module Size(H×W)	192 × 96 (mm)
Module Pixel	32(H) x 16(V)
Module Weight	191(g)
Module Power	Max. 40W
Drive Voltage	DC 4.6 ~ 5.5V

2. Screen Parameter

Item	Parameter
Brightness	≥ 6500 cd/m ²
View Angle	≥140° (Vertical)
	≥140° (Horizontal)
Best View Distance	6 ~ 15m
Scan Mode	1/8 Scan
LED Lamps	SMD3535
Drive IC	5020
Screen Lifespan	100,000 (Hrs)

3. Environment Condition

Use the environment	Outdoor
Working temperature range	-30~60°C
Working humidity range	10%~95% RH
IP Grade	IP65

4. Signal Function

Pin Number	Pin Name	Function Description
1, 5	R1, R2	Data Input For Green Color
2, 6	G1, G2	Data Input For Blue Color
3, 7	B1, B2	Data Input For Red Color
9, 10, 11, 12	A[0:3]	Line Address
13	CLK	Shift Clock For Input Data
14	LATCH	Data Strobe
15	OE	Out Enable
4, 8, 16	GND	Ground

5. Connector Cable Specification

Data Cable: 16Pin Flat Cable



6. Frame Dimention (192 x 96 x 17mm)

