THE ENVELOPE EXPLORER

User guide

how to read, filter and trace every message the platform emits

At a glance	
Where it runs	http://127.0.0.1:8802
What it shows	every envelope recorded by the lake, live
Read-only	it never writes to the platform or the bus
Retains	the most recent 20,000 envelopes in memory, plus everything on disk
Built for	forensics, compliance and model analysis

This guide is task-oriented. Each section answers one question: how do I find a message, how do I read one, how do I see what led to a decision, and how do I prove what happened.

Contents

1 Before you start

2 The screen at a glance

3 Finding the message you want

4 Reading an envelope

5 The timeline: browsing history

6 The journey: a flow diagram from a point

7 The execution trace: what a model actually used

8 How and why a model traded — or did not

9 Roles and redaction

10 Three worked examples

11 Keyboard and quick reference

12 Troubleshooting

1 Before you start

The Explorer is a viewer. It reads the lake that the recorder writes; it does not talk to the exchange and it cannot change anything. If it is empty, the problem is upstream, not here.

1.1 What should be running

Service	Port	Why the Explorer needs it
market data	:8796	the source of every price, depth and candle envelope
recorder	:8801	consumes the bus once and writes the lake the Explorer reads
envelopeapi	:8802	the Explorer itself

Start them in that order. The Explorer will start without the recorder, but it will have nothing to show.

1.2 Opening it

1. Start the core, then the Explorer (scripts/start.sh does both in order).
2. Open http://127.0.0.1:8802 in a browser.
3. The header should show a rising envelope count within a few seconds.

If the header shows 20,000 and stops climbing, the Explorer is fine and the feed has stopped. Check the recorder's /stats before touching the Explorer.

2 The screen at a glance

Four regions, always in the same place.



Figure 1 — the Explorer with an envelope selected: filters on the left, the list in the middle, the envelope's anatomy on the right.

Region	What it is for
Header	counts: envelopes held, bytes, planes, topics. The 'viewing as' role is on the right.
Timeline	a histogram of traffic over the retained window. Drag across it to select a time range.
Left panel	filters: plane, topic, symbol, producer, correlation id, free text.
Middle	the list of envelopes (newest first) or the journey flow diagram.
Right	the anatomy of the selected envelope: meta, payload, references, chain.

2.1 Breadcrumbs, not modes

The middle pane is a contextual surface. With nothing selected it is the live feed. Select an envelope and it recomposes around that envelope: its identity, its verdict if it is a decision, the envelopes it read or the ones that read it, and buttons to the flow and the full trace.

The bar above it is a breadcrumb — FEED / symbol · topic — not a row of equal tabs. You do not choose a mode; the selection decides what is worth showing. The deeper views (flow, trace, why) open from the context's buttons.

The ← button at the left of the crumb bar is back. It is greyed out when there is nothing to go back to, and it is the same action as Escape: one step, restoring the view and the envelope you had selected.

2.2 Resizing: every panel

Three splitters: one between the filters and the list, one between the list and the detail pane, and one under the timeline. Drag any of them; double-click is not needed because the size persists in the browser, so the layout you set is the layout you get next time.




Figure 2 — the filters pane dragged wider, a model decision selected, and the context strip showing the four interceptors that passed before the operator ran.

2.3 What the surface decides

The surface is a set of rules, not a template. Given a selection it asks what kind of thing it is holding and composes accordingly.

The selection	What the surface shows
nothing	the live feed and the timeline
a decision (model.decision)	its verdict: traded or refused, the reason verbatim, the confidence
an outcome (a fill, a ranking)	what it read, by stage, with the age of each input at execution
an input with downstream traffic	what read it next, in time order
an input with no downstream	the chain it belongs to, and a plain statement that nothing has read it yet
a multi-symbol snapshot	an explanation that it carries every symbol, so it has no per-symbol chain




Figure 3 — an input with no downstream: the surface shows the chain that led to it and says plainly that no model has read it in the window.

The rule the surface follows: never show an empty panel. If there is no downstream traffic, show upstream; if there is no chain, say why — a multi-symbol snapshot has none by construction.

2.4 Testing the surface

Six checks that exercise the rules above. Each takes seconds and each has an observable outcome, so a regression shows up as a wrong panel rather than a vague feeling that the UI is off.

#	Do this	Expect
1	open the Explorer with nothing selected	feed plus timeline; no detail, no chain
2	select a market.depth row	chain of that symbol, and the note that nothing downstream yet
3	select a model.decision row (WHY, then the row)	verdict block with traded/refused and the reason
4	select a model.fill row	what it read, with per-stage ages in seconds

5	press ← or Escape	the previous envelope and view come back, not a blank pane
6	drag both splitters, then reload	the layout is exactly as you left it

If a check fails, the cause is usually data rather than layout: the decisions are rare, the in-memory window covers the last 20,000 envelopes, and a symbol with no traffic will legitimately have nothing to show.

3 Finding the message you want

Filters combine: each one narrows the list further. The count above the list tells you how many matched.



Figure 2 — the plane filter set to intel. Every row shows a green 'INTEL' pill and the topic counts on the left change with it.

Filter	Use it when	Example
Plane	you want one class of traffic only	market, intel, model, control, system
Topic	you know the exact kind of message	intel.forecast, model.decision
Symbol / key	you are following one instrument	BTCUSDT
Producer	you suspect one component	market_data, signals, tad
Correlation id	you have an id from a log or a report	cid-9f2a41…
Contains	you remember a value but not the topic	0.0431 or 'liquidation'

Filters match case-insensitively and apply to the symbol, producer, correlation id and free text. The topic list under 'by volume' is also a filter: click a topic to select it.

3.1 When nothing matches

An empty list is information. The header count drops to zero, the list says so plainly, and the timeline above it keeps filling — which tells you the feed is alive and the filters are the reason you see nothing.




Figure 8 — a symbol filter that matches nothing: 0 envelopes, while the timeline keeps receiving traffic.




Figure 9 — filtering by producer: every row is a message that component wrote.

3.2 Live versus paused

The green LIVE button means new envelopes are being prepended as they arrive. Set to PAUSED to freeze the list while you read. Selecting a time range on the timeline also pauses it, because you are no longer looking at 'now'.

4 Reading an envelope

An envelope has three members and the right-hand pane shows all three, always: data, meta and references. A strip at the top of the pane tells you at a glance which are present.

4.1 The three members

Member	What it carries	If it is missing
data	the payload for this topic	never — a message with no data is refused
meta	version, plane, producer, generation, correlation id, computed_at, recorded_at, bytes	the pane says 'inferred'
refs	topic, key, generation and correlation id of each input	the pane says 'none' and explains what a reference would contain

References come in two kinds, and the pane always says which: **declared** by the producer, or **derived** by the recorder. The books do not declare their inputs yet, so the recorder attaches, for every model decision, the newest envelope of each input topic for that symbol in the preceding five minutes — and marks each one derived, with its age. A reference is never silently presented as declared when it is inferred.




Figure 7 — a decision with three derived references: market.depth at 0.2 s, intel.signal and intel.flow at 1.8 s. The refs member shows 3, and the section names its own provenance.

When a producer publishes its own wrapper (the Python books do: topic, producer, data, version, seq), the pane unwraps it: the Data section shows the inner payload and names the topic and producer it was published under.

4.2 Meta — provenance and freshness

Field	Meaning	Why it matters
version	the envelope contract revision	a reader refuses a revision it does not understand
plane	market, intel, model, control or system	decides priority and how it is handled
producer	the component that wrote it	the first question in any incident
generation	the producer's own counter for that topic	gaps reveal a dropped producer

correlation id	the identity that follows the message	resolves the chain around it
computed_at	when the payload was produced	this is what staleness gates refuse on
recorded_at	when the recorder stored it	the difference is transport and queue time
bytes	size on disk	market data is bytes, and bytes have a budget

4.3 Data — the payload

The payload exactly as it travelled, syntax-coloured. It is never rewritten by the Explorer: what you see is what the recorder stored.



Figure 6 — one decision envelope: meta on top, payload in the middle, chain underneath.

4.4 Pipeline — interceptors, operator, transformer

Every envelope carries the stages it passed through: the interceptors that checked it, the operator that produced it, and the transformers that changed its shape. This is the ATLAS pipeline made visible on the packet itself rather than in a log beside it. A refusal is recorded as an envelope too, so 'why not' is a packet you can open rather than a line you have to find.




Figure 8 — the pipeline strip: four interceptors, the operator, and two transformers, each with its outcome. The last one is the view-time redaction applied for this role.

Stage	What ran	What the chip means
interceptor	authority, keying, correlation, freshness	a pass means the rule was satisfied; a refusal names the rule and the number
operator	the producer (market_data, signals, a model)	the capability that produced this payload
transformer	record, redact	a change of shape: stored once, or redacted for the viewing role

Outcome colours: green pass, red refuse, amber modify. Hover any chip for its detail — for a refusal that is the exact text the governor recorded, for a transformer it is what changed.

4.5 Chain — what else happened for that symbol

Every envelope recorded for the same symbol, oldest first, with arrows. Click any step to jump to it. This is the quick way to walk a symbol's recent history without leaving the page.

A message with no key (for example market.mini24h) has no chain. That is not a bug: it is a multi-symbol snapshot, so there is no single chain to show.

5 The timeline: browsing history

The histogram above the list is traffic over time, one bar per slice, coloured by plane. It is how you find a moment rather than a message.



Figure 3 — a time range selected by dragging across the bars. Everything outside dims, the header names the window, and the list narrows to it.

1. Drag across the bars to select a window. The list reloads to that window and the live pill turns to paused.
2. Press ▶ play to step the window forward, so the retained period plays back like a recording.
3. Press 'live' to return to the newest 200 envelopes.

Two details worth knowing. The selection survives the histogram's own refresh, so the bars do not jump under the cursor while you are reading. And a gap in the histogram is a real gap: the Explorer never interpolates traffic that was not recorded.

6 The journey: a flow diagram from a point

This is the view to use when the question is 'how did this happen', rather than 'what is this message'.




Figure 4 — the whole platform as a flow: five stages and fifteen nodes, including each model that wrote a fill. Box height is volume; ribbon width is the number of correlations observed.

6.1 Two ways to open it

Way	What you get
Select an envelope, then open JOURNEY	the flow opens at that message: two minutes of lead-in, five minutes forward, on its symbol. The node containing it is ringed.
Open JOURNEY with nothing selected	the last five minutes across all symbols — a live view of the platform's shape.




Figure 5 — the same diagram anchored on a model.fill envelope: the dashed ring marks where you came in, and the window runs forward from that moment.

6.2 Reading the diagram

- Columns are the pipeline, left to right: market data → advisories → risk & alerts → decisions → other.
- Box height is volume. market.depth is tall; a handful of fills is a sliver.
- Box label is the topic and its count; the small line beneath is the time span those messages cover.
- Ribbon width is the number of observed correlations between the two topics.
- Colour is the plane: blue market, green intel, amber model, teal control, grey system.
- Nodes are split by producer, so three models writing model.fill appear as three boxes, each labelled with its engine.
- The dashed ring marks the anchor — the message you came in on.

6.3 Moving around

Action	What happens
Click a box	opens the newest envelope of that topic in the right-hand pane
Double-click a box	re-anchors the flow on that node and walks forward from it
Select another envelope in the list	re-anchors the flow there
Esc	back: returns to the previous view and the state you were in — selection, scroll and filters included
Brush the timeline	the flow uses that window too

6.4 A worked walk

1. Find a model.decision row in the list (filter plane=model, topic=model.decision).
2. Open JOURNEY. The ring shows where the decision sits in the flow.
3. Read left: the market data and advisories that preceded it.
4. Double-click the fill box to re-anchor on the fill and see what followed it.

Honest caveat: ribbons are temporal correlations — 'next stage for the same symbol within 120 seconds' — not declared references, because the Python books do not emit refs yet. When they do, the same diagram becomes literal lineage with no

interpretation required.

7 The execution trace: what a model actually used

The journey answers 'how does traffic flow'. The execution trace answers a narrower and more useful question: for this one fill, which raw envelopes did the model read, in what order, and how old were they when it acted?




Figure 10 — the execution trace for one model.fill: lanes by stage, nodes placed in time, the dashed line marking the moment of execution, and the inputs listed beneath with the age each had when the model acted.

7.1 How to read it

Element	Meaning
Lanes	one row per stage: market, advisories, risk, model, other
Node	one envelope. The label is the topic and how old it was at execution (−1s means one second before the fill)
Dashed vertical line	the moment of execution — the anchor envelope
Dotted path	the reading order: stage by stage through the chosen envelopes
1× / 2× / 4×	zoom. The canvas scrolls horizontally, so a fifteen-minute window stays readable
Table beneath	the inputs the anchor used: stage, topic, producer, age at execution, bytes

7.2 The Gantt: spans at a glance

The Gantt draws each span as a horizontal bar on one time axis. Open it from the context's gantt button. It has two modes, and they answer different questions.



Figure 12 — positions mode: each bar is one trade from entry to exit, with the engine labelled on the bar and the table beneath giving held time and net.

Mode	Bars are	Answers
positions	one trade per row, from entry to exit, for the last 40 fills	which trades were held far longer than intended, and what they returned
trace	one input per row, from when it was computed to when the outcome read it	which inputs were already stale when they were used

Bars are coloured by stage and labelled with the producer; the table under the chart is the same data as numbers. Click any bar to open that envelope. The horizontal scale is set from the median bar, so a single very long hold stretches the axis rather than flattening every other bar into a hairline — scroll to follow it.

7.3 Working through an execution

1. Open the EXECUTION tab with a fill selected (filter topic = model.fill to find one).
2. The view scrolls itself to the moment of execution and marks it with a dashed line.
3. Read left to right: market data first, then the advisories, then anything that followed the fill.
4. Click any node to see its raw envelope in the right-hand pane — data, meta and references.
5. Use the table beneath to compare ages: a decision made on a 600-second-old candle is a different decision from one made on a 2-second-old candle.

This is the view for 'why did the model do that'. It shows the exact envelopes, their ages, and their producers — not a summary of them. When books start emitting references, the dotted path becomes literal lineage instead of a time-ordered reading of the window.

8 How and why a model traded — or did not

This is the question a reviewer actually asks. The WHY tab answers it directly: every decision the models recorded, split into the trades they took and the trades they refused, with the rule that stopped them.




Figure 11 — the WHY tab: reason tally on the left, decisions on the right, and the raw refusal envelope open beside them.

8.1 Reading the tab

Part	What it tells you
Header	how many decisions the scan found: traded, refused, and the symbol if filtered
Why not (left)	the refusal reasons, tallest first. 'stale signals' dominating means the feed is late, not that the model is picky
Decision rows	time, symbol, reason as the model recorded it, outcome, engine
Right pane	the raw decision envelope: data, meta, references — including allowed and reason verbatim
Filters	symbol and engine; Enter runs the scan

8.2 What a decision actually contains

A model.decision payload is short on purpose. It carries the engine, the symbol and side, whether the governor allowed it, the reason, and the confidence the model had. Everything else is in the envelope: who produced it, when, and the correlation id that ties it to the rest of the chain.

Field	Example	Why it matters
engine	alpha_rank	which model made the call
symbol / side	UNIUSDT · buy	what it wanted to do
allowed	false	the governor's verdict
reason	stale signals: 847s old (max 90s)	the rule and the number that tripped it
confidence	0	the model's own conviction — 0 means none

8.3 From refusal to evidence in three clicks

1. Open WHY and find the refusal you care about — the reason is already visible in the row.
2. Click it: the right pane shows the raw envelope, so the reason is quoted from the record, not paraphrased.
3. Double-click it: the EXECUTION tab opens on that decision, with the inputs it read and how old each was.

A refusal is evidence, not noise. 'stale signals: 847s old' names the rule, the age and the limit, and the envelope that says it is the one the platform stored. That is the difference between 'it did not trade' and 'we cannot explain why it did not trade'.

9 Roles and redaction

The 'viewing as' selector in the header changes what you are allowed to see. It is a real filter applied on the server, not a cosmetic setting.




Figure 12 — the same envelope viewed as a bystander: depth fields removed, and a red band naming exactly what was withheld.

Role	Sees	Typical use
owner	everything	you are the operator
auditor	prices and sizes removed, everything else	reviewing decisions without market detail
bystander	the shape and provenance only	showing status to someone outside the desk

Every redaction is recorded in the envelope's meta as redacted_for and redacted_fields, so the removal is part of the record rather than a silent edit. If someone asks what you were shown, the answer is in the message.

10 Three worked examples

10.1 Why did we buy this?

1. Filter symbol = BTCUSDT and plane = model.
2. Open the model.decision row you care about.
3. Switch to JOURNEY: the ring sits on the decision; read left for the advisories and market data.
4. Note the correlation id from the meta pane — quote it in any discussion.

10.2 What happened at a specific minute?

1. Drag the timeline across that minute.
2. The list narrows to it; sort your reading by plane using the left panel.
3. Watch for a gap rather than a quiet period: a gap means no producer, not no market.

10.3 Which model is producing decisions?

1. Filter producer = books (or a specific engine) and topic = model.decision.
2. Compare the generation numbers: a stall shows as a flat generation while others climb.
3. Cross-check the recorder's per-topic counts in /stats to confirm delivery, not just display.

11 Keyboard and quick reference

Key or control	Effect
← (crumb bar)	back one step — the same action as Escape
Esc	one step back: the previous view *and* the envelope selected in it; with no history it clears the selection
Tab (browser)	focus the next filter
drag splitter	resize the filters, the list, the detail pane or the timeline
live / paused	follow new envelopes, or freeze the list
▶ play	step the selected window forward
reset	clear every filter and return to live

11.1 What the colours mean

Colour	Plane	Typical topics
blue	market	ticks, market.price, market.depth, market.candle
green	intel	intel.signal, intel.flow, intel.ta, intel.forecast
amber	model	model.decision, model.fill, model.pnl, model.rank
teal	control	risk.state, exec.quote, alert.pumpdump
grey	system	system.health, review.verdict

12 Troubleshooting

Symptom	Likely cause	What to do
List is empty	nothing matches the filters	press reset
Count frozen at 20,000	feed or recorder stopped	check :8801/stats and :8796/health
A topic never appears	its producer is silent	intel.forecast needs 40 bars before it publishes
Journey shows one column	the symbol only has market data	pick a symbol with decisions (filter plane=model first)
Ribbons are missing	no correlations in the window	widen the window or pick a busier symbol
Chain says 'no key'	the topic is a multi-symbol snapshot	expected for market.mini24h and ticks

The Explorer is read-only by construction: it opens the lake, never the bus, and never writes. If something looks wrong in the platform, the Explorer is the wrong place to fix it — but the right place to prove it.

13 Investigating a book

This is the compliance workflow end to end: a question arrives about a model's trading, and the answer has to be evidence rather than opinion. The Explorer's BOOKS view is the starting point.




Figure 15 — the books view: every engine that traded, with trade count, net sum, mean net, mean holding time and refusals.

1. Open BOOKS from the breadcrumb. The list is every engine that has produced a fill, ordered by activity.
2. Click a book. The summary shows trades, refusals, mean net, sum of net, mean and longest holding time, and how many instruments it touched.
3. Scan the trade table: time, instrument, side, held, net, and the envelope id for each trade.
4. Click any row to open that envelope: its three members, its pipeline, its references.
5. Press export regulatory report to open the printable book report in a new tab.

The book view is deliberately numeric first. A regulator's first question is what the book did, not why one trade happened; the narrative belongs in the case file for a specific trade.

13.1 What to look for

Signal	What it suggests	Where to look next
mean held far above the model's stated horizon	positions are being held without a decision to exit	Gantt positions mode, longest holds
net sum positive but mean net near zero	a few winners carrying many flat trades	trade table sorted by net
refusals much larger than trades	the governor is the binding constraint, not the model	WHY tab, reason tally
one instrument dominating the trade count	concentration risk or a stuck symbol	exposure by instrument in the report
holds clustering at a round number of seconds	a timeout is closing trades rather than a signal	Gantt, held distribution

14 Regulatory reporting

Two documents are produced, both from recorded envelopes, both printable to PDF from the browser: a case file for a single decision, and a book report for a book over a window.

14.1 The case file




Figure 16 — a case file: what happened, the verdict, what it read, the pipeline, the references and the raw payload, with the provenance note in the footer.

Section	Contents	Why it is there
What happened	topic, symbol, producer, recorded time, correlation id, generation	identity of the event under review
Verdict	traded or refused, with the rule quoted verbatim	the decision, in the platform's own words
What it read	input envelopes with their age at the decision	the evidence the model acted on, and how stale it was
Pipeline	each interceptor, the operator and the transformers, with outcome	proof the controls ran before the action
References	declared or derived, with age and correlation id	lineage, and which part of it is inferred
Raw payload	the stored payload, unmodified	the primary record, readable without this tool

14.2 The book report




Figure 17 — the regulatory book report: scope, summary, the full trade table with envelope ids, exposure by instrument, methodology and a case hash.

Section	Contents
1 Scope	book, window, counts, instruments, and the data-source statement
2 Summary	trades, mean net, sum of net, sum of gross, mean and longest hold, refusals
3 Trades	every trade in the window with time, instrument, side, entry, exit, held, net, reason, envelope id
4 Refusals	every refused decision with the rule and the envelope id
5 Exposure	trade count per instrument
6 Methodology	how holding time and net are defined, and what derived versus declared means
footer	a case hash over book, window and counts, for comparison between copies

14.3 Archiving without a document store

Both pages are self-contained HTML with print CSS. Saving as PDF from the browser produces the artefact; the case hash printed on the report lets two copies be compared, and every row carries an envelope id that can be resolved back to the lake. That is deliberate: the report is a rendering of records, not a new source of truth, and nothing in it cannot be checked against the store.

15 Field dictionary

Every field an investigator will meet, in one place.

15.1 Envelope metadata

Field	Type	Meaning
version	int	envelope contract revision; a reader accepts the current and the previous one
plane	string	market, intel, model, control or system
topic	string	the bus topic the envelope was published on
key	string	the symbol, when the message concerns one; empty for snapshots
producer	string	the component that computed the payload
generation	uint	the producer's own counter for that topic; gaps mean loss
sequence	uint	publish order within a producer session
cid	string	correlation id; the identity that follows the work
computed_at	timestamp	when the payload was produced — the field staleness gates use
received_at	timestamp	when the recorder accepted it
compute_ms	int	how long the producer took, when it reports it
refs	array	inputs; each has topic, key, generation, cid, derived and age_ms
hops	array	pipeline stages: kind (interceptor/operator/transformer), name, outcome, detail, ms
extra	map	free-form markers, for example refused=true or redacted_for

15.2 Payload fields by topic

Topic	Fields
model.decision	engine, symbol, side, allowed, reason, confidence
model.fill	engine, symbol, side, entry, exit, gross_pct, net_pct, peak_pct, reason, held_s, notional, pnl_usd, entry_ms, exit_ms
model.rank	top[] with symbol and score
model.pnl	engine, realised, unrealised, equity
intel.signal	symbol, funding_pct, basis_bps, open_interest, oi_change_1h_pct, taker_ratio, smart_vs_dumb, flow_conf, score
intel.flow	symbol, buy_ratio, flow_conf, score, flow_series
intel.ta	symbol, signals[], count
intel.forecast	symbol, side, horizon_s, prob, move_pct, confidence, action, views[], resolution
market.depth	symbol, bids[], asks[], bid_qty, ask_qty, imbalance
ticks	p{} price per symbol, m{} 24h statistics per symbol
market.candle	symbol, interval, t, o, h, l, c, v, q, Q
risk.state	snapshot{equity, gross_multiple, longs, shorts, per_symbol}, ts

16 API reference

Everything the UI does is one of these calls. They are read-only and need no key on localhost.

Endpoint	Parameters	Returns
/api/envelopes	plane, topic, key, producer, cid, q, from, to, limit	matching envelopes, newest first
/api/envelope/{id}	role	one envelope with payload, meta, refs and hops
/api/trace	key	every envelope recorded for a symbol
/api/execution	id, window_s	the inputs an outcome read, with ages
/api/why	key, engine, limit	decisions split into allowed and refused, with reason tallies
/api/search	symbol, engine, outcome, from, to, limit	candidate decisions in a window
/api/books	—	engines with trade counts, net and holding summary
/api/book	engine, from, to	one book's trades, refusals and per-symbol counts
/api/book.html	engine, from, to	the printable regulatory report
/api/case.html	id	the printable case file for one decision
/api/flow	key, id, from, to	stage nodes with volumes and counted links
/api/timeline	buckets	a stacked histogram of traffic
/api/gantt	mode, id, limit	spans: position lifetimes or input validity
/api/stats	—	counts by plane and topic, bytes and window

17 Known limitations and FAQ

17.1 Limitations, stated plainly

Limitation	What it means in practice
references are usually derived	the books do not declare their inputs; the recorder infers them from the preceding five minutes and marks them derived
the in-memory window is finite	20,000 envelopes; older decisions are found by scanning the lake, which takes about half a second
market-floor coverage differs	some topics are snapshots with no symbol, so they have no per-symbol chain
holding time is the payload's figure	not recomputed from fills
net return is the model's figure	after fees as the model computed them
the case file is HTML printed to PDF	there is no signed PDF; the case hash is the comparison handle

17.2 Questions an investigator asks

Question	Answer
Can I see what the model read?	CONTEXT on a decision: what it read, by stage, with ages. EXECUTION has the timeline.
Can I prove a control ran?	PIPELINE shows each interceptor with pass or refuse, before the operator.
Can I see why it did nothing?	WHY lists refusals with the rule and the number that tripped it.
Can I compare two books?	BOOKS lists them side by side; the reports carry a case hash each.
Can I export for a regulator?	Case file per trade, book report per book, both printable to PDF.
What if data is missing?	A gap is shown as a gap: the timeline does not interpolate and the recorder counts refusals.

18 Glossary

Term	Meaning
envelope	the fixed carrier: data, meta and references
interceptor	a rule that runs before work, and can refuse with the rule named
operator	the capability that produces a payload
transformer	a stage that changes an envelope's shape, never its truth
hop	one recorded pipeline stage on an envelope
reference	a link to an input envelope; declared by a producer or derived by the recorder
correlation id	the identity that follows one piece of work through the platform
derived reference	an input inferred by the recorder, marked derived with its age
generation	a producer's monotonic counter; a gap means missing messages
plane	the traffic class: market, intel, model, control, system
case file	the printable record of one decision and its evidence
case hash	a fingerprint over a report's scope, for comparing copies
refusal	a decision the governor declined, with the rule that stopped it
holding time	entry to exit, as recorded in the fill payload
lake	the recorded store of envelopes the Explorer reads

19 A worked investigation, start to finish

A question arrives: the grid book has been trading a lot, and someone wants to know whether it is behaving as designed. This is the sequence an investigator would follow, and what each step produced.

1. BOOKS, then grid. 253 trades, mean net +0.09%, mean hold 1,469 s, longest hold 5,715 s, 37 instruments.
2. Sort the trade table by held. The long tail is visible immediately: a cluster of holds between 4,000 and 5,800 seconds.
3. Open GANTT in positions mode for the book. The long bars are the same trades; the short ones sit around 30 to 400 seconds.
4. Pick the longest hold and open its envelope. The fill carries the engine, the reason and the exit — here, a grid level exit rather than a timeout.
5. Open the decision behind it. The verdict says traded, with confidence and the model's reason.
6. Read what it read: a candle and a depth snapshot, both under a second old at the decision.
7. Export the case file for that trade, and the book report for the window. The two documents answer the individual and the aggregate question.




Figure 18 — step 2: the book's summary and trade table, with held time and net per trade.



Figure 19 — step 3: the same trades as spans; the long holds are the bars that stretch right.

19.1 What the investigation found

Observation	Evidence	Conclusion
holds cluster in two regimes	Gantt: ~30–400 s and ~4,000–5,800 s	two exit paths are in use, not one
mean net positive but small	summary: +0.09% per trade	edge is thin relative to fees; cost assumptions matter
no refusals from this book	book summary: 0 refusals	the governor is not the binding constraint here
37 instruments	exposure table	diversified, but watch per-symbol concentration

The point of the exercise is that every row above is traceable to an envelope id. The conclusion can be disputed; the evidence cannot be re-invented.

20 Design notes

Why the Explorer behaves the way it does. These are decisions, not accidents, and each one has a consequence an investigator should know about.

Decision	Reason	Consequence
one contextual surface, not tabs	an investigator should not have to know which mode holds the answer	the selection decides what is shown; deeper views open from it
never show an empty panel	an empty pane reads as a bug or, worse, as concealment	absence is stated: 'nothing downstream yet', 'no per-symbol chain'
derived references are labelled	inferred lineage is weaker evidence than declared lineage	the case file distinguishes them, always
refusals are recorded	'why not' is a compliance question, not a debug question	refusals appear in WHY and in book reports
case hash on reports	two printed copies must be comparable	a changed window or count changes the hash
read-only by construction	a viewer that can write cannot be trusted as evidence	the Explorer opens the lake, never the bus

21 Appendix — sample case file

An actual case file, reduced to text, so the shape is recognisable without opening the tool.

```
Case file — model.decision NEARUSDT
decision 947528192 · recorded 2026-10-19T12:04:05Z · generated 2026-10-19T12:12:49Z

WHAT HAPPENED
  topic            model.decision
  symbol           NEARUSDT
  producer         alpha_rank
  correlation id   cid-8c50fc9388443f4e
  generation       1695

VERDICT
  REFUSED          stale signals: 3230s old (max 90s)

WHAT IT READ
  The inputs are no longer in the in-memory window; the recorded references are:
  market.candle    5007 ms   derived true   cid-fd7bb550b9ba9d5b
  market.depth      906 ms   derived true   cid-59288cd5a55a3bec

PIPELINE
  interceptor  authority    pass
  interceptor  keying       pass
  interceptor  correlation  pass
  interceptor  freshness    pass
  operator     alpha_rank   pass   produced model.decision
  transformer  record       pass   stored once in the lake

RAW PAYLOAD
  { "engine": "alpha_rank", "symbol": "NEARUSDT", "side": "buy",
    "allowed": false, "reason": "stale signals: 3230s old (max 90s)", "confidence": 0 }
```

22 Appendix — sample book report rows

The trade table of a book report, first rows only. Every row carries the envelope id that resolves it.

#	time	instrument	side	entry	exit	held	net	reason	envelope
1	10:40:23	APTUSDT	sell	0.77724	0.77587	19s	0.116%	grid	1916297078
2	10:40:31	APTUSDT	sell	0.775882	0.774514	65s	0.116%	grid	2104151056
3	10:40:35	ADAUSDT	sell	0.218687	0.218446	67s	0.050%	grid	718800172
4	10:40:56	FETUSDT	sell	0.188821	0.188501	58s	0.109%	grid	1594588925
5	10:40:58	BNBUSDT	sell	725.465	724.739	55s	0.040%	grid	2098522729
6	10:41:01	ETHUSDT	sell	2428.08	2425.55	91s	0.044%	grid	587372541
7	10:41:06	AAVEUSDT	sell	151.708	151.483	101s	0.088%	grid	1382730695
8	10:41:08	ETCUSDT	sell	7.74694	7.73892	98s	0.043%	grid	1841120590

summary: 253 trades · mean net +0.090% · sum +21.54% · mean held 1469s · longest 5715s
case hash: 485c35a20fff538d

23 Appendix — operations checklist

Check	How	Expected
the Explorer is up	open :8802, the header counts climb	envelope count rising
the recorder is consuming	GET :8801/stats	received = written, refused small, errors 0
the feed is alive	GET :8796/health	prices > 0, kline series rising
the queue is bound	GET :15672, queue q.rec.model.decision	consumers 1, publish rising
a case file resolves	open /api/case.html?id=<a recent decision>	six sections render
a book report resolves	open /api/book.html?engine=grid	scope counts match BOOKS

24 Search cookbook

Twelve questions an investigator actually asks, and the exact filter that answers each one. Every recipe is stated as a filter you can type, not a concept.

You want to know	Filter	What you will see
everything one symbol did today	symbol = BTCUSDT	the feed narrows to that symbol; use the chain for order
what one model decided	producer = alpha_rank, topic = model.decision	every decision that engine recorded
why a model stopped trading	WHY, outcome = refused, window 6 h	refusals ranked by rule, with the numbers
which trades were held too long	GANTT, positions	spans sorted by start; the long bars stand out
what an input was used for	select the input, CONTEXT	what read it next, in time order
whether an advisory was stale	select the decision, CONTEXT what it read	age per input in seconds
a trade from a report id	paste the envelope id into /api/case.html?id=	the case file for that trade
what happened in a minute	timeline brush across it	the window's traffic, by plane
whether a producer is alive	producer = tad, window 1 h	empty means silent; compare with the header counts
which instruments dominate a book	BOOKS, then the book	exposure by instrument in the report
what a refusal was about	WHY row, click	the raw refusal envelope, reason verbatim
how the whole platform is moving	JOURNEY with nothing selected	the five-stage flow with volumes

25 Data quality checks

Before a report is signed, these are the checks worth running. Each one is a question with a numeric answer, so it can be recorded alongside the document.

Check	How	Pass looks like
no gap in a producer	compare generation between consecutive envelopes of a topic	generation increases by one
no silent queue	queue q.rec.<topic> consumers and publish rate	consumers 1, rate matching the producer
refusals are explained	WHY, reason tally	every refusal carries a rule and a number
inputs are fresh	CONTEXT on a sample of decisions	ages well under the documented limit
holding times are plausible	GANTT, positions	no cluster at implausible durations without a reason
reports reconcile	book report counts vs BOOKS summary	identical trade and refusal counts
case files resolve	open three case files at random	six sections, payload present, hash printed

25.1 What to do when a check fails

Failure	First action
generation gap	check the producer's process and its queue; a gap is a fact, not a rounding error
queue silent with consumers	check the binding; a missing binding looks exactly like a quiet topic
refusal without a rule	treat as a defect: every refusal must name the rule that produced it
stale inputs beyond the limit	the governor should have refused; if it did not, the limit is wrong
report counts disagree	trust the report's envelope ids and recount from the lake

26 Appendix — a search session, as it happened

A transcript of a short session, so the rhythm of the tool is visible: filter, read, drill, export.

```
USER  books
TOOL  grid 253 trades · net +21.54% · mean +0.090% · held 1469s · refusals 0
      hft 73 trades · net +3.54% · mean +0.050% · held 439s
      movers 65 trades · net +4.98% · mean +0.080% · held 375s
      alpha_rank 0 trades · 326 refusals

USER  open grid
TOOL  summary: trades 253 · refusals 0 · mean net 0.09% · sum 21.54%
      mean held 1469s · longest 5715s · instruments 37

USER  gantt, positions
TOOL  40 spans · mean hold 1876s · bars coloured by stage

USER  click the longest bar
TOOL  envelope 215876507 · model.fill · GALAUSDT · grid
      held 547s … (a level exit, not a timeout)

USER  export case file
TOOL  six sections · payload present · case hash printed

USER  export book report
TOOL  scope 253 trades · 0 refusals · 37 instruments · case hash 485c35a20fff538d
```

27 Case study: investigating a refusal

A model did nothing for six hours, and someone asks why. The answer is not 'it had no signal' — it is a rule, a number and an envelope.

1. WHY, window 6 h, outcome refused. The tally shows stale signals dominating, with counts in the hundreds.
2. Open the newest refusal. The verdict reads refused, and the reason quotes the age and the limit: 'stale signals: 3230s old (max 90s)'.
3. Read the pipeline. The freshness interceptor passed, because the freshness rule measures the envelope's computed_at, not the signal's age — the refusal came from the model's own signal-age check.
4. Read what it read. Two derived references, both under six seconds old, so the market data was fresh; the signals were not.
5. Export the case file. It carries the reason verbatim, the references with ages, and the raw payload.

Question	Answer found	Where
Did the model try to trade?	yes, repeatedly, hundreds of times	WHY row count
What stopped it?	the signal-age rule inside the model, at 90 seconds	reason text
Was the market data stale?	no: inputs were seconds old	case file, what it read
Was the governor at fault?	no: the model never presented an order	pipeline shows no refusal there
What is the actual fault?	the signal producer was not publishing for that symbol	generation gap on intel.signal

This is the distinction that matters in a report: the platform did not fail to trade — one producer stopped, and the model correctly refused to act on stale information. The evidence says so in three clicks, and the case file carries it.




Figure 20 — the WHY tab where the investigation starts: refusals ranked by rule, and the raw refusal beside them.

28 Operating and retaining

The Explorer is one binary and one directory. This is what it needs and what it keeps.

Component	Port	Purpose
envelopeapi	8802	the Explorer and its API
recorder	8801	consumes the bus once and writes the lake
market data	8796	the source of market envelopes
RabbitMQ	61613 / 15672	STOMP and management

28.1 Retention

Data	Kept	Why
in-memory window	20,000 envelopes	instant filtering and the live feed
lake journals	until rotated or expired	the record; case files and reports resolve against it
scanned cache	for the session	lets a case file open a decision older than the window
case files and reports	whatever you save	self-contained HTML printed to PDF

28.2 Restarting

Restart order matters because the Explorer reads the lake the recorder writes. Start the broker, then the feed, then the recorder, then the Explorer. If the Explorer comes up first it will show an empty feed and fill within a few seconds of the recorder starting.

Symptom after a restart	Cause	Fix
feed empty, header at 0	recorder not up yet	start the recorder, wait for /stats
feed frozen	recorder stopped	check /stats and the recorder log
a topic missing entirely	queue not bound	the recorder declares bindings at startup; restart it
case file 404	envelope outside the window and never scanned	open it through WHY first, which scans the lake