CRYPTALYST

DOMAIN MODEL

from the first socket message to the byte on disk

seven bounded contexts · one envelope contract · one record

MARKET DATA · INTELLIGENCE · BOOKS · RISK · RECORDING · FORENSICS · CONTROL

Platform build 1.0.0 · 823eb7a · 2026-10-21

© 2026 CryptAlyst · designed by Andrew Preston · built by the CryptAlyst engineering team

seven contexts · eight figures · four levels

domain model · revision 1.0

Contents

Every section begins with what it shows; every figure is listed here and captioned where it appears. The document runs from the whole platform down to the filesystem.

— **How to read this**

How the document narrows its lens, from the whole platform to a single byte on disk.

1 **The context map**

The seven contexts, the aggregates each owns, and the direction knowledge travels between them.

2 **The envelope — the only thing that travels**

The one object that crosses every boundary, and the hops that record what happened to it.

3.1 **Market data — the only process that talks to the exchange**

How an exchange socket becomes topics: shards, a single parse, in-memory state, and a publisher that cannot block the read.

3.2 **The book — the aggregate that decides**

The aggregate that decides: equity, positions, the decisions that opened them and the refusals that did not.

3.3 **The gate — what must pass before money moves**

The order of the gate — identity and freshness before arithmetic — and the exit policy that books losses.

3.4 **The recorder — the only writer**

The only writer of the record, and the derived references it attaches when a producer did not declare its inputs.

3.5 **Control — what may change behaviour**

What may change behaviour — supervise and stop — and what STOP must never touch.

4.1 **The lake — what is actually on disk**

What is actually on disk: the journal, its line format, the index that avoids scanning it, and retention.

4.2 **The data stores, as they exist**

Every place data is actually written on this machine, in which format, by which process, for how long.

4.3 **How the lake chooses**

The decision tree that decides which store receives an envelope, how long it lives, and when a segment is sealed.

5 **Beneath the lake**

The filesystem properties that let a case file be called evidence a year later.

— **Crossing concerns — time, identity and generations**

Time, identity and generations, modelled once in the envelope rather than per context.

— **What the model deliberately refuses to do**

The boundaries the model will not pretend to cross, stated so they can be argued with.

FIGURES

FIG	FIGURE	WHAT IT SHOWS
1	The context map	seven contexts, their aggregates, the flow between them
2	The envelope	data, meta, refs, and the hops appended along the way
3.1	Market data	shards, parse, state, topics — and a publisher off the read path
3.2	The book aggregate	equity, positions, trades, decisions, refusals
3.3	The gate	interceptors before arithmetic, and the exit policy
3.4	The recorder	one writer, hops recorded, derived references attached
3.5	Control	supervise, stop, and what STOP must never touch
4.1	The lake	journal, line format, index, retention, replay
4.2	Data stores	every store on disk: format, writer, reader, lifetime
4.3	How the lake chooses	the rules that decide where data lands and how long it lives

How to read this

WHAT THIS SHOWS How the document narrows its lens, from the whole platform to a single byte on disk.

A domain model is an argument about what belongs together, not an inventory of files. Each level here narrows the lens: the contexts, then one context at a time, then the record, and finally the bytes underneath the record.

Two rules run through every level. First, exactly one kind of thing travels between contexts: an envelope. Second, only the control plane may change what the platform does; data may inform a decision but never stop the machinery.

LEVEL	QUESTION IT ANSWERS	WHERE
1	what is this platform about?	the context map
2	what travels between the parts?	the envelope
3	what is inside one part?	one figure per context
4	what is the record, and where does it live?	the lake and the data stores
5	what is beneath the record?	the filesystem

1 The context map

WHAT THIS SHOWS The seven contexts, the aggregates each owns, and the direction knowledge travels between them.




Figure 1 — The platform in one picture: contexts, the aggregates they own, and which way knowledge flows.

Seven contexts, arranged by the direction knowledge travels. Market data observes. Intelligence interprets. Books decide. Risk refuses. Recording writes. Forensics reads. Control may stop.

The arrows are not calls. Each one is a stream of envelopes on one bus, so a context can be stopped, restarted or replaced without the others knowing.

CONTEXT	OWNS	MAY
Market data	the exchange connection, the price and depth state	publish market.*
Intelligence	signals, flow, TA, forecasts	publish intel.*
Books	equity, positions, trades, decisions, refusals	publish model.*
Risk & execution	the gate, the sizing rule, the exit policy	allow or refuse
Recording	the envelope, the journal, derived references	append to the lake
Forensics	case files, reports, search, journey	read only
Control	trading state, the stop flag, the registries	supervise, stop

2 The envelope — the only thing that travels

WHAT THIS SHOWS The one object that crosses every boundary, and the hops that record what happened to it.




Figure 2 — Three members, and the hops that prove what happened to the envelope on the way.

An envelope is data, meta and refs. The data is the payload a producer computed and is never rewritten. The meta is provenance: version, plane, topic, key, producer, generation, sequence, correlation id, computed_at, received_at, compute time, and a free-form extra map. The refs are the inputs, declared or derived, each carrying its age.

- interceptors run first and append a hop each — authority, keying, freshness, correlation, redaction
- the operator produces the payload and appends a hop
- transformers may change the shape, never the truth, and append a hop
- a refusal is a hop with outcome refuse and the rule in its detail

The contract is deliberately strict in one direction and lenient in the other. An unknown top-level member is refused, because a reader must never silently ignore something it does not understand. An unknown meta key is ignored, because provenance may grow without breaking every reader. One previous version is accepted, so a writer can be rolled forward before every reader is.

3.1 Market data — the only process that talks to the exchange

WHAT THIS SHOWS How an exchange socket becomes topics: shards, a single parse, in-memory state, and a publisher that cannot block the read.




Figure 3.1 — Shards, one parse, in-memory state, then topics. Publishing never blocks the socket.

The feed streams the top symbols by 24-hour quote volume, four streams each, sharded so no websocket carries more than about a thousand streams. Each shard reconnects with backoff. The parse is single-pass: bookTicker becomes top of book, depth becomes the depth book, klines become series with a closed flag, miniTicker becomes 24-hour stats.

The one design decision worth naming: publishing happens on a goroutine through a bounded queue. Publishing inline on the read path means a slow broker write stops the reader, the exchange's ping times out, and the connection dies. Under pressure the feed drops depth samples and counts them, because a missed sample is better than a dead stream.

STATE	FED BY	SERVED BY
Prices	bookTicker	GET /streamprices
Books	depth5	GET /depth?symbol=
Klines	kline_1m / kline_5m	GET /klines?symbol=&interval=
Mini stats	miniTicker	GET /movers

3.2 The book — the aggregate that decides

WHAT THIS SHOWS The aggregate that decides: equity, positions, the decisions that opened them and the refusals that did not.




Figure 3.2 — A book is one aggregate: equity, positions, and the decisions that produced them.

A book is the unit of consistency. Its equity moves only when a position closes, by that trade's net, and never by an opinion about an open position. Positions live inside the book; a decision that would open one either becomes an allowed decision or a refusal, and both are recorded.

- a position is never opened without an allowed decision
- a trade is only born from a position that existed
- equity moves only by a closed trade's net
- a refusal is recorded even though nothing was bought

The refusals are the part most systems omit. A refusal carries the rule that stopped it and the number that tripped it, so the question 'why did it not trade' is answered by the same object as 'why did it trade'.

3.3 The gate — what must pass before money moves

WHAT THIS SHOWS The order of the gate — identity and freshness before arithmetic — and the exit policy that books losses.




Figure 3.3 — Interceptors, then the arithmetic. Every stage appends a hop, so a refusal explains itself.

The gate is ordered deliberately: identity and freshness before arithmetic. There is no point in sizing a trade on a signal that is four hours old, and no point in asking whether a stale signal is affordable.

The exit policy is part of the model, not an implementation detail. The platform once refused every losing exit, which made the fills table contain only winners while equity fell on the losers still open. The policy now holds a loss only while it is shallow and young, and releases it at a stop or a time cap. A loss is booked like any other outcome.

CHECK	REFUSES WHEN
size	notional is zero
forecast age	older than the limit
signal age	older than the limit
kill switch	the stop flag exists
gross multiple	exposure would exceed the cap
symbol share	one position would exceed the book

3.4 The recorder — the only writer

WHAT THIS SHOWS The only writer of the record, and the derived references it attaches when a producer did not declare its inputs.




Figure 3.4 — One consumer per topic, hops recorded as they pass, derived references attached at the door.

The recorder owns one queue per topic, so it sees every message exactly once. It runs the interceptors one at a time and records each as a hop on the envelope itself — which is why the pipeline an envelope went through is data, not a log line.

- a refused envelope is recorded too, with extra.refused = true
- the record therefore contains what did not happen
- derived references are labelled, never implied
- the recorder declares its own topology; it does not rely on another process to do it

Books do not declare their inputs. Rather than leave a decision parentless, the recorder attaches derived references: the newest input per topic within five minutes, marked derived, carrying the age it had at decision time. It is the weakest form of lineage and it is always labelled as such.

3.5 Control — what may change behaviour

WHAT THIS SHOWS What may change behaviour — supervise and stop — and what STOP must never touch.



Figure 3.5 — The supervisor, the stop flag and the heartbeat, and what STOP must never touch.

STOP is the most important verb in the platform, so it is defined precisely. It kills every trading process, writes a flag that every gate reads, publishes a control envelope on the bus, and resets books and statistics after archiving them. It must never stop market data, the recorder or the explorer: an operator needs the record most at the moment they stop trading.

- STOP kills trading, writes the flag, publishes system.control, resets the books
- STOP leaves market data, the recorder and the explorer running
- starting the platform does not start trading unless it is asked to
- a stopped book is visibly stopped; it does not linger as a row on a dashboard

The inverse is equally deliberate: no data path can stop the platform. A feed outage, a dead book or a missing consumer degrades what you see; only the control plane changes what the platform will do next.

4.1 The lake — what is actually on disk

WHAT THIS SHOWS What is actually on disk: the journal, its line format, the index that avoids scanning it, and retention.




Figure 4.1 — A journal, a line format, an index, and the retention that keeps it from growing forever.

The lake is a directory of JSONL journals. One line is one envelope. The line carries the topic, the key, the timestamp and the envelope itself. There is no database, no queue and no cache between the record and the filesystem, which is what makes it readable by grep and jq a year later.

Reader queries do not scan the journal. An index of topic to byte offsets is built once at startup and extended as the recorder appends; refreshing it is throttled, because a cold query that walks a multi-gigabyte file is indistinguishable from a hang.

LAYER	CONTENTS	WRITTEN BY
bronze	the raw journal, every envelope	the recorder
silver	features extracted from fills	the historian
gold	datasets for training and study	the trainer
archive	sealed, compressed, cold	retention

4.2 The data stores, as they exist

WHAT THIS SHOWS Every place data is actually written on this machine, in which format, by which process, for how long.




Figure 4.2 — Eight stores. The journal is the only one that is a record; the rest are derived, cached, archived or diagnostic.

It is worth being literal about storage, because most architectures hide their stores behind services. Here there are eight, and every one of them is a file you can open.

The journal is the record: 60 GB of JSONL, one envelope per line, written by the recorder alone. The datasets are derived from it by the historian. Live state is what the books currently hold, rewritten in place and explicitly not a record. Ledgers are the per-engine trade files, appended by the engines themselves. Archives are copies taken before a reset. The index is memory, rebuilt at boot. Logs are diagnostic. Older journals are kept for replay comparison.

STORE	FORMAT	WRITTEN BY	LIFETIME
state/lake3/envelopes.jsonl	JSONL	recorder	the record; rotated and expired by policy
datasets/	CSV + JSON	historian	rebuilt on demand
state/pack_*.json	JSON	each book	until the next write
ledger/*.jsonl	JSONL	each engine	append only, never expired
state/archive_*	JSON	control on reset	kept for recovery
state/lake, lake2, lake4	JSONL	older recorders	cold, for comparison

index (memory)	offsets	the explorer	rebuilt on boot
logs/	text	every process	diagnostic

4.3 How the lake chooses

WHAT THIS SHOWS The decision tree that decides which store receives an envelope, how long it lives, and when a segment is sealed.




Figure 4.3 — One question per level: what is it, how long does it live, is it big enough to seal. Nothing is deleted by a rule that is not drawn here.

Retention is not a setting in a configuration file; it is a short tree. An envelope arrives, and the first question is whether it is a trading outcome. Outcomes go to the silver record — the ledger and the fills file — which is never rotated and never expired, because a trade record that disappears is not a record.

- a trading outcome is never expired; it is the part of the record that must survive
- the journal is the default, and its lifetime is decided by topic class, not by age alone
- sealing is about the size of the hot file, not about the calendar
- sealing never invalidates the index: offsets stay valid because the line does not change

Everything else goes to the bronze journal. There the topic class decides the lifetime: market and intelligence traffic is the bulk of the volume and lives long enough to replay; control and health messages are small, high-value and short-lived. Finally the segment is measured: past a gigabyte it is sealed and compressed, and the index keeps pointing into it.

5 Beneath the lake

WHAT THIS SHOWS The filesystem properties that let a case file be called evidence a year later.

Underneath the lake there is a filesystem and nothing else. The properties that follow from that are worth stating plainly, because they are the reason a case file can be called evidence.

PROPERTY	CONSEQUENCE
one line, one envelope, append only	a line never changes after it is written
plain UTF-8 JSON	grep, jq, awk and a shell are enough to read it
no service dependency to read	an investigator does not need the platform running
rotation by size, then gzip	the working journal stays small and fast
expiry by window	the record has a stated lifetime, not an accidental one
offsets in memory, rebuilt on boot	the index is disposable, the journal is not

The separation matters architecturally: the journal is the durable fact, the index is a convenience that can be thrown away and rebuilt. A corruption in the index costs a restart; a corruption in the journal costs history. Only the second one is serious, and the design keeps them apart.

Crossing concerns — time, identity and generations

WHAT THIS SHOWS Time, identity and generations, modelled once in the envelope rather than per context.

Three things are shared by every context and are therefore modelled once, in the envelope.

CONCERN	FIELD	RULE
when it was computed	computed_at	staleness is measured from here, never from arrival
who is asking	cid	one identity follows work across contexts
what changed	generation	a gap is a missing message, not an accident
what it read	refs	declared or derived, always with age
what happened to it	hops	every stage, with outcome and duration

A correlation id is minted locally at the boundary, so work can start without a central registry. Mapping it centrally and resolving it are separate, gated operations — a reader that cannot resolve still knows which id it was handed.

What the model deliberately refuses to do

WHAT THIS SHOWS The boundaries the model will not pretend to cross, stated so they can be argued with.

A model is also a list of things it will not pretend to know. These are the boundaries, stated so they can be argued with.

- it does not reconstruct what a producer read if the producer did not say so — it derives and labels
- it does not treat a dashboard as the record; the journal is the record
- it does not let a viewer write, which is why the explorer has no write path
- it does not hide a loss: a losing exit is booked, not deferred forever
- it does not call a stopped book running, or an empty book profitable

Colophon

WHAT THIS SHOWS Where this document comes from, and how to regenerate it.

Platform build 1.0.0 · 823eb7a · 2026-10-21 · domain model · revision 1.0

© 2026 CryptAlyst · designed by Andrew Preston · built by the CryptAlyst engineering team

The text lives once in content.py; the Markdown and this PDF are both generated from it, so they cannot disagree. The figures are drawn as SVG by diagrams.py and cover.py, rendered to PNG by render_figs.py, and placed here by build_pdf.py.

ARTIFACT	COMMAND
figures	python3 diagrams.py && python3 cover.py && python3 render_figs.py
markdown	python3 build_md.py
pdf	python3 build_pdf.py && libreoffice --convert-to pdf