



Common Sheets:
500 GRID
600 USB_POWER
700 MCU

Module Specific:
800 HWCFG
900 LED
1000 UI



1000



Sheet: /UI_POT/
File: UI_POT.kicad_sch

Title:

Size: A4

Date:

KiCad E.D.A. 8.0.6

Rev:

Id: 2/10

1000

Simulation:
<http://tinyurl.com/y229mt4>



Sheet: /UI_BUTTON/ File: UI_BUTTON.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. 8.0.6	Id: 3/10	

900



Sheet: /UI_LED/
File: UI_LED.kicad_sch

Title:

Size: A4


Date:

KiCad E.D.A. 8.0.6

Rev:

Id: 4/10

1000



1000



Sheet: /sheet5D8763D6/ File: UI_MUX.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. 8.0.6	Id: 6/10	




500

GRID Connector
Bi-Directional Data
2x SYNC



Board Mounting Pattern



Sheet: /MCU/sheet5D85C9EA/
File: GRID.kicad_sch

Title:

Size: A4
KiCad E.D.A. 8.0.6

Date:

Rev:
Id: 8/10

600

ESD Diodes

ESD protection for all of the externally accessible nets.



+3V3 LDO Regulators

Regulators for generating independent power rails for the microcontroller and the user interface.



Sheet: /MCU/Sheet60F06FE1/
File: USB_POWER.kicad_sch

Title:

Size: A4

Date:

KiCad E.D.A. 8.0.6

Rev:

Id: 9/10

800



Board Identification

Grid firmware can identify the hardware and the board revision through a 3 wire serial interface using one or more shift register as read only memory. The content of the memory is defined by pulling the inputs high or low through pcb traces or solderable configuration jumpers.

4b'Model + 4b'Revision + nb'Reserved (Multiple shift registers)

- D0: MODEL (LSB)
- D1: MODEL
- D2: MODEL
- D3: MODEL (MSB)
- D4: REVISION (LSB)
- D5: REVISION
- D6: REVISION
- D7: REVISION (MSB)

Model Codes (D3–D0):

- Po16 0000
- Bo16 0001
- PBF4 0010
- EN16 0011
- ...

Revision Codes (D7–D4):

- RevA 0000
- RevB 0001
- RevC 0010
- RevD 0011
- ...

Sheet: /HWCFG/ File: HWCFG.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. 8.0.6	Id: 10/10	