









1000



Sheet: /UI_POT_BTN/
File: UI_POT_BTN.kicad_sch

Title:

Size: A4

Date:





KiCad E.D.A. 8.0.4

Rev:

Id: 2/11

1000

Simulation:
<http://tinyurl.com/y229mty4>



Sheet: /UI_BUTTON/
File: UI_BUTTON.kicad_sch

Title:

Size: A4

Date:

KiCad E.D.A. 8.0.4

Rev:

Id: 3/11

900



Sheet: /UI_LED/
File: UI_LED.kicad_sch

Title:

Size: A4
KiCad E.D.A. 8.0.4


Date:

Rev:
Id: 4/11

1000



1000



Sheet: /sheet5D8763D6/
File: UI_MUX.kicad_sch

Title:

Size: A4 Date:

KiCad E.D.A. 8.0.4

Rev:

Id: 6/11

700



500

GRID Connector
Bi-Directional Data
2x SYNC

Board Mounting Pattern



Sheet: /MCU/sheet5D85C9EA/ File: GRID.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. 8.0.4		Id: 8/11

[illegible]

Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. 8.0.4		Id: 9/11

800

RIGHT SCREEN

LEFT SCREEN

U801 74HC165

HWCFG_LOW

HWCFG_HIGH

HWCFG_CLOCKD

HWCFG_SHIFTD

HWCFG_DATA

HWCFG_HIGH

HWCFG_LOW

C801 100n

Sheet: /HWCFG/
File: HWCFG.kicad_sch

Title:

Size: A4	Date:	Rev:
KiCad E.D.A. 8.0.4		Id: 10/11

Grid firmware can identify the hardware and the board revision through a 3 wire serial interface using one or more shift register as read only memory. The content of the memory is defined by pulling the inputs high or low through pcb traces or solderable configuration jumpers.

D0: MODEL (LSB)
D1: MODEL
D2: MODEL
D3: MODEL (MSB)
D4: REVISION (LSB)
D5: REVISION
D6: REVISION
D7: REVISION (MSB)

Po16	0000
Bo16	0001
PBF4	0010
EN16	0011
...	

```
RevA 0000
RevB 0001
RevC 0010
RevD 0011
...
```

Sheet: /HWCFG/ File: HWCFG.kicad_sch	
Title:	
Size: A4	Date:
KiCad E.D.A. 8.0.4	Id: 10/11

1000

