

UI_BUTTON

OUT_12

OUT_13

OUT_14

OUT_15

ANA_12

ANA_13

ANA_14

ANA_15

File: UI_BUTTON.kicad_sch

UI_LED

LED_DATA_IN

LED_DATA_OUT

File: UI_LED.kicad_sch

MCU

LED_DATA_OUT

HWCFG_SHIFT

HWCFG_CLOCK

HWCFG_DATA

File: MCU.kicad_sch

Sheet5D7C8BFD

ANA_0

ANA_1

ANA_4

ANA_5

ANA_8

ANA_9

ANA_12

ANA_13

IN_0

IN_1

IN_2

IN_3

IN_4

IN_5

IN_6

IN_7

OUTD

ADDRESS_A

ADDRESS_B

ADDRESS_C

ESP_GPIO_1

ESP_GPIO_18

ESP_GPIO_37

ESP_GPIO_36

ESP_GPIO_35

File: UI_MUX.kicad_sch

sheet5D8763D6

ANA_2

ANA_3

ANA_6

ANA_7

ANA_10

ANA_11

ANA_14

ANA_15

IN_0

IN_1

IN_2

IN_3

IN_4

IN_5

IN_6

IN_7

OUTD

ADDRESS_A

ADDRESS_B

ADDRESS_C

ESP_GPIO_2

ESP_GPIO_5

ESP_GPIO_4

ESP_GPIO_3

File: UI_MUX.kicad_sch

HWCFG

HWCFG_SHIFT

HWCFG_CLOCK

HWCFG_DATA

File: HWCFG.kicad_sch

Common Sheets:

500 GRID

600 USB_POWER

700 MCU

Module Specific:

800 HWCFG

900 LED

1000 UI

Sheet: /

File: PCBA-PBF4.kicad_sch

Title:

Size: A3

Date:

Rev:

KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1

Id: 1/10

1000



Sheet: /UI_POT/
File: UI_POT.kicad_sch

Title:

Size: A4

Date:



KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1

Rev:

Id: 2/10

1000

Simulation:
<http://tinyurl.com/y229mt4>



Sheet: /UI_BUTTON/ File: UI_BUTTON.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1		Id: 3/10

900



Sheet: /UI_LED/
File: UI_LED.kicad_sch


Title:

Size: A4
KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1

Date:

Rev:
Id: 4/10





1000



1000




700




QSPI Flash memory


This memory can be accessed through the QSPI interface of the MCU. Can be used for configuration, static data or program execution.



500



Board Mounting Pattern



Sheet: /MCU/sheet5D85C9EA/ File: GRID.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1		Id: 8/10

600


ESD Diodes

ESD protection for all of the externally accessible nets.



+3V3 LDO Regulators

Regulators for generating independent power rails for the microcontroller and the user interface.



Sheet: /MCU/Sheet60F06FE1/
File: USB_POWER.kicad_sch

Title:

Size: A4

Date:

KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1

Rev:

Id: 9/10

800



Board Identification

Grid firmware can identify the hardware and the board revision through a 3 wire serial interface using one or more shift register as read only memory. The content of the memory is defined by pulling the inputs high or low through pcb traces or solderable configuration jumpers.

4b'Model + 4b'Revision + nb'Reserved (Multiple shift registers)

- D0: MODEL (LSB)
- D1: MODEL
- D2: MODEL
- D3: MODEL (MSB)
- D4: REVISION (LSB)
- D5: REVISION
- D6: REVISION
- D7: REVISION (MSB)

Model Codes (D3-D0):

Po16 0000
Bo16 0001
PBF4 0010
EN16 0011
...

Revision Codes (D7-D4):

RevA 0000
RevB 0001
RevC 0010
RevD 0011
...

Sheet: /HWCFG/ File: HWCFG.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. kicad-cli 7.0.9-7.0.9-ubuntu23.04.1		Id: 10/10