

# Designing Any Imaging System from Natural Language: Agent-Constrained Composition over a Finite Primitive Basis

Chengshuai Yang

NextGen PlatformAI C Corp, USA

Correspondence: integrityyang@gmail.com

March 14, 2026

**Summary.** Designing a computational imaging system requires weeks of specialist effort per modality [1]. Building on a companion representation theorem [3], we introduce `spec.md`—an 8-field specification format—and three agents (Plan, Judge, Execute) that translate a one-sentence description into a validated forward model with bounded reconstruction error. Our central result (Theorem 2) decomposes the design-to-real error into five independently measurable terms, each linked to a compiler gate and corrective action. On 6 real-data modalities spanning all 5 carrier families (CT, MRI, CASSI, CACTI, ultrasound, electron ptychography), the framework matches expert-tuned quality ( $99.6 \pm 3.1\%$ ) with up to  $420\times$  reduction in setup time. The Judge rejects ill-posed designs with  $F_1 = 0.96$ ; a prospective algorithm-comparison study on 5 modalities—including two novel system designs (lensless imaging, structured illumination microscopy)—confirms that forward-model selection dominates reconstruction algorithm choice (inter-method PSNR CoV  $< 5.7\%$ ). Of 170 compilable modalities, 36 have quantitative reconstruction validation and 6 are validated on real data.

## Introduction

Every computational imaging system maps an unknown object  $x$  to measurements  $y = A(x) + \text{noise}$  via a forward model  $A$ , and reconstruction inverts this mapping [9, 10]. Designing  $A$ —selecting operators, setting parameters, validating consistency—requires weeks of specialist effort per modality [12, 30], creating an *expertise bottleneck* that excludes the broader scientific community from prototyping imaging instruments.

The parallel with genomics is instructive: before FASTA [41] and the Sequence Read Archive [42], biological sequence data was communicated through idiosyncratic, non-interoperable formats. Computational imaging today is in an analogous pre-standardisation state.

A companion paper [3] proved that 11 canonical primitives suffice to represent any imaging forward model across 170 modalities and 5 carrier families, building on compressed sensing [12, 13] and inverse problems theory [11, 35]. Each primitive is implemented at four fidelity tiers (Tier-0 geometric through Tier-3 full-physics). This *Finite Primitive Basis* (FPB) is the representation language, but representation alone does not automate design. **This paper’s contribution is the design layer:** the formal bridge from natural-language intent to bounded real-system reconstruction error.

We make the scope of ‘designable’ precise:

**Definition 1** (Designable Imaging System). *An imaging system  $A$  is designable within this framework if:*


1.  $A$  admits a finite DAG decomposition over the 11 FPB primitives with representation error

- 42  $\varepsilon_{FPB} < 0.01$ ;
- 43 2. The carrier belongs to one of 5 families: *photon*, *X-ray*, *electron*, *acoustic*, or *spin/particle*;
- 44 3. The system operates at one of the four fidelity tiers (Tier-0 through Tier-3);
- 45 4. All parameters are finitely specifiable with known physical bounds.

46 This definition encompasses 170 modalities across 22 domains (Figure 1, Extended Data Table 6).  
 47 We build the *design layer* on top of the FPB. Our contributions are:

- 48 1. **spec.md**: a structured 8-field specification format that decouples the imaging problem  
 49 (*what*) from the numerical method (*how*) and the hardware implementation (*with what*),  
 50 serving as a shareable, peer-reviewable scientific artifact (“[The spec.md Specification](#)  
 51 [Format](#)”).
- 52 2. **Three-agent pipeline**: Plan ( $\mathcal{A}_P$ ), Judge ( $\mathcal{A}_J$ ), and Execute ( $\mathcal{A}_E$ ) agents that generate,  
 53 formally verify, and execute specifications over the FPB (“[The Three-Agent Pipeline](#)”).
- 54 3. **Design-to-real error theorem**: the total reconstruction error decomposes into five  
 55 independently bounded, independently measurable terms, each linked to a compiler gate  
 56 and a corrective action (Theorem 2).

57 **Scope.** Of 170 compilable modalities, 36 have quantitative reconstruction validation; 6 are  
 58 validated on real data spanning all 5 carrier families. The remaining  $\sim 134$  pass all compiler gates  
 59 but lack per-modality benchmarks. Tier-lifting is demonstrated on 2 cross-tier combinations; the  
 60 agents depend on current LLM capabilities.



**Figure 1. Validation pyramid.** Of 170 designable modalities, all compile; 36 have quantitative reconstruction benchmarks; 6 are validated on real measured data spanning all 5 carrier families; 3 have ground-truth PSNR comparisons (CT, MRI, CASSI). Each tier is a strict subset.

## 61 Results

### 62 The spec.md Specification Format

63 The framework’s central design choice is that **spec.md**—not code—is the canonical scientific  
 64 artifact. A specification separates the imaging problem (*what*) from the numerical method (*how*)  
 65 and the hardware (*with what*), enabling sharing, version control, and peer review independently  
 66 of implementation [2]. A reviewer can verify—by running the 6-gate compiler—that a forward  
 67 model is physically consistent *without reading code*. A **spec.md** has eight mandatory fields  
 68 (Figure 2): seven physics fields plus a **system\_elements** field that connects the specification to  
 69 hardware feasibility.

### 70 The Three-Agent Pipeline

71 **Plan Agent** ( $\mathcal{A}_P$ ) generates a **spec.md** from natural language, selecting FPB primitives,  
 72 parameters, and noise models from the 170-modality registry.

**Eight-field schema:** modality | carrier | geometry | object | forward\_model | noise | target | system\_elements

**(a) Clinical CT**

modality: computed\_tomography carrier: xray  
 geometry: parallel\_beam, n\_angles=128  
 object: 128×128 image, non-negative  
 forward\_model: Radon( $\Pi$ )  $\rightarrow$  Detect( $D$ , intensity)  
 noise: Poisson,  $I_0=1e4$  target: PSNR  $\geq 30$  dB  
 system\_elements: source=X-ray tube 120 kVp, detector=flat-panel 0.4 mm


**(b) CASSI (spectral)**

modality: cassi carrier: photon  
 geometry: coded\_aperture + disperser,  $\lambda=[400,700]$  nm  
 object: 256×256×28 spectral cube  
 forward\_model: Modulate( $M$ )  $\rightarrow$  Disperse( $W$ )  $\rightarrow$  Accumulate( $\Sigma$ )  $\rightarrow$  Detect( $D$ )  
 noise: Gaussian,  $\sigma=0.01$  target: PSNR  $\geq 28$  dB  
 system\_elements: source=broadband LED, optics=coded aperture + prism, detector=CMOS 2048×2048

**(c) Accelerated MRI**

modality: mri carrier: spin  
 geometry: cartesian\_kspace, acceleration=4x  
 object: 256×256 complex image  
 forward\_model: Modulate( $M$ , coil)  $\rightarrow$  Encode( $F$ , kspace)  $\rightarrow$  Sample( $S$ )  $\rightarrow$  Detect( $D$ )  
 noise: Gaussian, SNR=30 dB target: SSIM  $\geq 0.9$   
 system\_elements: source=main magnet 3T, optics=RF coils ×4, detector=ADC 16-bit

**Figure 2. The spec.md specification format.** Eight mandatory fields fully determine an imaging system design. Seven physics fields specify the forward model; the eighth (**system\_elements**) connects to hardware feasibility and cost. Three examples span X-ray (CT), optical (CASSI), and spin (MRI) carriers. Each **forward\_model** field is a primitive chain over the 11 FPB operators.



**Figure 3. Specification-driven design pipeline.** A natural-language prompt is the sole user input.  $\mathcal{A}_P$  generates a **spec.md**;  $\mathcal{A}_J$  validates it via a 6-gate compiler (Gates 1–3 from FPB compiler [3]; Gates 4–6 new to this work; mapping to Theorem 2: DAG  $\rightarrow \varepsilon_{\text{spec}}$ , Chain  $\rightarrow \varepsilon_{\text{trans}}$ , Bounds  $\rightarrow$  complexity, NL  $\rightarrow \varepsilon_{\text{param}}$ , Adj.  $\rightarrow$  consistency, Err.  $\rightarrow \varepsilon_{\text{FPB}}$ ); rejected designs trigger redesign (dashed blue, up to 3 rounds).  $\mathcal{A}_E$  executes reconstruction and outputs  $\hat{A}$  with an explicit  $\varepsilon$ -bound report. See Figure 4 for per-modality error breakdown.

**Judge Agent** ( $\mathcal{A}_J$ ) validates via a 6-gate compiler that combines 3 gates inherited from the FPB compiler [3]—(1) DAG acyclicity, (2) canonical chain fidelity, (3) complexity bounds—with 3 new agent-validation gates: (4) nonlinear constraints (VC dimension  $\leq 3$ ), (5) adjoint consistency, (6) representation error. Failures trigger rejection; the Plan Agent regenerates (up to 3 rounds).

**Execute Agent** ( $\mathcal{A}_E$ ) selects the reconstruction algorithm, executes it, and predicts quality from analytical estimates (condition number, noise amplification) combined with calibrated lookup.

The Judge executes *deterministic verification*, not prediction. If certified, every term in Theorem 2 is explicitly bounded—a formal contract independent of LLM quality. Bad specifications are caught by physics checks regardless of the Plan Agent’s accuracy.

## Design-to-Real Error Bound

The following theorem converts the implicit gap between a designed model and reality into an explicit five-term error budget—a *formal contract* between the framework and the user. Each term has a known physical origin, measurement procedure, and corrective action.

**Theorem 2** (Design-to-Real Error Decomposition). *Let  $A_{true}$  be the true imaging forward model and  $A_{agent}$  the agent-designed model for a designable system (Definition 1). Let  $\hat{x}$  be the regularized reconstruction from  $A_{agent}$  and  $x^*$  the true object. Under Assumptions A1–A4 (Methods), the reconstruction error satisfies:*

$$\|\hat{x} - x^*\| \leq \underbrace{\varepsilon_{FPB}}_{\text{basis}} + \underbrace{\varepsilon_{spec}}_{\text{specification}} + \underbrace{\varepsilon_{trans}}_{\text{translation}} + \underbrace{\varepsilon_{param}}_{\text{parameter}} + \underbrace{\varepsilon_{unmod}}_{\text{unmodeled}} + \varepsilon_{recon} \quad (1)$$

where each design-error term is independently bounded and independently measurable:

- $\varepsilon_{FPB} < 0.01$ : FPB representation error. Measured by: Gate 6. Guaranteed by: the basis theorem [3].
- $\varepsilon_{spec} = 0$  when all 6 compiler gates pass. Bounded by:  $C_1 \cdot \delta_{spec}$  otherwise.
- $\varepsilon_{trans} = 0$  when the canonical chain matches the 36-modality registry (31/36 = 86%). Bounded by:  $C_2 \cdot \delta_{chain}$  otherwise.
- $\varepsilon_{param} \leq \frac{2B}{\alpha + \lambda} L_A \|\theta_{agent} - \theta_{true}\|$ , where  $L_A$  is the operator Lipschitz constant (computed per primitive by Gate 4),  $\alpha$  is the coercivity constant,  $\lambda$  the regularization weight, and  $B$  a signal bound. Reducible by: calibration.
- $\varepsilon_{unmod} = 0$  at Tier-3; otherwise reducible by tier-lifting (“*Cross-Tier Hybrid Reconstruction*”).
- $\varepsilon_{recon}$ : irreducible reconstruction error (noise floor + regularization bias), independent of the design.

**Compiler–theorem link.** When all 6 gates pass:  $\varepsilon_{FPB} < 0.01$ ,  $\varepsilon_{spec} = 0$ , and  $\varepsilon_{param}$  is bounded by the Lipschitz constant from Gate 4. With canonical chain match:  $\varepsilon_{trans} = 0$ ; at Tier-3:  $\varepsilon_{unmod} = 0$ . In practice, the dominant residual is  $\varepsilon_{param}$ , reducible by calibration (Figure 4). The decomposition functions as a diagnostic protocol: each  $\varepsilon$  term maps to a corrective action. Full proof in Methods.

## Cross-Modality Validation

We validated the framework on all 170 modalities. For each, the Plan Agent generated a `spec.md` from a one-sentence description, the Judge validated it, and the Execute Agent predicted reconstruction quality. Table 1 reports 14 representative modalities spanning all 5 carrier families

(6 with real measured data), grouped by carrier; full results for all 36 validated modalities appear in Methods.

**Table 1.** Cross-modality validation (14 of 36 modalities), grouped by carrier family.  $\rho_{\text{recov}}$ : 4-scenario recovery ratio [3]. 95% CIs via bootstrap ( $n=1000$ ). Bold = real measured data (challenging conditions: 60-view CT, 4-coil MRI);  $\dagger$  = self-reference metric (no ground truth); \* = new system designs validated in the algorithm-comparison study (Table 7).

| Modality               | Chain                                                       | Carrier  | PSNR (dB)      | $\rho_{\text{time}}$ | $\rho_{\text{recov}}$ | Data                             |
|------------------------|-------------------------------------------------------------|----------|----------------|----------------------|-----------------------|----------------------------------|
| <i>X-ray</i>           |                                                             |          |                |                      |                       |                                  |
| CT                     | $\Pi \rightarrow D$                                         | X-ray    | $19.6 \pm 2.9$ | 420                  | $\sim 1.0$            | <b>Real</b>                      |
| <i>Optical photons</i> |                                                             |          |                |                      |                       |                                  |
| CASSI                  | $M \rightarrow W \rightarrow \Sigma \rightarrow D$          | Photon   | $15.7 \pm 2.3$ | 310                  | 0.85                  | <b>Real</b>                      |
| CACTI                  | $M \rightarrow \Sigma \rightarrow D$                        | Photon   | $30.2 \pm 1.1$ | 300                  | $\sim 1.0$            | <b>Real</b>                      |
| OCT                    | $P + P \rightarrow \Sigma \rightarrow D$                    | Photon   | $30.5 \pm 1.1$ | 290                  | 0.86                  | Synth.                           |
| SIM[34]                | $M \rightarrow C \rightarrow D$                             | Photon   | $27.7 \pm 2.0$ | 350                  | 0.92                  | <b>Synth.*</b>                   |
| Ptychography[33]       | $M \rightarrow P \rightarrow D$                             | Photon   | $28.4 \pm 1.6$ | 270                  | 0.83                  | Synth.                           |
| Lensless               | $C \rightarrow D$                                           | Photon   | $8.1 \pm 3.6$  | 340                  | 0.90                  | <b>Synth.*</b>                   |
| DOT[31]                | $M \rightarrow R \rightarrow P \rightarrow R \rightarrow D$ | Photon   | $24.1 \pm 2.1$ | 190                  | 0.72                  | Synth.                           |
| <i>Spin</i>            |                                                             |          |                |                      |                       |                                  |
| MRI                    | $M \rightarrow F \rightarrow S \rightarrow D$               | Spin     | $22.2 \pm 3.3$ | 380                  | $\sim 1.0$            | <b>Real</b>                      |
| <i>Acoustic</i>        |                                                             |          |                |                      |                       |                                  |
| Ultrasound             | $P \rightarrow R \rightarrow P \rightarrow D$               | Acoustic | $27.9 \pm 1.4$ | 250                  | 0.95                  | <b>Real<math>^\dagger</math></b> |
| <i>Electron</i>        |                                                             |          |                |                      |                       |                                  |
| E-ptychography         | $M \rightarrow P \rightarrow D$                             | Electron | $28.8 \pm 1.5$ | 260                  | $\sim 1.0$            | <b>Real<math>^\dagger</math></b> |
| <i>Particle</i>        |                                                             |          |                |                      |                       |                                  |
| PET                    | $\Pi \rightarrow D$                                         | Particle | $26.3 \pm 1.8$ | 220                  | 0.78                  | Synth.                           |
| SPECT                  | $M \rightarrow \Pi \rightarrow D$                           | Particle | $25.8 \pm 1.7$ | 200                  | 0.76                  | Synth.                           |
| Light field            | $M \rightarrow C \rightarrow S \rightarrow D$               | Photon   | $29.2 \pm 1.2$ | 280                  | 0.85                  | Synth.                           |


Across all 36 modalities: mean  $\rho_{\text{recov}} = 0.85 \pm 0.07$  (95% CI: [0.82, 0.88]) [3]. The agent–expert quality gap (Cohen’s  $d = 0.31$ ) indicates practical equivalence; time ratios  $\rho_{\text{time}}$  range from  $190\times$  to  $420\times$  [15, 16]. All 170 modalities compile (100% pass rate, Gates 1–4); canonical chain fidelity: 31/36 (86%).

**Theorem tightness.** The tightness ratio  $\tau = \varepsilon_{\text{predicted}}/\varepsilon_{\text{observed}}$  across 6 real-data modalities:  $\tau \in [1.8, 5.2]$ , median 2.9 (CT 2.1, MRI 2.4, CASSI 3.8). Ratios below 10 are typical for operator-perturbation bounds [26]; values near 2 indicate the bound captures the dominant mechanism with minimal slack.

## Real-Data Validation

**CT** (LoDoPaB [4],  $n=10$ ): 60-view fan-beam projections. Agent PSNR  $19.6 \pm 2.9$  dB; expert FISTA+TV [36]  $19.1 \pm 3.2$  dB (quality ratio 102.6%,  $\rho_{\text{time}} \approx 420$ ). **MRI** (M4Raw [5],  $n=10$ ): 4-coil,  $\sim 4\times$  undersampled. Agent  $22.2 \pm 3.3$  dB; expert FISTA+TV [36]  $21.6 \pm 3.4$  dB (102.8%). **CASSI** (KAIST [6],  $n=5$ ): 28-band coded aperture. Agent  $15.7 \pm 2.3$  dB; expert FISTA+TV [25]  $15.4 \pm 2.3$  dB (101.9%). **CACTI** ( $n=4$ ): real video [30];  $\rho_{\text{recov}} \approx 1.0$  after autonomous mask-alignment calibration. **Ultrasound** (PICMUS [7],  $n=5$ ): in-vivo carotid, self-reference protocol. After SoS calibration, SSIM recovers to  $0.98 \pm 0.01$  ( $\rho_{\text{recov}} \approx 0.95$ ). **E-ptychography** (SrTiO<sub>3</sub> 4D-STEM [8, 32]): iCoM phase retrieval;  $\rho_{\text{recov}} = 1.00$  after probe-position correction.

Across 6 real-data modalities spanning all 5 carrier families: mean quality ratio  $102.4 \pm 0.5\%$  (3 with ground truth) and  $\rho_{\text{recov}} \geq 0.95$  (3 via self-reference), consistent across carriers from X-ray to electron. Two additional synthetic modalities—**lensless** ( $n=10$ ,  $C \rightarrow D$ , Wiener/FISTA+TV/PnP+TV) and **SIM** ( $n=10$ ,  $M \rightarrow C \rightarrow D$ , Wiener-SIM/FISTA+TV/PnP+TV)—



**Figure 4. Error decomposition by modality.** Stacked bars show the relative contribution of each Theorem 2 error term for 6 representative modalities. For well-conditioned systems (CT, MRI, e-ptychography), parameter mismatch  $\epsilon_{\text{param}}$  dominates and is reducible by calibration. For scattering-dominated systems (DOT), unmodeled physics  $\epsilon_{\text{unmod}}$  dominates and requires tier-lifting.  $\epsilon_{\text{FPB}} < 1\%$  in all cases.  $\epsilon_{\text{spec}} = \epsilon_{\text{trans}} = 0$  for 31/36 modalities; CASSI shows nonzero  $\epsilon_{\text{trans}}$  due to dispersion-accumulation chain ambiguity.

119 demonstrate the framework’s ability to design novel imaging systems by composing existing  
 120 primitives in new chains.

## 121 Agent Ablation Study

122 We ablated the pipeline on 12 representative modalities spanning all 5 carrier families, with  
 123 5 independent trials per configuration (300 total runs). Table 2 reports the main result: **the**  
 124 **full pipeline is the only configuration achieving bounded-error success on all 12**  
 125 **modalities across all 5 trials.**

**Table 2.** Ablation study (5 trials  $\times$  12 modalities = 300 runs). “Valid”: passes all compiler gates. “ $\leq \epsilon$ ”: reconstruction within Theorem 2 error bound. No single agent is dispensable.


| Configuration                                            | Valid   | $\leq \epsilon$ | Redesign      | Time    | Dominant failure                   |
|----------------------------------------------------------|---------|-----------------|---------------|---------|------------------------------------|
| Full ( $\mathcal{A}_P + \mathcal{A}_J + \mathcal{A}_E$ ) | 12/12   | 12/12           | $1.7 \pm 0.6$ | 4.8 min | —                                  |
| No $\mathcal{A}_J$                                       | 8.2/12  | 6.4/12          | 0             | 2.9 min | Invalid spec, unbounded $\epsilon$ |
| No $\mathcal{A}_E$                                       | 12/12   | 9.6/12          | $1.7 \pm 0.6$ | 3.4 min | Suboptimal parameters              |
| No $\mathcal{A}_P$ (manual)                              | 10.4/12 | 10.4/12         | 0             | 52 min  | Human error (14%)                  |
| Template only                                            | —       | 3/12            | 0             | 0.5 min | No coverage (75%)                  |

126 **Without  $\mathcal{A}_J$ :** 4/12 physically invalid specifications pass; 2 additional produce unbounded error.  
 127 **Without  $\mathcal{A}_E$  (Execute):** all pass validation but mean PSNR drops 2.1 dB. **Without  $\mathcal{A}_P$ :**  
 128 manual specification averages 52 min with 14% error rate. Random specification passes Gate 1 in  
 129 12% of cases but never passes Gates 4–5; retrieval-only covers 22/36 modalities at 4.2 dB below  
 130 the full pipeline.

## 131 Failure Analysis

132 We characterise four failure modes (Figure 4): **(1) Scattering-dominated systems** (DOT [31],  
 133 Compton):  $\epsilon_{\text{unmod}}$  is large at Tier-2 (7.8% for DOT); mitigated by tier-lifting. **(2) LLM**  
 134 **misspecification:** 4% of test cases have subtle parametric errors; the 6-gate compiler catches  
 135 96%. **(3) Multi-parameter mismatch:**  $\rho_{\text{recov}}$  drops below 0.9 when  $>2$  parameters are  
 136 simultaneously off (CASSI: 0.85). **(4) Chain ambiguity:** 5/36 modalities have non-matching





**Figure 5. Agent vs. expert reconstruction on real data.** Ground truth, Agent reconstruction (automated pipeline), Expert reconstruction (established library method), and amplified absolute difference (5 $\times$ , inferno colormap) for 3 real-data modalities. CT: 60-view fan-beam LoDoPaB [4]; MRI: 4-coil 4 $\times$  undersampled M4Raw [5]; CASSI: 28-band KAIST TSA [6]. Both methods receive only measurements and calibration metadata (no ground truth). The small inter-method differences ( $<1.5$  dB) confirm that forward-model specification, not algorithm choice, is the primary quality determinant (Extended Data Table 7). PSNR/SSIM are scale-invariant (both images normalised to  $[0, 1]$ ).

chains due to  $\Sigma$ - $D$  merging.

## Judge and Execute Agents

**Judge rejection accuracy** ( $n=150$ : 75 valid, 75 ill-posed). Precision = Recall = 96.0% ( $F_1 = 0.96$ ): TP = 72, FP = 3, FN = 3, TN = 72. The 3 false positives had parametric values 1–5% outside bounds; the 3 false negatives were conservative CFL checks. Mean redesign rounds: 1.4.

**Execute Agent quality prediction** (36 modalities). Overall MAE: 1.8 dB ( $R^2 = 0.91$ ; Extended Data Figure 6). By group: well-characterised ( $n=20$ ) 0.9 dB; moderate ( $n=10$ ) 2.1 dB; scattering-dominated ( $n=6$ ) 3.8 dB.

## Expert Comparison

**Table 3.** Agent vs. established reconstruction methods. “Agent”: best-performing automated algorithm; “Expert”: established variational method (FISTA+TV [36]). Bold = real measured data; \* = new system designs with dedicated FISTA and PnP+TV algorithms. Quality > 100% indicates Agent slightly exceeds Expert. Expert times from specification to first successful reconstruction; remaining estimated from published timelines (see Methods).

| Modality            | PSNR (dB) |        | Setup  |        | Quality | LoC       |
|---------------------|-----------|--------|--------|--------|---------|-----------|
|                     | Agent     | Expert | Agent  | Expert |         |           |
| <b>CT (real)</b>    | 19.6      | 19.1   | 25 min | 7 d    | 102.6%  | 12 vs 340 |
| <b>MRI (real)</b>   | 22.2      | 21.6   | 20 min | 5 d    | 102.8%  | 14 vs 520 |
| <b>CASSI (real)</b> | 15.7      | 15.4   | 18 min | 4 d    | 101.9%  | 11 vs 280 |
| <b>Lensless*</b>    | 8.1       | 7.4    | 12 min | 2 d    | 109.5%  | 12 vs 180 |
| <b>SIM*</b>         | 27.7      | 26.2   | 15 min | 3 d    | 105.7%  | 10 vs 210 |
| OCT                 | 30.5      | 31.2   | 22 min | 6 d    | 97.8%   | 13 vs 450 |
| DOT                 | 24.1      | 25.3   | 30 min | 10 d   | 95.3%   | 15 vs 680 |

Mean quality ratio:  $103.4 \pm 4.6\%$ . Agent specifications: 10–15 lines; expert code: 180–680 lines. The two novel system designs (lensless, SIM) achieve quality ratios of 109.5% and 105.7%, demonstrating that the framework’s compositional approach extends naturally to new modalities.

**Prospective algorithm-comparison study.** To test whether forward-model selection or algorithm choice dominates quality, we ran 5 standard methods—including FISTA+TV [36] and PnP+TV [26]—on 5 modalities: 3 existing (CT, MRI, CASSI on harder conditions) and 2 novel system designs (lensless imaging, SIM), each with dedicated algorithms (Extended Data Table 7). Inter-method PSNR CoV is 3.7%, 5.7%, 1.9%, 4.0%, and 2.3% across the 5 modalities—much smaller than sample-to-sample variation ( $\sim 15\%$ ), confirming that *forward-model selection dominates algorithm choice* even for newly designed systems.

## Cross-Tier Hybrid Reconstruction

Each FPB primitive is implemented at four fidelity tiers: Tier-0 (geometric), Tier-1 (Fourier), Tier-2 (shift-variant), Tier-3 (full-physics; Extended Data Table 4). The *tier-lifting protocol* provides hybrid reconstruction via a Hybrid Proximal-Gradient method (Proposition 3, Methods), enabling the framework to handle scattering-dominated modalities where  $\varepsilon_{\text{unmod}}$  is large.

Tier-lifting validated on DOT (Tier-2→3:  $\varepsilon_{\text{unmod}}$  from 7.8% to  $< 10^{-12}$ ) and coherent imaging (Tier-1→3: 147% to  $< 10^{-12}$ ; Extended Data Table 5). The protocol preserves FPB structure: same primitives, same DAG, same `spec.md`—only fidelity changes.



## Discussion

The  $420\times$  setup-time reduction and  $103.4 \pm 4.6\%$  quality ratio across 5 carrier families mean that a scientist in any domain can prototype a computational imaging system from a one-sentence description without imaging-physics expertise. The algorithm-comparison study on 5 modalities—including 2 novel system designs (lensless imaging, SIM)—confirms that forward-model selection dominates algorithm choice (inter-method PSNR CoV  $< 5.7\%$ ), validating the specification-centric philosophy. Notably, the two novel systems, designed by composing existing primitives in new chains ( $C \rightarrow D$  for lensless,  $M \rightarrow C \rightarrow D$  for SIM), immediately achieve competitive quality without any new algorithmic development.

`spec.md` is designed to play for imaging an analogous standardisation role to that which FASTA played for genomics: decoupling the physics (*what*) from the numerics (*how*) and the hardware (*with what*), enabling sharing and peer review at the physics level [2]. The eighth field (`system_elements`) connects specifications to hardware feasibility, enabling the Judge Agent to assess cost and physical constraints alongside the mathematical forward model. An independence test confirmed reproducibility: three `spec.md` files reproduced PSNR within  $\pm 0.3$  dB across independent agent instances (see Methods). We propose that the community test this hypothesis by piloting `spec.md` as a journal supplement for computational imaging papers.

The five-term error decomposition (Theorem 2) functions as a formal contract: each  $\varepsilon$  term maps to a corrective action (Figure 4). The dominant residual is  $\varepsilon_{\text{param}}$ , reducible by calibration; the 4-scenario protocol [3] confirms  $\rho_{\text{recov}} \geq 0.85$  across all 5 carrier families.

**Relation to existing work.** AI for scientific discovery [19, 20, 22, 40], operator libraries [16–18, 26], and automated experiment design [11, 29] address related problems but none provide a formal error decomposition from natural-language intent to reconstruction quality. Theorem 2 assumes convex regularisation (Assumption A2); extension to non-convex priors [24, 27, 28] is empirically supported (PnP-NLM in Table 7) but not formally proven [26].

**Limitations.** (1) Agent quality depends on LLM capabilities; novel modalities may be mis-specified. (2) Quantitative reconstruction validated for 36/170 modalities; real data for 6. (3) Expert times rely partly on published estimates. (4) Execute Agent quality-prediction MAE degrades to 3.8 dB for scattering-dominated systems. (5) Tier-lifting demonstrated on 2 cross-tier combinations only. (6) Theorem assumes convex  $R(x)$ .

The validation pyramid ( $170 \rightarrow 36 \rightarrow 6$ ) identifies a clear path: extending benchmarks to the remaining  $\sim 134$  modalities, validating tier-lifting across additional Tier-3 physics, and improving calibration for scattering-dominated systems.

## Methods

### Proof of Theorem 2

#### Assumptions.

**A1. Coercivity.** The data-fidelity term  $f(x) = \|A(x) - y\|^2$  satisfies  $\langle \nabla f(x) - \nabla f(x'), x - x' \rangle \geq \alpha \|x - x'\|^2$  with coercivity constant  $\alpha = \sigma_{\min}^2(A) > 0$  (linear case) or  $\alpha > 0$  from restricted strong convexity (nonlinear case).

**A2. Regularisation.**  $R(x)$  is proper, convex, lower-semicontinuous, and  $\lambda > 0$ . The composite objective  $F(x) = f(x) + \lambda R(x)$  is  $\mu$ -strongly convex with  $\mu = \alpha + \lambda$  [35].

**A3. Lipschitz parameters.** Each FPB primitive  $A_i(\cdot; \theta_i)$  is  $L_i$ -Lipschitz continuous in its parameters:  $\|A_i(\cdot; \theta) - A_i(\cdot; \theta')\|_{\text{op}} \leq L_i \|\theta - \theta'\|$ . The DAG composition has Lipschitz constant  $L_A \leq \prod_i L_i$ , computed by Gate 4.

208 **A4. Bounded signal.**  $\|x^*\| \leq B$  for known bound  $B$ .

209 **Step 1: Operator decomposition.** The agent-designed operator differs from reality through  
 210 a chain of approximations:

$$A_{\text{true}} \xrightarrow{\delta_{\text{unmod}}} A_{\text{tier}} \xrightarrow{\delta_{\text{FPB}}} A_{\text{FPB}} \xrightarrow{\delta_{\text{spec}}} A_{\text{spec}} \xrightarrow{\delta_{\text{trans}}} A_{\text{DAG}} \xrightarrow{\delta_{\text{param}}} A_{\text{agent}}$$

211 where each  $\delta_i = \|A_i - A_{i-1}\|_{\text{op}}$  is the operator-norm difference at that stage. By the triangle  
 212 inequality:

$$\|A_{\text{agent}} - A_{\text{true}}\|_{\text{op}} \leq \delta_{\text{FPB}} + \delta_{\text{spec}} + \delta_{\text{trans}} + \delta_{\text{param}} + \delta_{\text{unmod}}. \quad (2)$$

213 **Step 2: Reconstruction perturbation.** Define  $x_{\text{oracle}} = \arg \min_x \|A_{\text{true}}(x) - y\|^2 + \lambda R(x)$   
 214 (oracle reconstruction using  $A_{\text{true}}$ ). Define  $\hat{x} = \arg \min_x \|A_{\text{agent}}(x) - y\|^2 + \lambda R(x)$  (agent recon-  
 215 struction). By the  $\mu$ -strong convexity of  $F$  (Assumptions A1–A2), the first-order optimality  
 216 conditions and the Cauchy–Schwarz inequality yield:

$$\|\hat{x} - x_{\text{oracle}}\| \leq \frac{2B}{\mu} \|A_{\text{agent}} - A_{\text{true}}\|_{\text{op}} = \frac{2B}{\alpha + \lambda} \|A_{\text{agent}} - A_{\text{true}}\|_{\text{op}}. \quad (3)$$

217 This is the *reconstruction stability bound*: the sensitivity of the reconstruction to operator  
 218 perturbation, controlled by coercivity  $\alpha$  and regularisation  $\lambda$ .

219 **Step 3: Define effective error terms.** For each  $i \in \{\text{FPB}, \text{spec}, \text{trans}, \text{param}, \text{unmod}\}$ , set  
 220  $\varepsilon_i = 2B \delta_i / (\alpha + \lambda)$ . Then:

$$\|\hat{x} - x_{\text{oracle}}\| \leq \varepsilon_{\text{FPB}} + \varepsilon_{\text{spec}} + \varepsilon_{\text{trans}} + \varepsilon_{\text{param}} + \varepsilon_{\text{unmod}}. \quad (4)$$

221 **Step 4: Total error.**  $\|\hat{x} - x^*\| \leq \|\hat{x} - x_{\text{oracle}}\| + \|x_{\text{oracle}} - x^*\|$ . The second term  $\varepsilon_{\text{recon}} =$   
 222  $\|x_{\text{oracle}} - x^*\|$  is the irreducible reconstruction error (noise amplification + regularisation bias),  
 223 independent of the design. Combining:

$$\|\hat{x} - x^*\| \leq (\varepsilon_{\text{FPB}} + \varepsilon_{\text{spec}} + \varepsilon_{\text{trans}} + \varepsilon_{\text{param}} + \varepsilon_{\text{unmod}}) + \varepsilon_{\text{recon}}.$$

224 **Step 5: Bounding each term.**

- 225 (a)  $\delta_{\text{FPB}} < 0.01$  by the FPB basis theorem [3]. Verified by Gate 6 of the compiler:  $\varepsilon =$   
 226  $\mathbb{E}[\|A_{\text{agent}}(x) - A_{\text{true}}(x)\| / \|A_{\text{true}}(x)\|] < 0.01$  over 5 random test vectors. Hence  $\varepsilon_{\text{FPB}} <$   
 227  $0.01 \cdot 2B / (\alpha + \lambda)$ .
- 228 (b)  $\delta_{\text{spec}} = 0$  when all 6 compiler gates pass. *Condition*: Gates 1–5 jointly verify that the  
 229 `spec.md` fully and correctly specifies the FPB composition: DAG acyclicity (Gate 1), chain  
 230 fidelity (Gate 2), complexity bounds (Gate 3), nonlinear family constraints (Gate 4), and  
 231 adjoint consistency (Gate 5). When all pass,  $A_{\text{spec}} \equiv A_{\text{FPB}}$ .
- 232 (c)  $\delta_{\text{trans}} = 0$  when the natural-language-to-DAG translation produces a canonical chain that  
 233 exactly matches one of the 36 entries in the validated registry. *Condition*: Gate 2 (chain  
 234 fidelity) returns exact match. This holds for 31/36 (86%) of validated modalities.
- 235 (d)  $\delta_{\text{param}} \leq L_A \|\theta_{\text{agent}} - \theta_{\text{true}}\|$  by Assumption A3.  $L_A$  is computed per primitive by Gate 4’s  
 236 Lipschitz analysis: each nonlinear primitive has at most 2 free parameters with VC  
 237 dimension  $\leq 3$ , so  $L_i$  is computable in closed form.
- 238 (e)  $\delta_{\text{unmod}} = 0$  at Tier-3 by definition:  $A_{\text{tier}} \equiv A_{\text{true}}$  when operating at full-physics fidelity.  
 239 For lower tiers,  $\delta_{\text{unmod}}$  is estimated empirically via cross-tier comparison (Table 5) and is  
 240 reducible to machine precision via tier-lifting.

241 This completes the proof: each  $\varepsilon_i$  is bounded, measurable, and linked to a specific compiler gate  
 242 and corrective action.  $\square$

## 243 Tier-Lifting Protocol

244 **Proposition 3** (Tier-Lifting). *Let  $A_{low}$  be the low-tier and  $A_{high}$  the high-tier forward model (same*  
 245 *primitives, different fidelity). Define  $\Gamma(x) = A_{high}(x) - A_{low}(x)$ . Then  $\varepsilon_{unmod} \leq \|\Gamma(x) - \hat{\Gamma}(x)\| =$*   
 246  *$\varepsilon_{lift}$ , where  $\hat{\Gamma}$  is the correction used in reconstruction. In full-correction mode ( $\hat{\Gamma} = \Gamma$ ),  $\varepsilon_{lift} = 0$ .*

247 The Hybrid Proximal-Gradient (HPG) loop:

$$x_{k+1} = \text{prox}_{\lambda R}(x_k - \gamma A_{low}^T(A_{high}(x_k) - y))$$

248 uses the fast low-tier adjoint  $A_{low}^T$  for gradient computation and the high-tier forward  $A_{high}$   
 249 for data fidelity. Convergence follows from standard proximal-gradient theory under Lipschitz  
 250 continuity of  $\nabla f$ .

## 251 6-Gate Compiler

252 The compiler combines 3 gates from the FPB compiler [3] with 3 new agent-validation gates.

253 *Gates inherited from the FPB compiler [3]:*

254 **Gate 1 (DAG).** Compiled into a typed `OperatorGraphSpec` (Pydantic v2). Acyclicity verified  
 255 via Kahn’s algorithm,  $O(V+E)$ .

256 **Gate 2 (Chain).** Canonical chain extracted and compared against the 36-modality registry.  
 257 Match is exact or within known equivalences ( $\Sigma$  merged into  $D$ ).

258 **Gate 3 (Bounds).**  $N \leq 20$  nodes,  $D \leq 10$  depth.

259 *New agent-validation gates (this work):*

260 **Gate 4 (Nonlinear).** For each nonlinear node  $(D, R, \Lambda)$ : family resolved, parameter count  
 261  $\leq 2$ , values within physics bounds, Lipschitz constant  $L_i$  computed.

262 **Gate 5 (Adjoint).** Randomised dot-product test:  $|\langle Ax, y \rangle - \langle x, A^T y \rangle| / \max(|\langle Ax, y \rangle|, 10^{-8}) <$   
 263  $10^{-4}$ , 3 trials.

264 **Gate 6 (Error).** When reference available:  $\varepsilon = \mathbb{E}[\|(A_{\text{agent}} - A_{\text{true}})(x)\| / \|A_{\text{true}}(x)\|]$  over 5  
 265 random non-negative test vectors, threshold  $< 0.01$ .

## 266 4-Scenario Recovery Protocol

267 The recovery ratio  $\rho_{\text{recov}}$  quantifies how well the framework compensates for model mismatch.  
 268 Following [3], we define four scenarios validated on 6 representative modalities spanning 4 carrier  
 269 families (CASSI, CACTI, SPC: photon; CT: X-ray; electron ptychography: electron; MRI: spin):

$$\text{Sc. I (oracle): } y = A_{\text{true}}(x) + n; \hat{x}_{\text{I}} = \arg \min_x \|A_{\text{true}}(x) - y\|^2 + \lambda \text{reg}(x) \quad (5)$$

$$\text{Sc. II (mismatch): } y = A_{\text{true}}(x) + n; \hat{x}_{\text{II}} = \arg \min_x \|A_{\text{agent}}(x) - y\|^2 + \lambda \text{reg}(x) \quad (6)$$

$$\text{Sc. III (oracle correction): } \hat{x}_{\text{III}} = \text{refine}(\hat{x}_{\text{II}}) \text{ with data-consistency} \quad (7)$$

$$\text{Sc. IV (autonomous calibration): } \hat{x}_{\text{IV}} = \arg \min_x \|A_{\text{agent}}^{\text{cal}}(x) - y\|^2 + \lambda \text{reg}(x) \quad (8)$$

270 The recovery ratio  $\rho_{\text{recov}} = (\text{PSNR}_{\text{IV}} - \text{PSNR}_{\text{II}}) / (\text{PSNR}_{\text{I}} - \text{PSNR}_{\text{II}})$  measures autonomous  
 271 calibration effectiveness relative to the oracle correction.

For modalities with low-dimensional parameter mismatch (CT, electron ptychography, MRI): Sc. IV  $\approx$  Sc. III  $\approx$  Sc. I, confirming near-complete recovery ( $\rho_{\text{recov}} \approx 1.0$ ). For multi-parameter mismatch: CASSI 85%, CACTI 100%, SPC 86%. Across all 36 modalities: mean  $\rho_{\text{recov}} = 0.85 \pm 0.07$ .

## Expert Time Methodology

Expert setup times are defined as the interval from problem specification to first successful reconstruction, including literature review, code development, parameter tuning, and validation. For CT and MRI, times are cross-validated against published development reports [15, 16] and confirmed by domain experts. For the remaining modalities, times are estimated from published development timelines in the respective communities. We acknowledge this is not a prospective head-to-head comparison; such a study would strengthen the claims.

## Implementation

The framework is implemented in Python (Physics World Model platform). Specifications are structured markdown with 8 fields parsed into typed Pydantic v2 objects; the `system_elements` field has 4 sub-fields (source, optics, detector, calibration) and is auto-populated from the modality registry when not user-specified. The primitive library contains 101 implementations covering all 11 canonical types across all 4 fidelity tiers, each with a dedicated adapter: `Tier0Adapter` (geometric: invertibility, ray transforms), `Tier1Adapter` (Fourier: Parseval energy, Fresnel, OTF), `Tier2Adapter` (shift-variant: positivity, reciprocity, Mie, cost), and `Tier3Adapter` (full-physics: FDTD, MC, learned surrogates, uncertainty calibration). A `TierPolicy` selects the tier based on compute budget and modality requirements. Agents are LLM pipelines [38, 39] with tool access to the compiler and primitive library. Mean compilation time: 0.35 ms. The tier-lifting protocol is a generic `TierLiftingProtocol` class with validated cross-tier combinations for DOT and coherent imaging. Source code: [https://github.com/integritynoble/Physics\\_World\\_Model](https://github.com/integritynoble/Physics_World_Model).

## Extended Data

**Table 4. Extended Data Table 1: Four-tier fidelity hierarchy.** All 11 primitives are implemented at every tier.

| Tier              | Physics                    | Validation                    | Example         |
|-------------------|----------------------------|-------------------------------|-----------------|
| 0 (geometric)     | Ray optics, transforms     | Invertibility, adjoint        | LiDAR           |
| 1 (Fourier)       | Paraxial, angular spectrum | Parseval energy, adjoint      | SIM, holography |
| 2 (shift-variant) | Radon, k-space, Mie        | Positivity, reciprocity, cost | CT, MRI         |
| 3 (full-physics)  | FDTD, BPM, MC, NeRF        | Agreement, uncertainty        | DOT, NeRF       |

**Table 5. Extended Data Table 2: Tier-lifting validation.** Tier-lifting demonstrated on two cross-tier combinations; broader Tier-3 validation is future work.

| Domain   | Low tier            | High tier          | Correction           | $\epsilon_{\text{unmod}}$ | $\epsilon_{\text{lift}}$ |
|----------|---------------------|--------------------|----------------------|---------------------------|--------------------------|
| DOT      | Tier-2 ( $P_1$ )    | Tier-3 ( $P_3$ RT) | Higher-order moments | 7.8%                      | $< 10^{-12}$             |
| Coherent | Tier-1 (ang. spec.) | Tier-3 (FDTD)      | Evanescent + scatter | 147%                      | $< 10^{-12}$             |

**Table 6. Extended Data Table 3: Modality registry (36 validated canonical decompositions).**  
Status: FV = fully validated (canonical chain + quantitative reconstruction), QV = quantitatively validated (reconstruction without independent canonical chain), HO = held-out validation, T = template.  
An additional  $\sim 134$  modalities pass all compiler gates but lack per-modality reconstruction benchmarks; the full list is in the repository.

| Modality               | Domain   | Carrier  | Tier | Chain                                                             | Status | Real? | Dom. $\varepsilon$           |
|------------------------|----------|----------|------|-------------------------------------------------------------------|--------|-------|------------------------------|
| <i>X-ray</i>           |          |          |      |                                                                   |        |       |                              |
| CT                     | Medical  | X-ray    | 1–2  | $\Pi \rightarrow D$                                               | FV     | Yes   | $\varepsilon_{\text{param}}$ |
| CBCT                   | Medical  | X-ray    | 2    | $\Pi \rightarrow \Lambda \rightarrow D$                           | T      | No    | $\varepsilon_{\text{param}}$ |
| CT (polychromatic)     | Medical  | X-ray    | 2    | $\Pi \rightarrow \Lambda \rightarrow D$                           | T      | No    | $\varepsilon_{\text{unmod}}$ |
| Phase contrast         | Medical  | X-ray    | 1–2  | $\Pi \rightarrow P \rightarrow M \rightarrow D$                   | HO     | No    | $\varepsilon_{\text{param}}$ |
| PET                    | Nuclear  | X-ray    | 2    | $\Pi \rightarrow D$                                               | T      | No    | $\varepsilon_{\text{unmod}}$ |
| SPECT                  | Nuclear  | X-ray    | 2    | $\Pi \rightarrow S \rightarrow D$                                 | T      | No    | $\varepsilon_{\text{unmod}}$ |
| DEXA                   | Medical  | X-ray    | 2    | $M \rightarrow \Pi \rightarrow D$                                 | T      | No    | $\varepsilon_{\text{param}}$ |
| Compton                | Nuclear  | X-ray    | 2    | $M \rightarrow R \rightarrow D$                                   | HO     | No    | $\varepsilon_{\text{unmod}}$ |
| <i>Optical photons</i> |          |          |      |                                                                   |        |       |                              |
| CASSI                  | Spectral | Photon   | 2    | $M \rightarrow W \rightarrow \Sigma \rightarrow D$                | FV     | Yes   | $\varepsilon_{\text{param}}$ |
| CACTI                  | Video    | Photon   | 2    | $M \rightarrow \Sigma \rightarrow D$                              | FV     | Yes   | $\varepsilon_{\text{param}}$ |
| SPC                    | Imaging  | Photon   | 2    | $M \rightarrow \Sigma \rightarrow D$                              | FV     | No    | $\varepsilon_{\text{param}}$ |
| OCT                    | Ophthal. | Photon   | 1–2  | $P+P \rightarrow \Sigma \rightarrow D$                            | HO     | No    | $\varepsilon_{\text{param}}$ |
| SIM                    | Micro.   | Photon   | 1    | $M \rightarrow C \rightarrow D$                                   | HO     | No    | $\varepsilon_{\text{param}}$ |
| STED                   | Micro.   | Photon   | 1    | $M \rightarrow C \rightarrow D$                                   | T      | No    | $\varepsilon_{\text{param}}$ |
| PALM/STORM             | Micro.   | Photon   | 1    | $M \rightarrow C \rightarrow D$                                   | T      | No    | $\varepsilon_{\text{param}}$ |
| TIRF                   | Micro.   | Photon   | 1    | $P \rightarrow C \rightarrow D$                                   | T      | No    | $\varepsilon_{\text{param}}$ |
| Ptychography           | Micro.   | Photon   | 1–2  | $M \rightarrow P \rightarrow D$                                   | FV     | No    | $\varepsilon_{\text{param}}$ |
| Lensless               | Imaging  | Photon   | 1    | $C \rightarrow D$                                                 | FV     | No    | $\varepsilon_{\text{param}}$ |
| DOT                    | Diffuse  | Photon   | 2–3  | $M \rightarrow R \rightarrow P \rightarrow R \rightarrow D$       | HO     | No    | $\varepsilon_{\text{unmod}}$ |
| Ghost imaging          | Quantum  | Photon   | 2    | $M \rightarrow \Sigma \rightarrow D$                              | HO     | No    | $\varepsilon_{\text{param}}$ |
| THz-TDS                | Spectro. | Photon   | 1    | $C \rightarrow D$                                                 | HO     | No    | $\varepsilon_{\text{param}}$ |
| Light field            | 3D       | Photon   | 1    | $M \rightarrow C \rightarrow S \rightarrow D$                     | T      | No    | $\varepsilon_{\text{param}}$ |
| Raman                  | Spectro. | Photon   | 2    | $M \rightarrow R \rightarrow D$                                   | HO     | No    | $\varepsilon_{\text{unmod}}$ |
| Fluorescence           | Micro.   | Photon   | 2    | $M \rightarrow R \rightarrow D$                                   | HO     | No    | $\varepsilon_{\text{unmod}}$ |
| Fluorescence (sat.)    | Micro.   | Photon   | 2    | $M \rightarrow R \rightarrow \Lambda \rightarrow D$               | T      | No    | $\varepsilon_{\text{unmod}}$ |
| Brillouin              | Spectro. | Photon   | 2    | $M \rightarrow R \rightarrow D$                                   | HO     | No    | $\varepsilon_{\text{unmod}}$ |
| <i>Spin</i>            |          |          |      |                                                                   |        |       |                              |
| MRI                    | Medical  | Spin     | 1–2  | $M \rightarrow F \rightarrow S \rightarrow D$                     | FV     | Yes   | $\varepsilon_{\text{param}}$ |
| MRI (phase)            | Medical  | Spin     | 2    | $M \rightarrow F \rightarrow S \rightarrow \Lambda \rightarrow D$ | T      | No    | $\varepsilon_{\text{unmod}}$ |
| <i>Acoustic</i>        |          |          |      |                                                                   |        |       |                              |
| Ultrasound             | Medical  | Acoustic | 2    | $P \rightarrow D$                                                 | FV     | Yes   | $\varepsilon_{\text{param}}$ |
| Doppler US             | Medical  | Acoustic | 2    | $P \rightarrow D$                                                 | T      | No    | $\varepsilon_{\text{unmod}}$ |
| Elastography           | Medical  | Acoustic | 2    | $P \rightarrow P \rightarrow D$                                   | T      | No    | $\varepsilon_{\text{unmod}}$ |
| Photoacoustic          | Medical  | Acoustic | 2    | $M \rightarrow P \rightarrow D$                                   | HO     | No    | $\varepsilon_{\text{param}}$ |
| <i>Electron</i>        |          |          |      |                                                                   |        |       |                              |
| SEM                    | Material | Electron | 2    | $M \rightarrow D$                                                 | T      | No    | $\varepsilon_{\text{param}}$ |
| TEM                    | Material | Electron | 2    | $M \rightarrow C \rightarrow D$                                   | T      | No    | $\varepsilon_{\text{param}}$ |
| E-ptychography         | Material | Electron | 2    | $M \rightarrow P \rightarrow D$                                   | FV     | Yes   | $\varepsilon_{\text{param}}$ |
| <i>Particle</i>        |          |          |      |                                                                   |        |       |                              |
| Muon tomography        | Security | Particle | 2    | $R \rightarrow \Pi \rightarrow D$                                 | T      | No    | $\varepsilon_{\text{unmod}}$ |
| Proton therapy         | Medical  | Particle | 2    | $\Lambda \rightarrow \Pi \rightarrow D$                           | T      | No    | $\varepsilon_{\text{unmod}}$ |

**Table 7. Extended Data Table 4: Prospective algorithm-comparison study** (5 methods  $\times$  5 modalities). Each method independently implements the forward model and reconstruction from a one-sentence brief. The first 3 modalities use harder acquisition conditions (60-view fan-beam CT, 4-coil MRI); the last 2 are novel system designs with dedicated FISTA and PnP+TV algorithms. PSNR/SSIM are scale-invariant (both images normalized to  $[0, 1]$ ).

| Method      | Algorithm    | CT (60-view fan-beam) |        | MRI (4-coil 4 $\times$ ) |        |
|-------------|--------------|-----------------------|--------|--------------------------|--------|
|             |              | PSNR                  | Time   | PSNR                     | Time   |
| M1          | POCS/ADMM    | $19.6 \pm 2.9$        | 8.0 s  | $21.4 \pm 3.4$           | 54.5 s |
| M2          | FBP/Fourier  | $18.9 \pm 2.4$        | 5.5 s  | $21.0 \pm 3.4$           | 0.2 s  |
| M3          | FISTA+TV     | $19.1 \pm 3.2$        | 8.6 s  | $21.6 \pm 3.4$           | 69.9 s |
| M4          | CG/Iterative | $19.3 \pm 3.1$        | 9.4 s  | $19.1 \pm 2.0$           | 94.5 s |
| M5          | PnP+TV       | $17.8 \pm 3.8$        | 24.6 s | $22.2 \pm 3.3$           | 61.3 s |
| <b>Mean</b> |              | $18.9 \pm 0.7$        | 11.2 s | $21.1 \pm 1.2$           | 56.1 s |
| <b>CoV</b>  |              | 3.7%                  |        | 5.7%                     |        |


  

| Method      | Algorithm    | CASSI (28-band) |       | Lensless ( $C \rightarrow D$ ) |       |
|-------------|--------------|-----------------|-------|--------------------------------|-------|
|             |              | PSNR            | Time  | PSNR                           | Time  |
| M1          | POCS/ADMM    | $15.6 \pm 2.3$  | 70 s  | $7.6 \pm 3.6$                  | 0.4 s |
| M2          | FBP/Fourier  | $16.1 \pm 2.2$  | 14 s  | $8.1 \pm 3.6$                  | 0.1 s |
| M3          | FISTA+TV     | $15.4 \pm 2.3$  | 80 s  | $7.4 \pm 3.7$                  | 26 s  |
| M4          | CG/Iterative | $15.7 \pm 2.3$  | 136 s | $7.7 \pm 3.6$                  | 4.0 s |
| M5          | PnP+TV       | $15.3 \pm 2.4$  | 120 s | $8.0 \pm 3.6$                  | 40 s  |
| <b>Mean</b> |              | $15.6 \pm 0.3$  | 84 s  | $7.8 \pm 0.3$                  | 14 s  |
| <b>CoV</b>  |              | 1.9%            |       | 4.0%                           |       |

| Method      | Algorithm       | SIM ( $M \rightarrow C \rightarrow D$ ) |       |
|-------------|-----------------|-----------------------------------------|-------|
|             |                 | PSNR                                    | Time  |
| M1          | Wiener+TV       | $27.6 \pm 1.9$                          | 1.0 s |
| M2          | Wiener          | $27.6 \pm 1.9$                          | 0.1 s |
| M3          | FISTA+TV        | $26.2 \pm 2.5$                          | 18 s  |
| M4          | Richardson-Lucy | $27.5 \pm 1.9$                          | 3.8 s |
| M5          | PnP+TV          | $27.7 \pm 2.0$                          | 24 s  |
| <b>Mean</b> |                 | $27.3 \pm 0.6$                          | 9.4 s |
| <b>CoV</b>  |                 | 2.3%                                    |       |





**Figure 6. Extended Data Figure 1: Execute Agent calibration.** Predicted vs. actual PSNR for 36 validated modalities. Shaded band:  $\pm 1.8$  dB (overall MAE). Well-characterised modalities (green) cluster tightly around the identity line (MAE 0.9 dB); scattering-dominated modalities (red) show systematic under-prediction, reflecting unaccounted  $\varepsilon_{\text{unmod}}$  at lower tiers.

## Data Availability

The LoDoPaB-CT dataset is publicly available [4]. The M4Raw MRI and KAIST TSA CASSI datasets are publicly available from their respective repositories. The PICMUS ultrasound data is from the IEEE IUS challenge [7]. The SrTiO<sub>3</sub> 4D-STEM data is publicly available on Zenodo [8]. The CACTI real video data is from the project repository. The full modality registry, canonical decomposition registry, and validation datasets are in the open-source repository.

## Code Availability

All source code—Constrained Primitive Compiler, Agent-to-Graph Translator, three-agent pipeline, 101-primitive library, and 4-tier adapter framework—is available at [https://github.com/integritynoble/Physics\\_World\\_Model](https://github.com/integritynoble/Physics_World_Model) under the MIT licence.

## Acknowledgements

The author thanks the creators of the open datasets that made this work possible: the LoDoPaB-CT team (J. Leuschner et al.), the M4Raw consortium (M. Lyu et al.), the KAIST TSA group, the PICMUS challenge organisers (H. Liebgott et al.), and the 4D-STEM data providers (D. Jannis et al.). Computational resources were provided by NextGen PlatformAI.

## Author Contributions

C.Y. conceived the project, developed the theory (Theorem 2 and its proof), designed and implemented the three-agent pipeline, built the 101-primitive library across 4 fidelity tiers, conducted all experiments (6 real-data modalities, 36 validated modalities, 170-modality compilation, ablation study, and algorithm-comparison study), and wrote the manuscript.

## Competing Interests

C.Y. is affiliated with NextGen PlatformAI C Corp, which develops the Physics World Model platform described in this paper.

- [1] Baker, M. 1,500 scientists lift the lid on reproducibility. *Nature* **533**, 452–454 (2016).
- [2] Wilkinson, M. D. *et al.* The FAIR Guiding Principles for scientific data management and stewardship. *Scientific Data* **3**, 160018 (2016).
- [3] Yang, C. An agent framework for scientific simulation within a formal simulability class. *Preprint* (2026). Available at [https://github.com/integritynoble/Physics\\_World\\_Model](https://github.com/integritynoble/Physics_World_Model); key results (FPB basis theorem, canonical decompositions) are reproduced in Supplementary Information.
- [4] Leuschner, J., Schmidt, M., Baguer, D. O. & Maaß, P. LoDoPaB-CT, a benchmark dataset for low-dose computed tomography reconstruction. *Scientific Data* **8**, 109 (2021).
- [5] Lyu, M. *et al.* M4Raw: a multi-contrast, multi-repetition, multi-channel MRI k-space dataset for low-field MRI research. *Scientific Data* **10**, 264 (2023).
- [6] Meng, Z., Ma, J., & Yuan, X. End-to-end low cost compressive spectral imaging with spatial-spectral self-attention. *Proc. ECCV* (2020).
- [7] Liebgott, H. *et al.* Plane-wave imaging challenge in medical ultrasound. *Proc. IEEE Int. Ultrasonics Symp.* (2016).
- [8] Jannis, D., Hofer, C. & Verbeeck, J. SrTiO<sub>3</sub> [001] 4D-STEM dataset. Zenodo <https://doi.org/10.5281/zenodo.5113449> (2021).
- [9] Barbastathis, G., Ozcan, A. & Situ, G. On the use of deep learning for computational imaging. *Optica* **6**, 921–943 (2019).
- [10] Bertero, M., Boccacci, P. & De Mol, C. *Introduction to Inverse Problems in Imaging* 2nd edn (CRC Press, 2021).
- [11] Arridge, S. *et al.* Solving inverse problems using data-driven models. *Acta Numerica* **28**, 1–174 (2019).
- [12] Lustig, M., Donoho, D. & Pauly, J. M. Sparse MRI: the application of compressed sensing for rapid MR imaging. *Magn. Reson. Med.* **58**, 1182–1195 (2007).
- [13] Candès, E. J., Romberg, J. & Tao, T. Robust uncertainty principles: exact signal reconstruction from highly incomplete frequency information. *IEEE Trans. Inform. Theory* **52**, 489–509 (2006).
- [14] Rudin, L. I., Osher, S. & Fatemi, E. Nonlinear total variation based noise removal algorithms. *Physica D* **60**, 259–268 (1992).

- [15] van Aarle, W. *et al.* The ASTRA Toolbox: a platform for advanced algorithm development in electron tomography. *Ultramicroscopy* **157**, 35–47 (2016).
- [16] Ong, F. & Lustig, M. SigPy: a Python package for high performance iterative reconstruction. *Proc. ISMRM* (2019).
- [17] Adler, J. & Öktem, O. Operator Discretisation Library (ODL). Software available from <https://github.com/odlgroup/odl> (2017).
- [18] Tachella, J. *et al.* DeepInverse: a deep learning framework for inverse problems in imaging. *Preprint at* <https://arxiv.org/abs/2312.09828> (2023).
- [19] Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).
- [20] Merchant, A. *et al.* Scaling deep learning for materials discovery. *Nature* **624**, 80–85 (2023).
- [21] Karniadakis, G. E. *et al.* Physics-informed machine learning. *Nature Rev. Phys.* **3**, 422–440 (2021).
- [22] Wang, H. *et al.* Scientific discovery in the age of artificial intelligence. *Nature* **620**, 47–60 (2023).
- [23] Bommasani, R. *et al.* On the opportunities and risks of foundation models. *Preprint at* <https://arxiv.org/abs/2108.07258> (2022).
- [24] Ongie, G. *et al.* Deep learning techniques for inverse problems in imaging. *IEEE J. Sel. Top. Signal Process.* **14**, 171–182 (2020).
- [25] Monga, V., Li, Y. & Eldar, Y. C. Algorithm unrolling: Interpretable, efficient deep learning for signal and image processing. *IEEE Signal Process. Mag.* **38**, 18–44 (2021).
- [26] Kamilov, U. S. *et al.* Plug-and-play methods for integrating physical and learned models in computational imaging. *IEEE Signal Process. Mag.* **40**, 85–97 (2023).
- [27] Aggarwal, H. K., Mani, M. P. & Jacob, M. MoDL: model-based deep learning architecture for inverse problems. *IEEE Trans. Med. Imaging* **38**, 394–405 (2019).
- [28] Adler, J. & Öktem, O. Learned primal-dual reconstruction. *IEEE Trans. Med. Imaging* **37**, 1322–1332 (2018).
- [29] Tian, L., Hunt, B. & Bhatt, M. Computational imaging: machine learning for 3D, live, and multi-contrast microscopy. *Optica* **10**, 464–474 (2023).
- [30] Yuan, X., Brady, D. J. & Katsaggelos, A. K. Snapshot compressive imaging: theory, algorithms, and applications. *IEEE Signal Process. Mag.* **38**, 65–88 (2021).
- [31] Arridge, S. R. & Schotland, J. C. Optical tomography: forward and inverse problems. *Inverse Problems* **25**, 123010 (2009).
- [32] Jiang, Y. *et al.* Electron ptychography of 2D materials to deep sub-ångström resolution. *Nature* **559**, 343–349 (2018).
- [33] Rodenburg, J. M. & Maiden, A. M. Ptychography. In: *Springer Handbook of Microscopy* (Springer, 2019).
- [34] Gustafsson, M. G. L. *et al.* Three-dimensional resolution doubling in wide-field fluorescence microscopy by structured illumination. *Biophysical J.* **94**, 4957–4970 (2008).

- 389 [35] Chambolle, A. & Pock, T. An introduction to continuous optimization for imaging. *Acta*  
390 *Numerica* **25**, 161–319 (2016).
- 391 [36] Beck, A. & Teboulle, M. A fast iterative shrinkage-thresholding algorithm for linear inverse  
392 problems. *SIAM J. Imaging Sci.* **2**, 183–202 (2009).
- 393 [37] Boyd, S., Parikh, N., Chu, E., Peleato, B. & Eckstein, J. Distributed optimization and  
394 statistical learning via the alternating direction method of multipliers. *Found. Trends Mach.*  
395 *Learn.* **3**, 1–122 (2011).
- 396 [38] OpenAI. GPT-4 technical report. *Preprint* at <https://arxiv.org/abs/2303.08774> (2023).
- 397 [39] Schick, T. *et al.* Toolformer: language models can teach themselves to use tools. *Proc.*  
398 *NeurIPS* (2023).
- 399 [40] Boiko, D. A., MacKnight, R., Kline, B. & Gomes, G. Autonomous chemical research with  
400 large language models. *Nature* **624**, 570–578 (2023).
- 401 [41] Pearson, W. R. & Lipman, D. J. Improved tools for biological sequence comparison. *Proc.*  
402 *Natl Acad. Sci. USA* **85**, 2444–2448 (1988).
- 403 [42] Kodama, Y., Shumway, M. & Leinonen, R. The Sequence Read Archive: explosive growth  
404 of sequencing data. *Nucleic Acids Res.* **40**, D54–D56 (2012).