




Hands-on "modernization of an application using Intel Advisor"

Matrix Transposition

- This Hands-on is based on chapter 24 ("Profiling-Guided Optimization") - "High Performance Parallelism Pearls" book;
- This chapter exploits the use of Intel® VTune™ Amplifier XE reports to understand where to apply optimization on matrix transposition.



- Speedup Estimation Analysis
 - Create Advisor Project
 - Collect Survey Data
 - Include Annotations
 - Collect Suitability Data

- Speedup Estimation Analysis
 - Create Advisor Project
 - Collect Survey Data
 - Include Annotations
 - Collect Suitability Data

•


Intel Advisor

- Intel® Advisor XE is a shared memory threading designing and prototyping tool for C, C++, C# and Fortran.
- This tool provides a mechanism called annotation which is used to inform the regions of the code which can be parallelized. Based on such annotations a model is built in order to compare the performance scaling of different threading designs without the cost and disruption of implementation.
- In this part of Hands-on you will execute the following steps in order to perform threading prototyping:
- ✓ Create project;
- ✓ Survey data: Discover opportunities for parallelization;
- ✓ Annotate sources: include annotations on source code to check scalability;
- ✓ Check suitability: evaluate the performance of annotated loops in different architectures and frameworks.


- Speedup Estimation Analysis
 - Create Advisor Project
 - Collect Survey Data
 - Include Annotations
 - Collect Suitability Data

Intel Advisor – Create New Project


- Execute Intel Advisor on terminal: advixe-gui
- create new Advisor project:
 - name: TP
 - application: ~/hands-on/Pearl/1/runme-CPU
 - application parameters: 3000 100
 - Source Folder: ~/hands-on/Pearl/1/



Intel Advisor – Create New Project




Intel Advisor – Create New Project




Application Application

Intel Advisor – Source Search



- Speedup Estimation Analysis
 - Create Advisor Project
 - Collect Survey Data
 - Include Annotations
 - Collect Suitability Data

Intel Advisor - collect survey data



Intel Advisor - survey data results

A Higher instruction set architect		(ISA) available												ø :
Loops	å	Vector Issues	Self Time ▼	Total Time	Loop Type	Why No Vectorization?	Vectorized Loops				Instruction S	et Analysis	я г	<u></u>
							Vector ISA	Gain Estimate	VL (Vector Length)	Compiler Estimated Gain	Traits	Data Types	Advanced	Location
U [loop in Transpose at Transpose.cc:20]			40.470s	40.470s	Vectorized (B		SSE	3.43×	2; 4	3.43x		Float32; Float64	Unrolled by 4	Transpose.
☑ [loop in Transpose at Transpose.cc:20]			40.470s	40.470s	Vectorized (B		SSE		2; 4	3.43x		Float32; Float64	Unrolled by 4	Transpose.
☑ [loop in _kmp_launch_thread at kmp_runtime.c:5900]			24.499s	24.820s	Scalar									kmp_runtii
Use [loop in VerifyTransposed at Main.cc:24]		② 1 Data type conversions present	0.171s[0.171s(Vectorized (B		SSE2	2.73x	2; 4	2.73x	Type Conv	Float32; Float64; Int32	Unrolled by 4	Main.cc:24
☐ [loop in VerifyTransposed at Main.cc:24]		② 1 Data type conversions present	0.171s[0.171s(Vectorized (B		SSE2		2; 4	2.73x	Type Conv	Float32; Float64; Int32	Unrolled by 4	Main.cc:24
U [loop in Transpose at Transpose.cc:20]			0.080s	0.080s	Vectorized		SSE	1.86x	2; 4	1.86x		Float32; Float64		Transpos
☑ [loop in Transpose at Transpose.cc:20]			0.050s[0.050s (Vectorized (R		SSE		2; 4	1.86×		Float32; Float64		Transpose.
☑ [loop in Transpose at Transpose.cc:20]			0.030s[0.030s (Remainder									Transpose.
☑ 🖔 [loop in Transpose at Transpose.cc:17]			0.030s[40.500s	Scalar	inner loop was al								Transpose.
☑ 🖔 [loop in start_thread]			0.000s[24.820s	Scalar									
☑ 🖔 [loop inlibc_start_main]			0.000s [40.670s	Scalar									
☑ 🖔 [loop in main at Main.cc:74]			0.000s [40.600s	Scalar	🔳 loop with multipl						Float32; Float64		Main.cc:74
☑ 🖔 [loop in VerifyTransposed at Main.cc:23]			0.000s [0.171s(Scalar						Unpacks	Float32; Float64; Int32; Int64		Main.cc:23
			0.000s (24.820s	Scalar									z_Linux_uti

Top Down Loop Assembly			
Source	Total Time %	Loop Time %	Traits
You are free to use, modify and distribute this code as long as you acknowledge the above mentioned publication. (c) Colfax International, 2013 nclude "Transpose.h" nclude <cstdlib> id Transpose(FTYPE* const A, const int n) { for (int j = 0; j < n; j++) {</cstdlib>		40.499s	
for (int i = 0; i < j; i++) {	0.280s	40.550s	
const FTYPE $c = A[i^{x}n + i]$; $A[i^{x}n + i] = A[i^{x}n + i]$; $A[i^{x}n + i] = c$; }	29.950s 10.180s 0.190s (

Intel Advisor - survey data results

Loops	å	Vector Issues	a 15m			Why No Vectorization?	Vectorized L	.oops		≪	Instruction Set Analysis		<u>></u>	Location 🛚
			Self Time▼	Total Time	Loop Type		Vector ISA	Gain Estimate	VL (Vector Length)	Compiler Estimated Gain	Traits	Data Types	Advanced	Location
Uloop in Transpose at Transpose.cc:20]			40.470s	40.470s	Vectorized (B		SSE	3.43x	2; 4	3.43x		Float32; Float64	Unrolled by 4	Transpose.c
U [loop in Transpose at Transpose.cc:20]			40.470s	40.470s	Vectorized (B		SSE		2; 4	3.43x		Float32; Float64	Unrolled by 4	Transpose.c
☑ 🖔 [loop inkmp_launch_thread at kmp_runtime.c:5900]			24.499s	24.820s	Scalar									kmp_runtim
Uloop in VerifyTransposed at Main.cc:24		② 1 Data type conversions present	0.171s[0.171s[Vectorized (B		SSE2	2.73x	2; 4	2.73x	Type Conv	Float32; Float64; Int32	Unrolled by 4	Main.cc:24
☑ [loop in VerifyTransposed at Main.cc:24]			0.171s[0.171s[Vectorized (B		SSE2		2; 4	2.73x	Type Conv	Float32; Float64; Int32	Unrolled by 4	Main.cc:24
- <mark>⊍</mark> [loop in Transpose at Transpose.cc:20]		💡 1 Ineffective peeled/remainder loop	0.080s	0.080s (Vectorized		SSE	1.86x	2; 4	1.86x		Float32; Float64		Transpose
U [loop in Transpose at Transpose.cc:20]			0.050s[0.050s (Vectorized (R		SSE		2; 4	1.86x		Float32; Float64		Transpose.co
☑ (5 [loop in Transpose at Transpose.cc:20]			0.030s [0.030s (Remainder									Transpose.co
☑ 🖔 [loop in Transpose at Transpose.cc:17]			0.030s [40.500s	Scalar	inner loop was al								Transpose.co
☑ 🖔 [loop in start_thread]			0.000s[24.820s	Scalar									
☑ 🖔 [loop inlibc_start_main]			0.000s [40.670s	Scalar									
☑ 🖔 [loop in main at Main.cc:74]			0.000s [40.600s	Scalar	loop with multipl						Float32; Float64		Main.cc:74
☑ 🖔 [loop in VerifyTransposed at Main.cc:23]			0.000s [0.171s[Scalar						Unpacks	Float32; Float64; Int32; Int64		Main.cc:23
☑ 🖔 [loop in [OpenMP worker] at z_Linux_util.c:786]			0.000s[24.820s	Scalar									z_Linux_util.

												_
Source Top Down Loop Assembly & Recommendations	🛚 Compiler Diag	nostic Details										
Function Call Sites and Loops	Total Time %	Tatal Times	n -16 Ti	1 T	Mile No Version From	Vecto	riz 🔊	Instructi	on Set Analysis 🕞	Advanced	1	>>
		Total Time	Self Time	Loop Type	Why No Vectorization?	Vec	VL	Traits	Data Types		Location	
─Total	100.0%	65.490s	0s									
libc_start_main	62.1%	40.670s	0s									
☐ [loop in _libc_start_main]	62.1%	40.670s	0s	Scalar								
[Unknown stack frame(s)]	62.0%	40.600s	0s									
_ main	62.0%	40.600s	0s								Main.cc:38	
🖯 🖔 [loop in main at Main.cc:74]	62.0%	40.600s	0s	Scalar	loop with multiple exits cannot be vectorized unless it meets search loop idiom criteria				Float32; Float64		Main.cc:74	
─Transpose	62.0%	40.600s	0.0200s								Transpose.cc:15	
🖯 🖔 [loop in Transpose at Transpose.cc:17]	61.8%	40.500s	0.0300s	Scalar	inner loop was already vectorized						Transpose.cc:17	
🖳 🕖 [loop in Transpose at Transpose.cc:20]	61.8%	40.470s	0s								Transpose.cc:20	
[U] [loop in Transpose at Transpose.cc:20]	61.8%	40.470s	40.4696s	Vectorized (Body)		SSE	2; 4		Float32; Float64	Unrolled by 4	Transpose.cc:20	
☐ [loop in Transpose at Transpose.cc:20]	0.1% [0.080s (0s								Transpose.cc:20	
[U] [loop in Transpose at Transpose.cc:20]	0.1% [0.050s (0.0500s	Vectorized (Remainder)		SSE	2; 4		Float32; Float64		Transpose.cc:20	
 [loop in Transpose at Transpose.cc:20] 	0.0% [0.030s (0.0300s	Remainder							Transpose.cc:20	
⊞ main	0.1% [0.070s [0s								Main.cc:38	
<u>+clone</u>	37.9%	24.820s	0s									

Intel Advisor - survey data results

What lines are the hot spots in this code?

- Speedup Estimation Analysis
 - Create Advisor Project
 - Collect Survey Data
 - Include Annotations
 - Collect Suitability Data

Intel Advisor – Include Annotations

- Include the annotations on "~/handson/Pearl/1/transpose.cc" in the following way:
 - #include "advisor-annotate.h": include header file
 - ANNOTATE_SITE_BEGIN(id): before beginning of loop;
 - ANNOTATE_ITERATION_TASK(id): first line inside the loop;
 - ANNOTATE_SITE_END(): after end of loop;

Intel Advisor – Include Annotations

```
#include "Transpose.h"
#include <cstdlib>
void Transpose(FTYPE* const A, const int n) {
for (int j = 0; j < n; j++) {
 for (int i = 0; i < j; i++) {
   const FTYPE c = A[i*n + j];
   A[i*n + j] = A[j*n + i];
   A[i*n+i]=c;
```

```
#include "Transpose.h"
#include <cstdlib>
#include "advisor-annotate.h"
void Transpose(FTYPE* const A, const int n) {
 ANNOTATE_SITE_BEGIN( MySite1);
 for (int j = 0; j < n; j++) {
  ANNOTATE ITERATION TASK( MyTask1 );
  ANNOTATE_SITE_BEGIN( MySite2 );
  for (int i = 0; i < j; i++) {
   ANNOTATE_ITERATION_TASK( MyTask2 );
   const FTYPE c = A[i*n + i];
   A[i*n + j] = A[j*n + i];
   A[j*n+i]=c;
  ANNOTATE_SITE_END();
 ANNOTATE SITE END();
```

Intel Advisor – Include Annotations


 Red Lines shows the lines that has to be included in original source code;

- After include these lines recompile application:
 - Cd ~/hands-on/Pearl/1/
 - rm -rf runme-CPU
 - Make

Check your annotations on "view annotations" options;


- Speedup Estimation Analysis
 - Create Advisor Project
 - Collect Survey Data
 - Include Annotations
 - Collect Suitability Data

Intel Advisor - collect suitability data




Click here


Check Suitability Expected Results (Intel Xeon) Site 1



Check Suitability Expected Results (Intel Xeon) Site 2



Check Suitability Expected Results (Intel Xeon Phi) Site 1



Check Suitability Expected Results (Intel Xeon Phi) Site 2

