
Comparison of Machine Learning Methods to Predict Sleep Quality from Daytime Activity and Nightly Bedroom Environmental Conditions

WHOLE COMMUNITIES WHOLE HEALTH
AUT Grand Challenge

Hagen Fritz, Congyu Wu, Kerry Kinney, and Zoltan Nagy | The University of Texas at Austin

Objective: Assess relationship between IAQ/activity with sleep by predicting 7 sleep metrics.

Methods



Features

PM_{2.5} > 1000 Steps CO₂ > 30 Minutes TVOCs Activity CO T

Targets

Sleep Efficiency (SE) % Rapid-Eye-Movement (REM) Total Sleep Time (TST)

TST
Sleep Onset Latency (SOL)
Number of Awakenings (NAW)
Restfulness

Models

Logistic Regression

K-Nearest Neighbor k=7, Euclidean

Random Forest trees=10, depth=1

Results

	Model	Accuracy			Feature Importance		Feature Importance	
		Train	Test	Dummy	Test	Dummy	LR (coefficient)	RF (impurity)
SE	LR	0.79	0.78	0.79	0.89 (0.45)	0.89	RH-	Steps-
	kNN	0.82	0.74		0.89 (0.26)		T -	TVOC-
	RF	0.79	0.79		0.89 (0.71)		·	'
% REM	LR	0.64	0.63	0.64	0.54 (0.28)	0.53	Active -	Active -
	kNN	0.69	0.60		0.53 (0.09)		PM _{2.5} -	PM _{2.5} -
	RF	0.64	0.64		0.53 (0.34)			·
TST (Fitbit)	LR	0.65	0.64	0.65	0.52 (0.25)	0.52	Active-	Active -
	kNN	0.70	0.59		0.52 (0.17)		TVOC-	RH-
	RF	0.65	0.65		0.52 (0.32)		·	
SOL	LR	0.60	0.51	0.56	0.71 (0.33)	0.71	Т-	Active -
	kNN	0.67	0.54		0.72 (0.23)		Steps-	CO ₂ -
	RF	0.58	0.53		0.71 (0.5)		• • • • • • • • • • • • • • • • • • •	
NAW	LR	0.59	0.43	0.52	0.67 (0.36)	0.69	CO-	CO ₂ -
	kNN	0.69	0.47		0.69 (0.23)		T -	CO-
	RF	0.57	0.40		0.68 (0.48)			
Restful	LR	0.83	0.82	0.82	0.9 (0.53)	0.90	CO-	CO-
	kNN	0.83	0.79		0.9 (0.46)		RH-	RH-
	RF	0.82	0.82		0.9 (0.75)			
TST (Survey)	LR	0.69	0.61	0.64	0.78 (0.42)	0.78	Active -	Active -
	kNN	IN 0.70 0.61		0.78 (0.26)	.78 (0.26)	RH-	RH-	
	RF	0.64	0.64		0.78 (0.56)			

Conclusion: IAQ/activity are related to and can predict sleep quality better than a dummy model that assumes the majority outcome.