

Adaptive Law-Based Transformation *altx*

Wigner Summer Camp
Data and Compute Intensive Sciences Research Group

Balázs, Paszkál, Vince, Levente, Bence, Antal
Éva, Hajni

6-10 July 2026



Table of Contents


Dataset

The detailed calculation

The Parameters r, l, k

Dataset

Time series data



Time series is some function of time, for example:

$$x = [1, 2, 5, -1, 3]. \quad (1)$$

Dataset

Consider the following dataset:

- ▶ Train instance from class **a**: $a = [1, 1, 2, 3, 5]$.
- ▶ Train instance from class **b**: $b = [2, 1, 5, 7, 17]$.
- ▶ Test instance from an unknown class: $x = [2, 3, 5, 8, 13]$.

We now apply *altx* to classify the test instance, i.e., determine to which class x belongs.

The detailed calculation

Step 1: Extracting the Laws

We define parameters $r = 3$, $l = 2$, $k = 1$. (Their meaning will be discussed later.)

From $a = [1, 1, 2, 3, 5]$ we extract the following segments of length $r = 3$:

$$[1, 1, 2], [1, 2, 3], [2, 3, 5]. \quad (2)$$

Then we embed them to $l \times l = 2 \times 2$ matrices:

$$\begin{bmatrix} 1 & 1 \\ 1 & 2 \end{bmatrix}, \quad \begin{bmatrix} 1 & 2 \\ 2 & 3 \end{bmatrix}, \quad \begin{bmatrix} 2 & 3 \\ 3 & 5 \end{bmatrix}. \quad (3)$$

From those, the laws are the eigenvectors corresponding to the smallest absolute eigenvalues:

$$\begin{bmatrix} -0.8507 \\ 0.5257 \end{bmatrix}, \quad \begin{bmatrix} -0.8507 \\ 0.5257 \end{bmatrix}, \quad \begin{bmatrix} -0.8507 \\ 0.5257 \end{bmatrix}. \quad (4)$$

Step 1: Extracting the Laws (continued)

We combine the results into one matrix and repeat the process for all training instances (separately for each class).

From class **a**, we obtain laws:

$$L_a = \begin{bmatrix} -0.8507 & -0.8507 & -0.8507 \\ 0.5257 & 0.5257 & 0.5257 \end{bmatrix}. \quad (5)$$

From class **b**, we obtain laws:

$$L_b = \begin{bmatrix} -0.9571 & -0.8702 & -0.9085 \\ 0.2898 & 0.4927 & 0.4179 \end{bmatrix}. \quad (6)$$

Step 2: Embedding the Test Instance

The test instance $x = [2, 3, 5, 8, 13]$ is embedded as:

$$E = \begin{bmatrix} 2 & 3 \\ 3 & 5 \\ 5 & 8 \\ 8 & 13 \end{bmatrix}. \quad (7)$$

Step 3: Projection by Laws

Multiplying with class **a** laws:

$$F_a = EL_a = \begin{bmatrix} -0.1241 & -0.1241 & -0.1241 \\ 0.0767 & 0.0767 & 0.0767 \\ -0.0474 & -0.0474 & -0.0474 \\ 0.0293 & 0.0293 & 0.0293 \end{bmatrix}. \quad (8)$$

Multiplying with class **b** laws:

$$F_b = EL_b = \begin{bmatrix} -1.0448 & -0.2623 & -0.5635 \\ -1.4224 & -0.1471 & -0.6363 \\ -2.4672 & -0.4094 & -1.1997 \\ -3.8895 & -0.5565 & -1.8360 \end{bmatrix}. \quad (9)$$

Step 4: Feature Calculation

Using the mean of all squared values:

- ▶ Class **a**: $\text{mean} = 0.0061$.
- ▶ Class **b**: $\text{mean} = 3.5359$.

Conclusion: The test instance is closer to class **a**.

The Parameters r, l, k

Meaning of Parameters r, l, k

- ▶ r : Length of the original sequence window used for feature extraction.
- ▶ l : Embedding size, defines a symmetric $l \times l$ matrix.
- ▶ $2l - 1$: Number of equally spaced elements sampled from the window of length r .
- ▶ k : Step size (stride) used for shifting the window over the time series.

Example r, l, k values

Consider the following instance:

$$x' = [2, 1, 5, 7, 17, 31, 65, 127, 257, 511].$$

Let $r = 5, l = 2$, and $k = 1$. Then $2l - 1 = 3$ and

$$x'_1 = [\boxed{2}, 1, \boxed{5}, 7, \boxed{17}], 31, 65, 127, 257, 511].$$

$$x'_2 = [2, \boxed{1}, 5, \boxed{7}, 17, \boxed{31}], 65, 127, 257, 511].$$

$$x'_3 = [2, 1, \boxed{5}, 7, \boxed{17}, 31, \boxed{65}], 127, 257, 511].$$

$$x'_4 = [2, 1, 5, \boxed{7}, 17, \boxed{31}, 65, \boxed{127}], 257, 511].$$

$$x'_5 = [2, 1, 5, 7, \boxed{17}, 31, \boxed{65}, 127, \boxed{257}], 511].$$

$$x'_6 = [2, 1, 5, 7, 17, \boxed{31}, 65, \boxed{127}, 257, \boxed{511}].$$

Example r, l, k values

Consider the following instance:

$$x'' = [2, 1, 5, 7, 17, 31, 65, 127, 257, 511].$$

Let $r = 7, l = 2$, and $k = 2$. Then $2l - 1 = 3$ and

$$x_1'' = [\boxed{2}, 1, 5, \boxed{7}, 17, 31, \boxed{65}], 127, 257, 511].$$

$$x_2'' = [2, 1, \boxed{5}, 7, 17, \boxed{31}, 65, 127, \boxed{257}], 511].$$

Summary of ALT Method

- ▶ Extract subsequences and embed into symmetric matrices.
- ▶ Compute eigenvectors of smallest absolute eigenvalues — these are the laws.
- ▶ Multiply embedded test instances with class-specific laws.
- ▶ Compute summary statistics (e.g., mean of squared values).
- ▶ Classify by choosing the class that minimizes the statistic.