

IRSB Protocol: Bond Lifecycle

Economic Security Through Staked Collateral

IRSB Protocol Documentation

January 2026

Bond Lifecycle

Overview

The bond system is the economic backbone of the IRSB Protocol. It ensures solvers have skin in the game - collateral that can be slashed if they violate intent constraints. This creates strong incentives for honest behavior.

Key properties of the bond system:

- **Minimum Threshold:** 0.1 ETH required for solver activation
 - **Slashable Collateral:** Can be taken for violations
 - **Withdrawal Cooldown:** 7-day delay prevents slash-and-run
 - **Jail System:** Progressive penalties for repeat offenders
-

Solver States

State	Description	Can Post Receipts?	Can Withdraw?
Inactive	Registered, bond < 0.1 ETH	No	Yes
Active	Bonded >= 0.1 ETH	Yes	Yes (with cooldown)
Jailed	Temporarily suspended	No	No
Banned	Permanently blocked	No	Yes (remaining balance)

Phase 1: Registration

New solvers register and deposit initial bond:

```
// Register as a solver
function registerSolver(
    string calldata metadataURI,
    address operator
) external returns (bytes32 solverId);

// Deposit bond (can be called multiple times)
function depositBond(bytes32 solverId) external payable;
```




Figure 1: Bond Lifecycle Flowchart

Activation Logic:

```
// Auto-activate when minimum bond met
if (solver.status == Types.SolverStatus.Inactive &&
    solver.bondBalance >= MINIMUM_BOND) {
    solver.status = Types.SolverStatus.Active;
}
```

Phase 2: Active Operations

While active, solvers can post receipts and earn reputation:

```
// SolverRegistry tracks two balances
struct Solver {
    uint256 bondBalance;    // Available for use
    uint256 lockedBalance;  // Locked during disputes
}
```

Bond Locking During Disputes:

When a dispute is opened, the solver's bond is locked:

```
function lockBond(bytes32 solverId, uint256 amount) external onlyAuthorized {
    Types.Solver storage solver = _solvers[solverId];
    require(solver.bondBalance >= amount, "Insufficient bond");

    solver.bondBalance -= amount;
    solver.lockedBalance += amount;
}
```

Phase 3: Dispute Resolution

If Solver at Fault (Slashing)

```
function slash(
    bytes32 solverId,
    uint256 amount,
    bytes32 receiptId,
    Types.DisputeReason reason,
    address recipient
) external onlyAuthorized {
    // Slash from locked first, then available
    if (solver.lockedBalance >= amount) {
        solver.lockedBalance -= amount;
    } else {
        uint256 fromLocked = solver.lockedBalance;
        solver.lockedBalance = 0;
        solver.bondBalance -= (amount - fromLocked);
    }

    // Update reputation
    solver.score.disputesLost++;
    solver.score.totalSlashed += amount;
}
```

```

    // Transfer to recipient
    payable(recipient).call{value: amount}("");
}

```

If Solver Not at Fault

```

function unlockBond(bytes32 solverId, uint256 amount) external onlyAuthorized {
    solver.lockedBalance -= amount;
    solver.bondBalance += amount;
}

```

Phase 4: Withdrawal

Solvers can withdraw bonds with a 7-day cooldown:

```

// Step 1: Initiate withdrawal
function initiateWithdrawal(bytes32 solverId) external {
    require(solver.lockedBalance == 0, "Bond locked");
    _withdrawalRequest[solverId] = uint64(block.timestamp);
}

// Step 2: After 7 days, execute withdrawal
function withdrawBond(bytes32 solverId, uint256 amount) external {
    require(block.timestamp >= requestTime + WITHDRAWAL_COOLDOWN);

    solver.bondBalance -= amount;
    payable(solver.operator).call{value: amount}("");

    // Auto-deactivate if below minimum
    if (solver.bondBalance < MINIMUM_BOND) {
        solver.status = Types.SolverStatus.Inactive;
    }
}

```

Why the Cooldown?

The 7-day delay prevents “slash-and-run” attacks where a solver: 1. Commits fraud 2. Immediately withdraws their bond 3. Escapes before the dispute is resolved

Phase 5: Penalty States

Jailing (Temporary Suspension)

After losing a dispute, solvers may be jailed:

```

function jailSolver(bytes32 solverId) external onlyAuthorized {
    _jailCount[solverId]++;

    if (_jailCount[solverId] >= MAX_JAILS) {
        solver.status = Types.SolverStatus.Banned;
    } else {
        solver.status = Types.SolverStatus.Jailed;
    }
}

```

Recovery from jail requires owner intervention:

```
function unjailSolver(bytes32 solverId) external onlyOwner {
    require(solver.status == Types.SolverStatus.Jailed);

    solver.status = solver.bondBalance >= MINIMUM_BOND
        ? Types.SolverStatus.Active
        : Types.SolverStatus.Inactive;
}
```

Permanent Ban

After 3 jailings, the solver is permanently banned:

```
uint8 public constant MAX_JAILS = 3;
```

Key Constants

```
// Minimum bond for activation
uint256 public constant MINIMUM_BOND = 0.1 ether;

// Withdrawal cooldown period
uint64 public constant WITHDRAWAL_COOLDOWN = 7 days;

// Maximum jails before permanent ban
uint8 public constant MAX_JAILS = 3;

// Challenger bond (10% of solver bond)
uint16 constant CHALLENGER_BOND_BPS = 1000;
```

Bond Balance Tracking

The protocol maintains aggregate statistics:

```
// Global tracking
uint256 public totalSolvers;    // Number of registered solvers
uint256 public totalBonded;    // Total ETH locked in bonds

// Per-solver tracking
uint256 bondBalance;           // Available balance
uint256 lockedBalance;         // Locked during disputes
uint256 totalSlashed;          // Cumulative slashed amount
```

Example Scenario

Solver Lifecycle with Bond Events:

```
Day 1:    registerSolver() - Status: Inactive
Day 1:    depositBond(0.15 ETH) - Status: Active
          bondBalance = 0.15 ETH

Day 10:   Dispute opened against receipt
```

```
lockBond(0.1 ETH)
bondBalance = 0.05 ETH
lockedBalance = 0.1 ETH
```

Day 11: Dispute resolved: solver not at fault

```
unlockBond(0.1 ETH)
bondBalance = 0.15 ETH
lockedBalance = 0 ETH
```

Day 30: Another dispute: solver AT FAULT

```
slash(0.1 ETH, ...)
bondBalance = 0.05 ETH (below minimum!)
Status: Inactive
```

Day 31: depositBond(0.1 ETH)

```
bondBalance = 0.15 ETH
Status: Active
```

Review Questions

1. What is the minimum bond required for a solver to become active?
2. How long must a solver wait after initiating a withdrawal?
3. What happens to a solver's status if their bond falls below the minimum?
4. How many times can a solver be jailed before permanent ban?
5. What prevents a malicious solver from withdrawing their bond immediately after committing fraud?

IRSB Protocol - Economic security through staked collateral