


TES (Unless otherwise specified)							
PCB MATERIAL	FR4 or similar						
SOLDER	ENIG per IPC-4552						
WASHABLE	YES						
COPPER WEIGHT FOR OUTER LAYERS	1oz						
PCB PLATING	ENIG per IPC-4552						
VIA SIZE	See Drill Table						
VIA IN PAD	NO						
VIA FILL	NO						
VIA TENTING	BOTH SIDES						
SOLDER MASK COLOR	GRAY						
SILK SCREEN COLOR	WHITE						
ACCEPTANCE	IPC-A-600 Class II						
PCB FINISH	IPC-4552						
		Layer Stack Legend					
			Material 	Layer	Thickness Dielectric Mat		oer Dk
		7/74	Surface Materia	Top Overlay	0.010mm Solder Resist	Legend GTO Solder Mask GTS	
			Copper	Top Layer	0.036mm	Signal GTL	0.0
					1.500mm FR-4	Dielectric	4.
					1.500HIIII FR-4	DIGIGUIIU	4.
			Copper	Bottom Layer	0.036mm	Signal GBL	
					0.010mm Solder Resist		3.5
				Bottom Overlay		Legend GBO	
			Total thickness:	1.591mm			
			CON	ITENTS CONFID	ENTIAL AND PROPERTY	OF INTERCREATE ANI	D CLIE
				FABRICATION			J OLIL
			P/N	TABINIDATION	DIAMINO		
				e Breakout_14pin.		INTERCR	EAT
				neer jerry@intercr		2415 3rd St. #23	32
				out jerry@intercr	Time 1:57 PM Sheet 1 of 11	San Francisco, CA	94107
					ODE OFFICE AND Sheet 1 Of 11		

UNLESS OTHERWISE SPECIFIED, UNITS in 0.001 INCH (MIL)







CONTENTS CONFIDENTIAL AND PROPERTY OF INTERCREATE AND CLIENT

Title TOP LAYER SILKSCREEN

Title TOP LAYER SILKSCREEN											
P/N						LNITE					
Name Breakout_14pin.PcbDoc			Rev	Α		INIE	RCREA	4 I F			
Engineer jerry@intercreate.io											
_ayout jerry@intercreate.io				5	San Francis	co, CA 9410)7				
Date 11/16/2023 Time 1:57 PM		Sheet	4 of 1	1							

UNLESS OTHERWISE SPECIFIED, UNITS in 0.001 INCH (MIL)

