```
import { useState, useEffect, useRef } from "react";

const FONTS_LINK =
"https://fonts.googleapis.com/css2?family=Instrument+Serif:ital@0;1&family=JetBrains+Mono:w
ght@400;500;600&family=Sora:wght@300;400;500;600;700&display=swap";

function loadFonts() {
  if (!document.querySelector(`link[href*="Instrument+Serif"]`)) {
    const link = document.createElement("link");
    link.rel = "stylesheet";
    link.href = FONTS_LINK;
    document.head.appendChild(link);
  }
}

// Intersection Observer hook
function useInView(threshold = 0.15) {
  const ref = useRef(null);
  const [inView, setInView] = useState(false);
  useEffect(() => {
    const el = ref.current;
    if (!el) return;
    const obs = new IntersectionObserver(([e]) => { if (e.isIntersecting) setInView(true); }, {
threshold });
    obs.observe(el);
    return () => obs.disconnect();
  }, [threshold]);
  return [ref, inView];
}

// Typewriter effect
function Typewriter({ text, speed = 40, delay = 0 }) {
  const [displayed, setDisplayed] = useState("");
  const [started, setStarted] = useState(false);
  useEffect(() => {
    const t = setTimeout(() => setStarted(true), delay);
    return () => clearTimeout(t);
  }, [delay]);
  useEffect(() => {
    if (!started) return;
    let i = 0;
    const iv = setInterval(() => {
      i++;
```

```
      setDisplayed(text.slice(0, i));
      if (i >= text.length) clearInterval(iv);
    }, speed);
    return () => clearInterval(iv);
  }, [started, text, speed]);
  return <span>{displayed}<span style={{ opacity: displayed.length < text.length ? 1 : 0,
transition: "opacity 0.3s" }}>|</span></span>;
}

// Agent node component
function AgentNode({ name, role, color, delay, active }) {
  return (
    <div style={{
      background: "rgba(255,255,255,0.03)",
      border: `1px solid ${active ? color : "rgba(255,255,255,0.08)"}`,
      borderRadius: 12,
      padding: "20px 24px",
      minWidth: 180,
      opacity: active ? 1 : 0,
      transform: active ? "translateY(0)" : "translateY(20px)",
      transition: `all 0.6s cubic-bezier(0.16, 1, 0.3, 1) ${delay}ms`,
      position: "relative",
    }}>
      <div style={{
        width: 8, height: 8, borderRadius: "50%", background: color,
        position: "absolute", top: 12, right: 12,
        boxShadow: `0 0 12px ${color}80`,
      }} />
      <div style={{ fontFamily: "'JetBrains Mono'", fontSize: 13, color, marginBottom: 4,
letterSpacing: 0.5 }}>{role}</div>
      <div style={{ fontFamily: "'Sora'", fontSize: 16, fontWeight: 600, color: "#F0EDE8"
}}>{name}</div>
    </div>
  );
}

// Feature card
function FeatureCard({ icon, title, description, index, inView }) {
  return (
    <div style={{
      background: "rgba(255,255,255,0.02)",
      border: "1px solid rgba(255,255,255,0.06)",
      borderRadius: 16,
```

```
      padding: "36px 32px",
      opacity: inView ? 1 : 0,
      transform: inView ? "translateY(0)" : "translateY(30px)",
      transition: `all 0.7s cubic-bezier(0.16, 1, 0.3, 1) ${index * 120}ms`,
    }}>
      <div style={{ fontSize: 32, marginBottom: 16 }}>{icon}</div>
      <h3 style={{ fontFamily: "'Sora'", fontSize: 20, fontWeight: 600, color: "#F0EDE8",
marginBottom: 12, lineHeight: 1.3 }}>{title}</h3>
      <p style={{ fontFamily: "'Sora'", fontSize: 15, color: "rgba(240,237,232,0.55)", lineHeight: 1.7,
margin: 0 }}>{description}</p>
    </div>
  );
}

// Pricing card
function PricingCard({ tier, price, features, highlighted, index, inView }) {
  return (
    <div style={{
      background: highlighted ? "rgba(233,69,96,0.06)" : "rgba(255,255,255,0.02)",
      border: `1px solid ${highlighted ? "rgba(233,69,96,0.3)" : "rgba(255,255,255,0.06)"}`,
      borderRadius: 16,
      padding: "40px 32px",
      position: "relative",
      opacity: inView ? 1 : 0,
      transform: inView ? "translateY(0)" : "translateY(30px)",
      transition: `all 0.7s cubic-bezier(0.16, 1, 0.3, 1) ${index * 150}ms`,
      flex: "1 1 0",
      minWidth: 260,
    }}>
      {highlighted && <div style={{
        position: "absolute", top: -1, left: 40, right: 40, height: 2,
        background: "linear-gradient(90deg, transparent, #E94560, transparent)",
      }} />}
      <div style={{ fontFamily: "'JetBrains Mono'", fontSize: 12, color: highlighted ? "#E94560" :
"rgba(240,237,232,0.4)", letterSpacing: 2, textTransform: "uppercase", marginBottom: 12
}}>{tier}</div>
      <div style={{ fontFamily: "'Sora'", fontSize: 44, fontWeight: 700, color: "#F0EDE8",
marginBottom: 4 }}>{price}</div>
      <div style={{ fontFamily: "'Sora'", fontSize: 14, color: "rgba(240,237,232,0.35)",
marginBottom: 28 }}>per month</div>
      <div style={{ display: "flex", flexDirection: "column", gap: 14 }}>
        {features.map((f, i) => (
          <div key={i} style={{ display: "flex", gap: 10, alignItems: "flex-start" }}>
```

```
          <span style={{ color: highlighted ? "#E94560" : "rgba(240,237,232,0.3)", fontSize: 14,
marginTop: 2, flexShrink: 0 }}>→</span>
          <span style={{ fontFamily: "'Sora'", fontSize: 14, color: "rgba(240,237,232,0.6)",
lineHeight: 1.5 }}>{f}</span>
        </div>
      ))}
    </div>
    <button style={{
      marginTop: 32, width: "100%", padding: "14px 0",
      background: highlighted ? "#E94560" : "transparent",
      border: highlighted ? "none" : "1px solid rgba(255,255,255,0.15)",
      borderRadius: 8, fontFamily: "'Sora'", fontSize: 15, fontWeight: 500,
      color: "#F0EDE8", cursor: "pointer",
      transition: "all 0.3s ease",
    }}
      onMouseEnter={e => { e.target.style.transform = "translateY(-1px)";
e.target.style.boxShadow = highlighted ? "0 8px 30px rgba(233,69,96,0.3)" : "0 4px 20px
rgba(255,255,255,0.05)"; }}
      onMouseLeave={e => { e.target.style.transform = ""; e.target.style.boxShadow = ""; }}
    >
      Get Started
    </button>
  </div>
  );
}

// Step component for How It Works
function Step({ number, title, desc, index, inView }) {
  return (
    <div style={{
      display: "flex", gap: 24, alignItems: "flex-start",
      opacity: inView ? 1 : 0,
      transform: inView ? "translateX(0)" : "translateX(-30px)",
      transition: `all 0.7s cubic-bezier(0.16, 1, 0.3, 1) ${index * 200}ms`,
    }}>
      <div style={{
        fontFamily: "'Instrument Serif'", fontSize: 56, fontStyle: "italic",
        color: "rgba(233,69,96,0.25)", lineHeight: 1, flexShrink: 0, width: 60, textAlign: "center",
      }}>{number}</div>
      <div>
        <h4 style={{ fontFamily: "'Sora'", fontSize: 18, fontWeight: 600, color: "#F0EDE8",
marginBottom: 8, marginTop: 8 }}>{title}</h4>
        <p style={{ fontFamily: "'Sora'", fontSize: 15, color: "rgba(240,237,232,0.5)", lineHeight: 1.7,
```

```
margin: 0 }}>{desc}</p>
      </div>
    </div>
  );
}

export default function AriaLanding() {
  useEffect(() => { loadFonts(); }, []);
  const [loaded, setLoaded] = useState(false);
  const [agentsVisible, setAgentsVisible] = useState(false);
  useEffect(() => { setTimeout(() => setLoaded(true), 100); }, []);

  const [agentRef, agentInView] = useInView(0.2);
  const [featRef, featInView] = useInView(0.1);
  const [howRef, howInView] = useInView(0.1);
  const [priceRef, priceInView] = useInView(0.1);
  const [ctaRef, ctaInView] = useInView(0.2);

  useEffect(() => { if (agentInView) setTimeout(() => setAgentsVisible(true), 200); },
[agentInView]);

  const features = [
    { icon: "🧭", title: "GTM Strategy Builder", description: "ARIA interviews you about your
product, audience, and goals — then generates a complete go-to-market playbook. Not generic
advice. A specific, actionable plan." },
    { icon: "✍️", title: "Content That Knows You", description: "Blog posts, landing pages, Product
Hunt copy, Show HN posts — all grounded in your product context and brand voice. No more
re-explaining your product to ChatGPT." },
    { icon: "📧", title: "Email Sequences", description: "Welcome series, launch campaigns,
newsletters. Complete with subject lines, send timing, and A/B variants. Copy into ConvertKit or
Mailchimp and send." },
    { icon: "📱", title: "Social Media Calendar", description: "Platform-optimized posts for X,
LinkedIn, and Facebook. Adapted from your content, scheduled on a calendar, ready to copy
and post." },
    { icon: "🎯", title: "Facebook Ads Playbook", description: "Complete campaign plans with
targeting specs, ad copy variants, budget recommendations, and step-by-step Ads Manager
instructions. Built for people who've never run an ad." },
    { icon: "📊", title: "Strategy That Adapts", description: "Report your results back to ARIA. It
adjusts the playbook, suggests new angles, and tells you what to double down on. Your strategy
gets smarter over time." },
  ];

  return (
```

```
    <div style={{
      minHeight: "100vh",
      background: "#0A0A0F",
      color: "#F0EDE8",
      overflowX: "hidden",
    }}>
      {/* Noise overlay */}
      <div style={{
        position: "fixed", inset: 0, pointerEvents: "none", zIndex: 1,
        opacity: 0.03,
        backgroundImage: `url("data:image/svg+xml,%3Csvg viewBox='0 0 256 256'
xmlns='http://www.w3.org/2000/svg'%3E%3Cfilter id='n'%3E%3CfeTurbulence
type='fractalNoise' baseFrequency='0.9' numOctaves='4'
stitchTiles='stitch'/%3E%3C/filter%3E%3Crect width='100%25' height='100%25'
filter='url(%23n)'/%3E%3C/svg%3E")`,
      }} />

      {/* Gradient orbs */}
      <div style={{
        position: "fixed", top: -200, right: -200, width: 600, height: 600,
        background: "radial-gradient(circle, rgba(233,69,96,0.08) 0%, transparent 70%)",
        pointerEvents: "none", zIndex: 0,
      }} />
      <div style={{
        position: "fixed", bottom: -300, left: -200, width: 800, height: 800,
        background: "radial-gradient(circle, rgba(15,52,96,0.15) 0%, transparent 70%)",
        pointerEvents: "none", zIndex: 0,
      }} />

      <div style={{ position: "relative", zIndex: 2 }}>
        {/* Nav */}
        <nav style={{
          display: "flex", justifyContent: "space-between", alignItems: "center",
          padding: "24px 48px", maxWidth: 1200, margin: "0 auto",
          opacity: loaded ? 1 : 0, transform: loaded ? "translateY(0)" : "translateY(-10px)",
          transition: "all 0.8s cubic-bezier(0.16, 1, 0.3, 1)",
        }}>
          <div style={{ display: "flex", alignItems: "center", gap: 10 }}>
            <div style={{
              width: 32, height: 32, borderRadius: 8,
              background: "linear-gradient(135deg, #E94560, #c23152)",
              display: "flex", alignItems: "center", justifyContent: "center",
              fontFamily: "'Sora'", fontWeight: 700, fontSize: 16, color: "#fff",
```

```
          }}>A</div>
          <span style={{ fontFamily: "'Sora'", fontWeight: 600, fontSize: 18, letterSpacing: 2
}}>ARIA</span>
        </div>
        <div style={{ display: "flex", gap: 36, alignItems: "center" }}>
          <a href="#features" style={{ fontFamily: "'Sora'", fontSize: 14, color:
"rgba(240,237,232,0.5)", textDecoration: "none", transition: "color 0.2s" }}
            onMouseEnter={e => e.target.style.color = "#F0EDE8"} onMouseLeave={e =>
e.target.style.color = "rgba(240,237,232,0.5)"}>Features</a>
          <a href="#how" style={{ fontFamily: "'Sora'", fontSize: 14, color: "rgba(240,237,232,0.5)",
textDecoration: "none", transition: "color 0.2s" }}
            onMouseEnter={e => e.target.style.color = "#F0EDE8"} onMouseLeave={e =>
e.target.style.color = "rgba(240,237,232,0.5)"}>How It Works</a>
          <a href="#pricing" style={{ fontFamily: "'Sora'", fontSize: 14, color:
"rgba(240,237,232,0.5)", textDecoration: "none", transition: "color 0.2s" }}
            onMouseEnter={e => e.target.style.color = "#F0EDE8"} onMouseLeave={e =>
e.target.style.color = "rgba(240,237,232,0.5)"}>Pricing</a>
          <button style={{
            fontFamily: "'Sora'", fontSize: 14, fontWeight: 500,
            background: "#E94560", border: "none", borderRadius: 8,
            color: "#fff", padding: "10px 24px", cursor: "pointer",
            transition: "all 0.3s ease",
          }}
            onMouseEnter={e => { e.target.style.boxShadow = "0 6px 24px rgba(233,69,96,0.4)";
e.target.style.transform = "translateY(-1px)"; }}
            onMouseLeave={e => { e.target.style.boxShadow = ""; e.target.style.transform = ""; }}
          >Join Waitlist</button>
        </div>
      </nav>

      {/* Hero */}
      <section style={{ maxWidth: 1200, margin: "0 auto", padding: "100px 48px 80px", textAlign:
"center" }}>
        <div style={{
          fontFamily: "'JetBrains Mono'", fontSize: 13, letterSpacing: 3,
          color: "#E94560", marginBottom: 32, textTransform: "uppercase",
          opacity: loaded ? 1 : 0, transition: "opacity 0.8s 0.2s",
        }}>
          YOUR AI MARKETING TEAM
        </div>
        <h1 style={{
          fontFamily: "'Instrument Serif'", fontSize: "clamp(48px, 7vw, 84px)",
          fontWeight: 400, lineHeight: 1.08, margin: "0 auto 32px", maxWidth: 900,
```

```
          opacity: loaded ? 1 : 0, transform: loaded ? "translateY(0)" : "translateY(20px)",
          transition: "all 1s cubic-bezier(0.16, 1, 0.3, 1) 0.3s",
        }}>
          You build the product.<br />
          <span style={{ fontStyle: "italic", color: "#E94560" }}>ARIA markets it.</span>
        </h1>
        <p style={{
          fontFamily: "'Sora'", fontSize: 18, color: "rgba(240,237,232,0.5)",
          lineHeight: 1.7, maxWidth: 600, margin: "0 auto 48px", fontWeight: 300,
          opacity: loaded ? 1 : 0, transition: "opacity 1s 0.6s",
        }}>
          ARIA gives developer founders an AI marketing team that builds your GTM strategy and
executes it — content, email, social, and ads — so you can stop guessing and start growing.
        </p>
        <div style={{
          display: "flex", gap: 16, justifyContent: "center", flexWrap: "wrap",
          opacity: loaded ? 1 : 0, transition: "opacity 1s 0.8s",
        }}>
          <button style={{
            fontFamily: "'Sora'", fontSize: 16, fontWeight: 500,
            background: "#E94560", border: "none", borderRadius: 10,
            color: "#fff", padding: "16px 40px", cursor: "pointer",
            transition: "all 0.3s ease",
          }}
            onMouseEnter={e => { e.target.style.boxShadow = "0 8px 32px rgba(233,69,96,0.4)";
e.target.style.transform = "translateY(-2px)"; }}
            onMouseLeave={e => { e.target.style.boxShadow = ""; e.target.style.transform = ""; }}
          >Join the Waitlist</button>
          <button style={{
            fontFamily: "'Sora'", fontSize: 16, fontWeight: 500,
            background: "transparent", border: "1px solid rgba(255,255,255,0.15)", borderRadius:
10,
            color: "#F0EDE8", padding: "16px 40px", cursor: "pointer",
            transition: "all 0.3s ease",
          }}
            onMouseEnter={e => { e.target.style.borderColor = "rgba(255,255,255,0.3)";
e.target.style.transform = "translateY(-2px)"; }}
            onMouseLeave={e => { e.target.style.borderColor = "rgba(255,255,255,0.15)";
e.target.style.transform = ""; }}
          >Watch Demo</button>
        </div>

        {/* Terminal preview */}
```

```
        <div style={{
          maxWidth: 700, margin: "80px auto 0",
          background: "rgba(255,255,255,0.02)",
          border: "1px solid rgba(255,255,255,0.06)",
          borderRadius: 16, overflow: "hidden",
          opacity: loaded ? 1 : 0, transform: loaded ? "translateY(0)" : "translateY(30px)",
          transition: "all 1s cubic-bezier(0.16, 1, 0.3, 1) 1s",
        }}>
          <div style={{
            display: "flex", gap: 8, padding: "16px 20px",
            borderBottom: "1px solid rgba(255,255,255,0.06)",
          }}>
            <div style={{ width: 12, height: 12, borderRadius: "50%", background:
"rgba(255,255,255,0.08)" }} />
            <div style={{ width: 12, height: 12, borderRadius: "50%", background:
"rgba(255,255,255,0.08)" }} />
            <div style={{ width: 12, height: 12, borderRadius: "50%", background:
"rgba(255,255,255,0.08)" }} />
            <span style={{ fontFamily: "'JetBrains Mono'", fontSize: 12, color:
"rgba(240,237,232,0.25)", marginLeft: 12 }}>aria — marketing session</span>
          </div>
          <div style={{ padding: "24px 28px", fontFamily: "'JetBrains Mono'", fontSize: 14,
lineHeight: 2 }}>
            <div style={{ color: "#E94560" }}>ARIA_CEO →</div>
            <div style={{ color: "rgba(240,237,232,0.7)", paddingLeft: 16 }}>
              <Typewriter text="I've analyzed your product and audience. Here's your 30-day GTM
plan: Week 1 — launch blog + Product Hunt prep. Week 2 — email sequence to beta users.
Week 3 — LinkedIn thought leadership push. Week 4 — Facebook ads targeting early adopters.
I'll draft everything. Ready?" speed={25} delay={1500} />
            </div>
          </div>
        </div>
      </section>

      {/* Social proof bar */}
      <section style={{
        borderTop: "1px solid rgba(255,255,255,0.04)",
        borderBottom: "1px solid rgba(255,255,255,0.04)",
        padding: "32px 48px", textAlign: "center",
      }}>
        <p style={{
          fontFamily: "'JetBrains Mono'", fontSize: 13, color: "rgba(240,237,232,0.25)",
          letterSpacing: 2, margin: 0,
```

```
        }}>
          BUILT FOR FOUNDERS WHO'D RATHER SHIP CODE THAN WRITE AD COPY
        </p>
      </section>

      {/* Agent hierarchy section */}
      <section ref={agentRef} style={{ maxWidth: 1200, margin: "0 auto", padding: "120px 48px"
}}>
        <div style={{ textAlign: "center", marginBottom: 64 }}>
          <div style={{
            fontFamily: "'JetBrains Mono'", fontSize: 12, letterSpacing: 3,
            color: "rgba(240,237,232,0.3)", textTransform: "uppercase", marginBottom: 16,
          }}>YOUR MARKETING ORG</div>
          <h2 style={{
            fontFamily: "'Instrument Serif'", fontSize: "clamp(36px, 4vw, 52px)",
            fontWeight: 400, lineHeight: 1.15, margin: 0,
          }}>
            Five agents. <span style={{ fontStyle: "italic", color: "#E94560" }}>One team.</span>
          </h2>
        </div>

        {/* Org chart */}
        <div style={{ display: "flex", flexDirection: "column", alignItems: "center", gap: 24 }}>
          <AgentNode name="ARIA CEO" role="STRATEGIST" color="#E94560" delay={0}
active={agentsVisible} />
          <div style={{
            width: 1, height: 32, background: "rgba(255,255,255,0.08)",
            opacity: agentsVisible ? 1 : 0, transition: "opacity 0.5s 0.3s",
          }} />
          <div style={{
            display: "flex", gap: 16, flexWrap: "wrap", justifyContent: "center",
          }}>
            <AgentNode name="ContentWriter" role="CONTENT" color="#4ECDC4" delay={400}
active={agentsVisible} />
            <AgentNode name="EmailMarketer" role="EMAIL" color="#FFE66D" delay={550}
active={agentsVisible} />
            <AgentNode name="SocialManager" role="SOCIAL" color="#A78BFA" delay={700}
active={agentsVisible} />
            <AgentNode name="AdStrategist" role="ADS" color="#FF8A5C" delay={850}
active={agentsVisible} />
          </div>
        </div>
      </section>
```

```
      {/* Features */}
      <section id="features" ref={featRef} style={{ maxWidth: 1200, margin: "0 auto", padding:
"40px 48px 120px" }}>
        <div style={{ textAlign: "center", marginBottom: 64 }}>
          <div style={{
            fontFamily: "'JetBrains Mono'", fontSize: 12, letterSpacing: 3,
            color: "rgba(240,237,232,0.3)", textTransform: "uppercase", marginBottom: 16,
          }}>FEATURES</div>
          <h2 style={{
            fontFamily: "'Instrument Serif'", fontSize: "clamp(36px, 4vw, 52px)",
            fontWeight: 400, lineHeight: 1.15, margin: 0,
          }}>
            Strategy <span style={{ fontStyle: "italic" }}>and</span> execution.<br />Not one or the
other.
          </h2>
        </div>
        <div style={{
          display: "grid", gridTemplateColumns: "repeat(auto-fit, minmax(320px, 1fr))",
          gap: 20,
        }}>
          {features.map((f, i) => (
            <FeatureCard key={i} icon={f.icon} title={f.title} description={f.description} index={i}
inView={featInView} />
          ))}
        </div>
      </section>

      {/* How it works */}
      <section id="how" ref={howRef} style={{
        maxWidth: 1200, margin: "0 auto", padding: "120px 48px",
        borderTop: "1px solid rgba(255,255,255,0.04)",
      }}>
        <div style={{ display: "flex", gap: 80, flexWrap: "wrap" }}>
          <div style={{ flex: "1 1 300px" }}>
            <div style={{
              fontFamily: "'JetBrains Mono'", fontSize: 12, letterSpacing: 3,
              color: "rgba(240,237,232,0.3)", textTransform: "uppercase", marginBottom: 16,
            }}>HOW IT WORKS</div>
            <h2 style={{
              fontFamily: "'Instrument Serif'", fontSize: "clamp(36px, 4vw, 48px)",
              fontWeight: 400, lineHeight: 1.15, margin: "0 0 24px",
            }}>
```

```
            From zero to<br /><span style={{ fontStyle: "italic", color: "#E94560" }}>full marketing
pipeline</span>
          </h2>
          <p style={{
            fontFamily: "'Sora'", fontSize: 16, color: "rgba(240,237,232,0.4)",
            lineHeight: 1.7, maxWidth: 400,
          }}>
            Tell ARIA about your product once. Get a strategy and ready-to-use marketing assets
— blog posts, emails, social posts, ad campaigns — on an ongoing basis.
          </p>
        </div>
        <div style={{ flex: "1 1 400px", display: "flex", flexDirection: "column", gap: 40 }}>
          <Step number="1" title="Tell ARIA about your product" desc="A 10-minute
conversation. Your product, your audience, your goals, your budget. ARIA builds a complete
GTM playbook from this." index={0} inView={howInView} />
          <Step number="2" title="Review your GTM strategy" desc="A 30/60/90-day plan with
specific channels, content themes, and campaign ideas. Tailored to your product and audience
— not generic advice." index={1} inView={howInView} />
          <Step number="3" title="Your agents go to work" desc="Content, emails, social posts,
and ad campaigns materialize on your calendar. Each piece ties back to your strategy and
builds on the last." index={2} inView={howInView} />
          <Step number="4" title="Copy, paste, grow" desc="Everything is ready to use. Paste
blog posts into your CMS, emails into your ESP, ad copy into Meta Ads Manager. Follow the
step-by-step instructions." index={3} inView={howInView} />
        </div>
      </div>
    </section>

    {/* Facebook Ads callout */}
    <section style={{
      maxWidth: 1200, margin: "0 auto", padding: "80px 48px",
    }}>
      <div style={{
        background: "rgba(233,69,96,0.04)",
        border: "1px solid rgba(233,69,96,0.12)",
        borderRadius: 20, padding: "60px 48px",
        display: "flex", gap: 48, flexWrap: "wrap", alignItems: "center",
      }}>
        <div style={{ flex: "1 1 400px" }}>
          <div style={{
            fontFamily: "'JetBrains Mono'", fontSize: 12, letterSpacing: 3,
            color: "#E94560", textTransform: "uppercase", marginBottom: 16,
          }}>FACEBOOK ADS — ZERO EXPERIENCE REQUIRED</div>
```

```
            <h3 style={{
              fontFamily: "'Instrument Serif'", fontSize: 36, fontWeight: 400,
              lineHeight: 1.2, margin: "0 0 20px",
            }}>
              ARIA writes your ads <span style={{ fontStyle: "italic" }}>and</span> teaches you<br
/>how to run them.
            </h3>
            <p style={{
              fontFamily: "'Sora'", fontSize: 15, color: "rgba(240,237,232,0.5)",
              lineHeight: 1.7,
            }}>
              Never opened Meta Ads Manager? No problem. ARIA's Ad Strategist produces
complete campaign plans with ad copy, targeting parameters, budget recommendations, and
numbered step-by-step instructions for every click in the interface.
            </p>
          </div>
          <div style={{
            flex: "1 1 300px",
            background: "rgba(0,0,0,0.3)",
            borderRadius: 12, padding: "24px",
            fontFamily: "'JetBrains Mono'", fontSize: 13,
            lineHeight: 1.8, color: "rgba(240,237,232,0.6)",
            border: "1px solid rgba(255,255,255,0.06)",
          }}>
            <div style={{ color: "#FF8A5C", marginBottom: 8 }}>AdStrategist →</div>
            <div style={{ color: "rgba(240,237,232,0.45)" }}>
              Campaign: "DevTool Signups"<br />
              Objective: Conversions<br />
              Daily budget: $25<br />
              Audience: Software devs, 25-44<br />
              <br />
              <span style={{ color: "#E94560" }}>Ad Copy (Variant A):</span><br />
              "Still deploying on Fridays<br />
              and praying? There's a better<br />
              way. Try [Product] free →"<br />
              <br />
              <span style={{ color: "rgba(240,237,232,0.3)" }}>+ 3 more variants...</span>
            </div>
          </div>
        </div>
      </section>

      {/* Pricing */}
```

```
      <section id="pricing" ref={priceRef} style={{
        maxWidth: 1200, margin: "0 auto", padding: "120px 48px",
        borderTop: "1px solid rgba(255,255,255,0.04)",
      }}>
        <div style={{ textAlign: "center", marginBottom: 64 }}>
          <div style={{
            fontFamily: "'JetBrains Mono'", fontSize: 12, letterSpacing: 3,
            color: "rgba(240,237,232,0.3)", textTransform: "uppercase", marginBottom: 16,
          }}>PRICING</div>
          <h2 style={{
            fontFamily: "'Instrument Serif'", fontSize: "clamp(36px, 4vw, 52px)",
            fontWeight: 400, lineHeight: 1.15, margin: "0 0 16px",
          }}>
            Less than a freelancer.<br /><span style={{ fontStyle: "italic", color: "#E94560"
}}>Better than an agency.</span>
          </h2>
        </div>
        <div style={{ display: "flex", gap: 20, flexWrap: "wrap" }}>
          <PricingCard
            tier="Starter" price="$49" highlighted={false} index={0} inView={priceInView}
            features={[
              "GTM playbook generation",
              "10 content pieces / month",
              "Content calendar",
              "1 campaign plan / month",
            ]}
          />
          <PricingCard
            tier="Growth" price="$149" highlighted={true} index={1} inView={priceInView}
            features={[
              "Everything in Starter",
              "30 content pieces / month",
              "Email sequences",
              "Social media calendar",
              "3 campaign plans / month",
              "Performance optimization",
            ]}
          />
          <PricingCard
            tier="Scale" price="$299" highlighted={false} index={2} inView={priceInView}
            features={[
              "Everything in Growth",
              "Unlimited content",
```

```
            "Priority generation",
            "Custom agent configs",
            "Dedicated support",
          ]}
        />
      </div>
    </section>

    {/* Final CTA */}
    <section ref={ctaRef} style={{
      maxWidth: 1200, margin: "0 auto", padding: "120px 48px 160px", textAlign: "center",
    }}>
      <h2 style={{
        fontFamily: "'Instrument Serif'", fontSize: "clamp(40px, 5vw, 64px)",
        fontWeight: 400, lineHeight: 1.15, margin: "0 0 24px",
        opacity: ctaInView ? 1 : 0, transform: ctaInView ? "translateY(0)" : "translateY(20px)",
        transition: "all 0.8s cubic-bezier(0.16, 1, 0.3, 1)",
      }}>
        Stop Googling<br />"<span style={{ fontStyle: "italic", color: "#E94560" }}>how to market
my startup</span>"
      </h2>
      <p style={{
        fontFamily: "'Sora'", fontSize: 18, color: "rgba(240,237,232,0.45)",
        lineHeight: 1.7, maxWidth: 500, margin: "0 auto 40px", fontWeight: 300,
        opacity: ctaInView ? 1 : 0, transition: "opacity 0.8s 0.3s",
      }}>
        Join the waitlist. Be the first to get an AI marketing team that actually understands your
product.
      </p>
      <div style={{
        display: "flex", gap: 12, justifyContent: "center", maxWidth: 480, margin: "0 auto",
        opacity: ctaInView ? 1 : 0, transition: "opacity 0.8s 0.5s",
      }}>
        <input
          type="email" placeholder="you@startup.com"
          style={{
            flex: 1, padding: "16px 20px",
            background: "rgba(255,255,255,0.04)",
            border: "1px solid rgba(255,255,255,0.1)",
            borderRadius: 10, fontFamily: "'Sora'", fontSize: 15,
            color: "#F0EDE8", outline: "none",
          }}
          onFocus={e => e.target.style.borderColor = "rgba(233,69,96,0.4)"}
```

```
            onBlur={e => e.target.style.borderColor = "rgba(255,255,255,0.1)"}
          />
          <button style={{
            fontFamily: "'Sora'", fontSize: 15, fontWeight: 500,
            background: "#E94560", border: "none", borderRadius: 10,
            color: "#fff", padding: "16px 32px", cursor: "pointer",
            transition: "all 0.3s ease", whiteSpace: "nowrap",
          }}
            onMouseEnter={e => { e.target.style.boxShadow = "0 8px 32px rgba(233,69,96,0.4)"; }}
            onMouseLeave={e => { e.target.style.boxShadow = ""; }}
          >Join Waitlist</button>
        </div>
      </section>

      {/* Footer */}
      <footer style={{
        borderTop: "1px solid rgba(255,255,255,0.04)",
        padding: "40px 48px", textAlign: "center",
      }}>
        <p style={{
          fontFamily: "'JetBrains Mono'", fontSize: 12,
          color: "rgba(240,237,232,0.2)", margin: 0,
        }}>
          © 2026 ARIA. Built by founders, for founders.
        </p>
      </footer>
    </div>
  </div>
);
}
```