```
Windows IP Configuration


Wireless LAN adapter Local Area Connection* 1:

   Media State . . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 2:

   Media State . . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :

Ethernet adapter VMware Network Adapter VMnet1:

   Connection-specific DNS Suffix  . :
   Link-local IPv6 Address . . . . . : fe80::1b57:cb23:8b75:1b37%13
   IPv4 Address. . . . . . . . . . . : 192.168.102.1
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . :

Ethernet adapter VMware Network Adapter VMnet8:

   Connection-specific DNS Suffix  . :
   Link-local IPv6 Address . . . . . : fe80::c7d0:c8:d338:d271%9
   IPv4 Address. . . . . . . . . . . : 192.168.142.1
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . :

Wireless LAN adapter Wi-Fi:

   Connection-specific DNS Suffix  . : domain.name
   IPv6 Address. . . . . . . . . . . : 2401:4900:894d:19b3:6017:cbf9:cda1:7bae
   Temporary IPv6 Address. . . . . . : 2401:4900:894d:19b3:d5dd:573f:6e6e:58c0
   Link-local IPv6 Address . . . . . : fe80::54ed:eb6f:4a5d:1a8b%12
   IPv4 Address. . . . . . . . . . . : 192.168.1.7
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . : fe80::9267:17ff:fe9e:ecbb%12
                                       192.168.1.1

Ethernet adapter Ethernet:

   Media State . . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :
```

Command used: ipconfig

This command displays the network configuration details of the system on Windows.

From the output, the active interface is the **Wi-Fi adapter**, which has the IPv4 address **192.168.1.7**. This is a private IP address, indicating that the system is connected to a local network.

The default gateway is **192.168.1.1**, which represents the router through which the device accesses the internet.

Other adapters such as **VMware Network Adapter VMnet1** (192.168.102.1) and **VMnet8** (192.168.142.1) are virtual network interfaces used for virtualization and internal networking.

Some interfaces show “Media disconnected,” meaning they are currently not in use.

```
(c) Microsoft Corporation. All rights reserved.

C:\Users\Tharun varma>netstat -nr
===========================================================================
Interface List
  4...ea fb 1c cb d5 2d ......Microsoft Wi-Fi Direct Virtual Adapter
 20...ea fb 1c cb d5 3d ......Microsoft Wi-Fi Direct Virtual Adapter #2
 13...00 50 56 c0 00 01 ......VMware Virtual Ethernet Adapter for VMnet1
  9...00 50 56 c0 00 08 ......VMware Virtual Ethernet Adapter for VMnet8
 12...e8 fb 1c cb d5 2d ......MediaTek Wi-Fi 6 MT7921 Wireless LAN Card
 10...58 11 22 87 4a fc ......Realtek PCIe GbE Family Controller
  1...........................Software Loopback Interface 1
===========================================================================

IPv4 Route Table
===========================================================================
Active Routes:
Network Destination        Netmask          Gateway       Interface  Metric
          0.0.0.0          0.0.0.0      192.168.1.1      192.168.1.7     40
        127.0.0.0        255.0.0.0         On-link         127.0.0.1    331
        127.0.0.1  255.255.255.255         On-link         127.0.0.1    331
  127.255.255.255  255.255.255.255         On-link         127.0.0.1    331
      192.168.1.0    255.255.255.0         On-link       192.168.1.7    296
      192.168.1.7  255.255.255.255         On-link       192.168.1.7    296
    192.168.1.255  255.255.255.255         On-link       192.168.1.7    296
    192.168.102.0    255.255.255.0         On-link     192.168.102.1    291
    192.168.102.1  255.255.255.255         On-link     192.168.102.1    291
  192.168.102.255  255.255.255.255         On-link     192.168.102.1    291
    192.168.142.0    255.255.255.0         On-link     192.168.142.1    291
    192.168.142.1  255.255.255.255         On-link     192.168.142.1    291
  192.168.142.255  255.255.255.255         On-link     192.168.142.1    291
        224.0.0.0        240.0.0.0         On-link         127.0.0.1    331
        224.0.0.0        240.0.0.0         On-link       192.168.1.7    296
        224.0.0.0        240.0.0.0         On-link     192.168.142.1    291
        224.0.0.0        240.0.0.0         On-link     192.168.102.1    291
  255.255.255.255  255.255.255.255         On-link         127.0.0.1    331
  255.255.255.255  255.255.255.255         On-link       192.168.1.7    296
  255.255.255.255  255.255.255.255         On-link     192.168.142.1    291
  255.255.255.255  255.255.255.255         On-link     192.168.102.1    291
===========================================================================
Persistent Routes:
  None

IPv6 Route Table
===========================================================================
Active Routes:
 If Metric Network Destination      Gateway
 12    296 ::/0                     fe80::9267:17ff:fe9e:ecbb
  1    331 ::1/128                  On-link
 12    296 2401:4900:894d:19b3::/64 On-link
 12     56 2401:4900:894d:19b3::/64 fe80::9267:17ff:fe9e:ecbb
 12    296 2401:4900:894d:19b3:6017:cbf9:cda1:7bae/128
                                    On-link
 12    296 2401:4900:894d:19b3:d5dd:573f:6e6e:58c0/128
                                    On-link
 12    296 fe80::/64                On-link
  9    291 fe80::/64                On-link
 13    291 fe80::/64                On-link
 13    291 fe80::1b57:cb23:8b75:1b37/128
                                    On-link
 12    296 fe80::54ed:eb6f:4a5d:1a8b/128
                                    On-link
  9    291 fe80::c7d0:c8:d338:d271/128
                                    On-link
  1    331 ff00::/8                 On-link
 12    296 ff00::/8                 On-link
  9    291 ff00::/8                 On-link
 13    291 ff00::/8                 On-link
===========================================================================
Persistent Routes:
  None
```

Command used: netstat -nr

This command displays the routing table of the system on Windows without resolving hostnames.

From the output, the system is connected through the **Wi-Fi interface (192.168.1.7)**, which is the active network adapter.

The **default route (0.0.0.0)** points to the gateway **192.168.1.1**, meaning all external network traffic (internet) is routed through this router.

Routes such as **192.168.1.0/24** represent the local network, which is directly reachable through the Wi-Fi interface. The address **127.0.0.1** represents the loopback interface, used for internal communication within the system.

Additional routes like **192.168.102.0** and **192.168.142.0** belong to VMware virtual networks (VMnet1 and VMnet8), which are used for virtual machines and internal networking.

The IPv6 table shows similar routing, where the default route (**::/0**) points to the IPv6 gateway, enabling internet access over IPv6.

Overall, this output shows how the system directs traffic between local networks, virtual networks, and the internet.

```
C:\Users\Tharun varma>netstat -an

Active Connections

  Proto  Local Address          Foreign Address        State
  TCP    0.0.0.0:135            0.0.0.0:0              LISTENING
  TCP    0.0.0.0:445            0.0.0.0:0              LISTENING
  TCP    0.0.0.0:902            0.0.0.0:0              LISTENING
  TCP    0.0.0.0:912            0.0.0.0:0              LISTENING
  TCP    0.0.0.0:5040           0.0.0.0:0              LISTENING
  TCP    0.0.0.0:5432           0.0.0.0:0              LISTENING
  TCP    0.0.0.0:12177          0.0.0.0:0              LISTENING
  TCP    0.0.0.0:49664          0.0.0.0:0              LISTENING
  TCP    0.0.0.0:49665          0.0.0.0:0              LISTENING
  TCP    0.0.0.0:49666          0.0.0.0:0              LISTENING
  TCP    0.0.0.0:49667          0.0.0.0:0              LISTENING
  TCP    0.0.0.0:49668          0.0.0.0:0              LISTENING
  TCP    0.0.0.0:49670          0.0.0.0:0              LISTENING
  TCP    127.0.0.1:6850         0.0.0.0:0              LISTENING
  TCP    127.0.0.1:7778         0.0.0.0:0              LISTENING
  TCP    127.0.0.1:13030        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:13030        127.0.0.1:49669        ESTABLISHED
  TCP    127.0.0.1:13031        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:13032        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:22112        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:24830        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:27275        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:27339        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:49669        127.0.0.1:13030        ESTABLISHED
  TCP    127.0.0.1:49676        127.0.0.1:50100        ESTABLISHED
  TCP    127.0.0.1:50100        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:50100        127.0.0.1:49676        ESTABLISHED
  TCP    127.0.0.1:50923        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:51100        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:52892        127.0.0.1:52893        ESTABLISHED
  TCP    127.0.0.1:52893        127.0.0.1:52892        ESTABLISHED
  TCP    127.0.0.1:59104        127.0.0.1:61503        ESTABLISHED
  TCP    127.0.0.1:61503        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:61503        127.0.0.1:59104        ESTABLISHED
  TCP    127.0.0.1:61504        127.0.0.1:65001        ESTABLISHED
  TCP    127.0.0.1:65001        0.0.0.0:0              LISTENING
  TCP    127.0.0.1:65001        127.0.0.1:61504        ESTABLISHED
  TCP    192.168.1.7:139        0.0.0.0:0              LISTENING
  TCP    192.168.1.7:51526      204.79.197.222:443     ESTABLISHED
  TCP    192.168.1.7:51530      71.18.1.211:443        CLOSE_WAIT
  TCP    192.168.1.7:51542      23.46.187.137:443      ESTABLISHED
  TCP    192.168.1.7:53526      166.108.200.175:443    CLOSE_WAIT
  TCP    192.168.1.7:53527      166.108.200.175:443    CLOSE_WAIT
  TCP    192.168.1.7:53529      166.108.200.175:443    CLOSE_WAIT
  TCP    192.168.1.7:53531      166.108.200.175:443    CLOSE_WAIT
  TCP    192.168.1.7:53532      166.108.200.175:443    CLOSE_WAIT
  TCP    192.168.1.7:54229      34.141.85.170:443      ESTABLISHED
  TCP    192.168.1.7:54529      71.18.1.232:443        CLOSE_WAIT
```

Command used: netstat -an

This command displays all active network connections and listening ports on the system, showing addresses in numerical form without resolving hostnames.

From the output, several ports such as **135, 445, 902, 5432** are in the **LISTENING** state, meaning the system is waiting for incoming connections on these ports. These are typically used by system services, file sharing (SMB), virtualization (VMware), and database services (PostgreSQL).

Connections with **127.0.0.1 (localhost)** indicate internal communication within the system. These are processes communicating locally and are not exposed to external networks.

The system's IP **192.168.1.7** shows multiple **ESTABLISHED** connections to external servers over port **443 (HTTPS)**, indicating active secure internet communication such as browsing or background services.

Some connections are in states like:

- **ESTABLISHED** – active communication is ongoing
- **LISTENING** – waiting for incoming connections
- **CLOSE_WAIT / TIME_WAIT** – connections are closing or recently closed

Entries with **192.168.102.1** and **192.168.142.1** correspond to VMware virtual network adapters used for virtual machines.

UDP entries show connectionless communication used for services like DNS, streaming, and system broadcasts. Ports like **5353 (mDNS)** and **1900 (UPnP)** are used for local network discovery.

Overall, this output provides a complete view of open ports, active connections, and network activity on the system.

```
C:\Users\Tharun varma>ping google.com

Pinging google.com [2404:6800:4009:809::200e] with 32 bytes of data:
Reply from 2404:6800:4009:809::200e: time=49ms
Reply from 2404:6800:4009:809::200e: time=36ms
Reply from 2404:6800:4009:809::200e: time=54ms
Reply from 2404:6800:4009:809::200e: time=52ms

Ping statistics for 2404:6800:4009:809::200e:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 36ms, Maximum = 54ms, Average = 47ms
```

Ping Test (google.com)
Command used: ping google.com
The ping command is used to test connectivity between my system and a remote server. From the output, my
system successfully communicated with Google's server (142.250.183.174) with 0% packet loss, which means
the connection is stable.
The response time (latency) varies, with an average of around 24 ms, indicating a good network connection.
Lower response times mean faster communication between my system and the server.

```
C:\Users\Tharun varma>tracert google.com

Tracing route to google.com [2404:6800:4009:809::200e]
over a maximum of 30 hops:

  1     8 ms    34 ms     1 ms  2401:4900:894d:19b3:9267:17ff:fe9e:ecbb
  2     *        *        *     Request timed out.
  3     6 ms    25 ms    11 ms  2404:a800:3a00::4b9
  4    41 ms    17 ms    64 ms  2404:a800::92
  5    35 ms    17 ms    41 ms  2001:4860:1:1::674
  6    38 ms    37 ms    60 ms  2404:6800:8202:2c0::1
  7    47 ms    31 ms    14 ms  2001:4860:0:1::5666
  8    15 ms    13 ms    26 ms  2001:4860:0:1::882a
  9    29 ms    30 ms    37 ms  2001:4860::c:4004:53be
 10    51 ms    57 ms    37 ms  2001:4860::9:4002:d931
 11    41 ms   100 ms    40 ms  2001:4860:0:1::3fe5
 12    28 ms    55 ms    27 ms  2001:4860:0:1::5ed3
 13    52 ms    44 ms    32 ms  bom05s11-in-x0e.1e100.net [2404:6800:4009:809::200e]

Trace complete.
```

Command used: tracert google.com

This command traces the route taken by packets from your system to **google.com**, showing each hop along the path.

From the output, the destination resolves to an IPv6 address **2404:6800:4009:809::200e**, indicating that your system is using IPv6 for communication.

- **Hop 1** (2401:4900:…): This is your **local router**, the first point of contact from your network.
- **Hop 2**: Shows Request timed out, which means that router is not responding to ICMP requests (common and not an issue).
- **Hops 3–4**: These belong to your **ISP network**, routing traffic outside your local network.
- **Hops 5–12**: These are part of **Google's backbone network** (addresses starting with 2001:4860::), showing the packet traveling within Google's infrastructure.

- **Hop 13**: Final destination (**bom05s11-in-x0e.1e100.net**) which is a Google server, likely located in Mumbai (based on “bom”).

The response times (in ms) indicate latency at each hop, generally staying within a reasonable range, meaning the connection is stable.

The trace completes successfully, showing that packets reach the destination without major issues.