KRINI CRUDE • 1-COOL

INDUSTRIAL CHEMICALS • LUBRICANTS DIVISION

1-COOL AL 7000

Premium Semi Synthetic Coolant Oil. Soluble cutting oils are mixed with water to make a coolant. The coolant carries heat away from the cutting zone, lubricates, flushes away chips and helps protect parts and machines from rust.

KEY FEATURES & BENEFITS

- Premium industrial grade formulation manufactured in Chennai
- Consistent batch-to-batch quality and high thermal stability
- Engineered for optimal operational efficiency and equipment protection

APPLICATIONS & USES

- Turning, milling, drilling and other machining with a coolant system
- Operations where cooling matters as much as lubrication

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Appearance	Clear amber / yellow fluid	Visual
Kinematic Viscosity @ 40°C	Typical: 32 - 68 cSt	ASTM D445
Density @ 29.5°C	0.850 - 0.890 g/cm³	ASTM D1298
Flash Point (COC)	> 200 °C	ASTM D92
Copper Strip Corrosion	1a (Passes)	ASTM D130

APPLICATION & HANDLING GUIDELINES

- Ensure contact surfaces or machines are clean and free of heavy contaminants.
- Apply as supplied without unauthorized dilution or contamination.
- Conduct a preliminary trial under site conditions to calibrate optimum consumption.

Packaging: Standard industrial packaging: 20 L pails, 200 L / 210 L steel drums. • **Storage:** Store in original tightly sealed containers in a cool, dry and well-ventilated area away from direct sunlight. • **Shelf Life:** 12 months from date of manufacture when stored in unopened containers as recommended.

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.