KRINI CRUDE • VIBRANT

INDUSTRIAL CHEMICALS • AEROSOLS DIVISION

Any RAL Shades

VIBRANT CUSTOM SHADE AEROSOL SPRAY PAINT is a professional-grade custom color-matched spray paint prepared to any requested RAL shade code. Specially formulated with quick-drying industrial resins, it provides precise color matching to powder coatings, painted equipment, and architectural standards with exceptional finish uniformity and weather durability.

KEY FEATURES & BENEFITS

- Exact shade replication matching powder-coated installations and architectural components
- Rapid touch-dry formulation minimizes production turnaround and downtime
- Available in high-gloss, satin, or semi-matt finish sheens upon request
- Eco-friendly, ozone-safe propellant formulation with zero CFCs or lead
- Long service life with high UV color fastness

APPLICATIONS & USES

- Precise RAL Matching: Matched to any classic RAL colour code (e.g., RAL 7035, RAL 9010, RAL 5015)
- Touch-Up & Finishing: Seamless touch-up on powder-coated fabrications, panels, enclosures, and equipment
- Indoor & Outdoor Durability: Resists UV degradation, fading, moisture, and temperature fluctuations
- Multi-Substrate Adhesion: Bonds firmly to steel, aluminium, plastics, wood, and pre-painted surfaces
- Consistent Spray Pattern: Uniform mist delivers factory-level finish without runs, drips, or blotches

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Product Type	Custom-Matched Acrylic Aerosol Paint	—
Color Range	Any RAL Classic Shade (Custom Formulation)	—
Drying Time	Touch dry in 10–15 min; Full cure in 24 hrs	—
Finish Options	Glossy / Satin / Matt (As per specification)	—
Weather & UV Resistance	High / Exterior Grade	—
Application Method	Aerosol Spray (Uniform fan pattern)	—

APPLICATION & HANDLING GUIDELINES

- Ensure surfaces are dry, clean, and free of dust, grease, rust, and contaminants.
- Shake the aerosol can vigorously for at least 1 minute after the agitator ball starts rattling.
- Test spray on a small test piece to verify color match before primary application.
- Apply in 2–3 light, even coats holding the can 20–25 cm away in smooth, overlapping strokes.

Packaging: Standard packing: 400 ml aerosol spray cans (Cartons of 12 / 24 cans) • **Storage:** Store below 50 °C in a cool, dry, well-ventilated area away from direct sunlight and heat sources. • **Shelf Life:** 24 months from date of manufacture

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.