KRINI CRUDE • VIBRANT

INDUSTRIAL CHEMICALS • AEROSOLS DIVISION

Black (Glossy/Matt)

VIBRANT BLACK SPRAY PAINT is a premium acrylic-based aerosol spray paint formulated for indoor and outdoor applications. Engineered with fast-drying resins and deep pigment technology, it delivers a smooth, uniform, and durable coating available in deep glossy and sleek matt black finishes.

KEY FEATURES & BENEFITS

- Smooth, professional spray pattern with minimal overspray
- Available in both high-sheen Glossy Black and sophisticated Matt Black finishes
- Strong adhesion on clean ferrous and non-ferrous surfaces
- CFC-free propellant system safe for ozone layer
- Long-lasting colour retention without fading

APPLICATIONS & USES

- Indoor & Outdoor Use: High resistance to weathering, UV exposure, and environmental moisture
- Fast Drying: Dries to touch rapidly, enabling faster assembly and reduced handling downtime
- Excellent Coverage: High-opacity formulation masks underlying substrates with fewer coats
- Durable Coating: Resists chipping, peeling, and mild abrasion across metal, wood, and plastic surfaces
- Touch-Up & Finishing: Ideal for powder-coated equipment, fabricated metal parts, and maintenance touch-ups

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Product Type	Acrylic Aerosol Spray Paint	—
Finish Options	Glossy Black / Matt Black	—
Drying Time	Touch dry in 10–15 min; Full cure in 24 hrs	—
Application Area	Indoor and Outdoor	—
Corrosion & UV Resistance	Excellent	—
Substrates	Mild steel, fabricated metal, wood, ABS plastics	—

APPLICATION & HANDLING GUIDELINES

- Clean surface thoroughly: remove oil, grease, rust, dirt, and moisture before spraying.
- Shake the can vigorously for at least 1 minute after the mixing ball begins to rattle.
- Hold can upright 20–30 cm from surface and apply in light, even coats using a sweeping motion.
- Apply 2–3 thin coats rather than one heavy coat, waiting 2–5 minutes between passes.

Packaging: Standard packing: Aerosol spray cans (Cartons of 12 / 24 cans) • **Storage:** Store below 50 °C in a cool, dry, well-ventilated area away from direct sunlight, sparks, and open flames. Pressurized container: do not puncture or incinerate. • **Shelf Life:** 24 months from date of manufacture when properly stored

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.