KRINI CRUDE • VIBRANT

INDUSTRIAL CHEMICALS • AEROSOLS DIVISION

Galva Zinc Spray

VIBRANT BRIGHT GALVA COATING is a high-performance zinc-rich cold galvanizing aerosol spray formulated with boosted zinc protection. It provides cathodic rust and corrosion defense for all ferrous metal surfaces, fabricated structural steelwork, weld seams, and cut edges, delivering a clean, bright metallic zinc finish.

KEY FEATURES & BENEFITS

- Prevents rust and galvanic corrosion in harsh industrial and coastal environments
- Excellent adhesion on bare steel, weathered galvanizing, and cleaned ferrous metals
- Can be used as a standalone protective coating or as a rust-inhibiting primer
- Smooth, even spray pattern eliminates drip marks and uneven build-up
- Formulated with ozone-friendly propellants and Krini Crude quality assurance

APPLICATIONS & USES

- Boosted Zinc Protection: High zinc concentration delivers galvanic and barrier corrosion defense
- Bright Galva Finish: Matches the visual sheen of freshly hot-dip galvanized steelwork
- Weld Seam & Cut Edge Repair: Seals cut edges, drill holes, and welded joints after fabrication
- Cathodic Electrochemical Protection: Sacrificial zinc action prevents rust creep under scratches
- Fast Drying Formulation: Dries quickly for rapid handling, transport, or recoating

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Product Type	Cold Galvanizing Zinc Aerosol Coating	—
Net Weight	300 Gms	—
Protection Type	Cathodic / Electrochemical Sacrificial	—
Finish / Sheen	Bright Metallic Zinc	—
Drying Time	Touch dry in 15 min; Full cure in 24 hrs	—
Corrosion Resistance	Boosted Zinc Barrier Protection	—

APPLICATION & HANDLING GUIDELINES

- Remove heavy rust, scale, grease, and dirt; abrade bare steel lightly for optimal adhesion.
- Shake can vigorously for at least 2 minutes after the agitator ball is heard.
- Hold upright 20–25 cm from the surface and spray in light, overlapping passes.
- Apply 2 uniform coats allowing 10–15 minutes flash-off between coats.

Packaging: Standard packing: 300 gms aerosol spray cans (Cartons of 12 / 24 cans) • **Storage:** Store in a cool, dry, well-ventilated area below 50 °C away from direct sunlight, ignition sources, and open flames. • **Shelf Life:** 24 months from date of manufacture

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.