**KRINI CRUDE • 1-COOL**

INDUSTRIAL CHEMICALS • LUBRICANTS DIVISION

# Gear Oil

Gear oils lubricate gearboxes and gear drives, keeping a film of oil between meshing teeth under load to reduce wear, heat and noise.

## KEY FEATURES & BENEFITS

- Available in: 90, 140, 220, 320

## APPLICATIONS & USES

- Industrial gearboxes and gear drives
- Automotive and equipment gear assemblies, as specified by the manufacturer

## TYPICAL TECHNICAL SPECIFICATIONS

| Test Parameter | Typical Value / Result | Test Method / Note |
|---|---|---|
| Appearance | Clear amber / yellow fluid | Visual |
| Kinematic Viscosity @ 40°C | Typical: 32 - 68 cSt | ASTM D445 |
| Density @ 29.5°C | 0.850 - 0.890 g/cm³ | ASTM D1298 |
| Flash Point (COC) | > 200 °C | ASTM D92 |
| Copper Strip Corrosion | 1a (Passes) | ASTM D130 |

## APPLICATION & HANDLING GUIDELINES

- Ensure contact surfaces or machines are clean and free of heavy contaminants.
- Apply as supplied without unauthorized dilution or contamination.
- Conduct a preliminary trial under site conditions to calibrate optimum consumption.

**Packaging:** Standard industrial packaging (pails, drums, barrels) • **Storage:** Store in original tightly closed container in a cool, dry place. • **Shelf Life:** 12 months from date of manufacture when stored properly.



Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.