KRINI SHUTTERING GREASE®

PDS- CALCIUM BASED SHUTTERING GREASE

PERFORMANCE:

1. Provides easy application and user friendly [non hazardous]
2. Provides smooth release from wall ties, sleeves and other Shuttering works
3. Used as mold release agent for critical or corner structures [where mold oil performance is low]
4. Non stainable finishing on concrete
5. Does not leave any residue or powder after demolding

PHYSICAL CHARACTERISTICS:

- Calcium & Oil based grease [Non powder or lesser filler - type grease].
- Mild odor – characteristic smell [Non solvent smell] and non-combustible.
- User friendly for Human skins [Non hazardous]

CHEMICAL CHARACTERISTICS

SL NO	CHARACTERISTICS	UNIT OF MEASUREMENT	TEST RESULT
1	APPEARANCE	-NIL-	GREASE
2	COLOUR	-NIL-	BROWN
3	BOILING POINT	°C	>300
4	FLASH POINT	°C	>230
5	AUTO IGNITION TEMPERATURE	°C	>300
6	SOLUBILITY	-NIL-	INSOLUBLE IN WATER
7	RELATIVE DENSITY	-NIL-	0.910

STABILITY: Stable under normal temperature conditions.

STORAGE: Avoid excessive heat for prolonged periods of time.