KRINI CRUDE • VIBRANT

INDUSTRIAL CHEMICALS • AEROSOLS DIVISION

Lock-Bond Adhesive Spray 400ml

LOCK-BOND ADHESIVE SPRAY is a premium multi-purpose industrial aerosol adhesive formulated for fast tack, high bonding strength, and long-lasting durability across a wide spectrum of materials. It is non-toxic, ozone-friendly, CFC and lead-free, ensuring safe handling in manufacturing, workshop assembly, and industrial maintenance.

KEY FEATURES & BENEFITS

- Instant tack with strong, permanent or repositionable adhesion
- Clean spray pattern prevents bleed-through and wrinkling
- Non-toxic and eco-conscious formulation with zero CFCs or lead
- Long shelf life and dependable spray valve performance
- Ideal for automotive interiors, upholstery, packaging, and sign-making

APPLICATIONS & USES

- Multi Purpose Adhesive Spray: Bonds paper, cardboard, fabric, foam, plastics, leather, foil, wood & metals
- Lasts Longer: Formulated for enduring bond durability under industrial conditions
- Non-Toxic: Safe formulation for workplace and operator handling
- Ozone Friendly: 100% CFC and lead free propellant system
- Fast Tack & Rapid Bonding: High initial adhesion reducing clamping and setup times

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Product Type	Aerosol Spray Adhesive	—
Net Volume	400 ml	—
Tack Type	Fast tack / High initial grab	—
Toxicity	Non-Toxic	—
Environmental Safety	Ozone Friendly (CFC & Lead Free)	—
Propellant	Eco-friendly hydrocarbon aerosol	—

APPLICATION & HANDLING GUIDELINES

- Shake the can vigorously for 15–30 seconds before spraying.
- Ensure surfaces to be bonded are clean, dry, and free from oil, grease, or dust.
- Hold the can upright approximately 20–25 cm (8–10 inches) from the target surface.
- Depress the actuator nozzle firmly and apply an even, overlapping coat.

Packaging: Standard packing: 400 ml aerosol spray cans (Cartons of 12 / 24 cans) • **Storage:** Store in a cool, well-ventilated dry area below 50 °C (122 °F). Keep away from open flames, heat sources, and direct sunlight. Pressurized container: do not pierce or incinerate. • **Shelf Life:** 24 months from date of manufacture when stored properly

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.