KRINI CRUDE

SPECIALITY CONSTRUCTION CHEMICALS

MAGIC SHUTTERING OIL

HIGH-PERFORMANCE RELEASE OIL FOR MIVAN FORMWORK

Magic Shuttering Oil is a ready-to-use release oil developed for Mivan aluminium formwork. It forms a thin, uniform release film that supports clean demoulding, smooth concrete finishes and efficient reuse of formwork when applied correctly.

AVERAGE COVERAGE

30-40 m²/L

Actual coverage may vary with formwork porosity, surface condition and application method.

KEY BENEFITS

- Excellent release performance on Mivan aluminium formwork
- Clean demoulding with reduced adhesion to the formwork
- Promotes a smooth and uniform concrete surface finish
- Helps reduce concrete build-up and simplifies cleaning
- Ready to use with economical spreading coverage



TYPICAL PROPERTIES

Appearance	Brown transparent liquid
Kinematic viscosity at 40°C	Typical: 32 cSt (specification: >12 cSt)
Density at 15°C	Typical: 0.88 g/mL (specification: >0.80 g/mL)
Flash point, Pensky-Martens	Typical: 180°C (specification: >100°C)
Coverage	30-40 m²/L

APPLICATION METHOD

- Clean the formwork and remove concrete residue, rust, dust, water and excess oil.
- Apply a very thin, uniform film by fine spray, lint-free cloth, roller or suitable applicator.
- Avoid puddles and over-application; wipe off excess oil before placing reinforcement or concrete.
- Conduct a small site trial to establish the optimum application rate for site conditions.

STORAGE, HANDLING & PACKING

Store in the original closed container in a cool, dry, well-ventilated area away from heat and direct sunlight.
Use appropriate gloves and eye protection. Avoid prolonged skin contact. Refer to the Safety Data Sheet before use.
Shelf life: 12 months from date of manufacture when stored as recommended. Standard packing: 200 L barrel.

Typical values are not guaranteed specifications. Suitability and coverage should be confirmed by a site trial under actual conditions.