Mold Release Oil

Mold (mould) release oil is applied to moulds so that cast concrete units come away cleanly, with a good surface finish, and the moulds can be reused.

KEY FEATURES & BENEFITS

- Formulated not just as physical release but also chemically engineered for superior performance and concrete finish.

APPLICATIONS & USES

- Precast concrete moulds
- Moulded concrete products

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Appearance	Uniform release fluid / grease	Visual
Coverage Rate	30–40 m²/L	Site trial rate
Formwork Compatibility	Mivan aluminium, MS, plywood, FRP	All moulds
Flash Point	> 140 °C	Safety standard
Demoulding Performance	Smooth concrete finish, clean strip	Field tested

APPLICATION & HANDLING GUIDELINES

- Ensure contact surfaces or machines are clean and free of heavy contaminants.
- Apply as supplied without unauthorized dilution or contamination.
- Conduct a preliminary trial under site conditions to calibrate optimum consumption.

Packaging: Standard industrial packaging (pails, drums, barrels) • **Storage:** Store in original tightly closed container in a cool, dry place. • **Shelf Life:** 12 months from date of manufacture when stored properly.

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.